



K2A40U2N, AL Universal Terminal, 2-Conductor, 2-Hole

By Burndy
Catalog # [K2A40U2N](#)

2-Conductor, 2-Hole, 1/2" Stud, 1.75" Spacing, 300-800 kcmil, Dual Rated,Tin Plated



Features

- Dual rated panelboard lugs
- Constructed from high strength, extruded aluminum alloy
- Electro tin-plated to provide low contact resistance

Application

For Aluminum and Copper Conductors

Specifications

Certification - UL Recognized	No
Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	No
Industry Standard(s)	UL 486A-486B
Certification - ETL	No
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	NC
Certification - UL Listed Direct Burial	No
UL Listed	Yes
Certification - CSA Approved	Yes

Conductor

Conductor - AL Str Size	• 300 kcmil • 336 kcmil • 350 kcmil • 397 kcmil • 400 kcmil • 450 kcmil • 477 kcmil • 500 kcmil • 550 kcmil • 556 kcmil • 600 kcmil • 636 kcmil • 650 kcmil • 700 kcmil • 715 kcmil • 750 kcmil • 795 kcmil • 800 kcmil
Conductor - AL Str Size Range	300-800 kcmil
Conductor - Copper Str Size	• 300 kcmil

Conductor Size	300-800 KCMIL
Number Of Conductors	2
Conductor Type	• AL C Str-Size • CU C Str-Size
Conductor - Copper Str Size Range	300-800 kcmil

Configuration

Physical Attribute - Number of Holes	2
Connector Type	Parallel Set-Screw

Dimensions

Dimension - Pad Width inch	3.20 in
Package Height	2.400 in
Dimension - Height mm	49.5 mm
Dimension - Height inch	1.95 in
Dimension - Height fraction	2 in
Package Weight	3.710 lb.
Package Length	10.000 in
Package Width	5.600 in
Dimension - L Length Overall mm	121 mm
Dimension - Width fraction	3-19/100 in
Dimension - Hole Size mm	14 mm
Dimension - Hole Size inch	0.56 in
Dimension - Screw Size inch	3/8
Dimension - Stud Size inch	1/2 in
Dimension - Bolt Hole Size inch	0.50 in
Dimension - Bolt Size fraction	1/2
Dimension - Width mm	81 mm
Dimension - Width inch	3.20 in
Dimension - D inch	3.03 in
Dimension - N inch	0.63 in
Dimension - Length Overall inch	4.75 in

Force Related

Installation Torque 375 LBS/in
Recommended in-lb

General

Material - Hardware Aluminum
Physical Attribute - Screw Type Slot
Plated N
Sub Brand UNIVERSAL TERM
UPC 781810600405
Type Bolted Lugs & Terminals
Material Aluminum
Plating Type Tin plated
UPC 12 Digit 781810600405



A Hubbell brand

Hardware Type 3/8 UNC Slotted Set Screw
UPC 14 Digit GTIN 00781810600405

Logistics

Minimum Pack Quantity 1
Pallet Quantity 30
Carton Quantity 30

Operational

Temperature Rating 194

Product Assets

[Catalog \[English\]](#)