

8767 B VDE HF TORX® Zyklop bit socket, insulated, with holding function, 3/8"
drive, TX 27 x 55 mm



| | | | |
|------------------------|---------------|-------------------------------|-------------|
| EAN: | 4013288210197 | Size: | 56x23x23 mm |
| Part number: | 05004922001 | Weight: | 47 g |
| Article number: | 8767 B VDE HF | Country of origin: | CZ |
| | | Customs tariff number: | 82079030 |

- Individually tested tools as per IEC 60900 at 10,000 V for safe working up to 1,000 volt
- Extremely short and compact insulated 3/8" bit socket for easy working even in very confined spaces
- Increased safety thanks to 2-component insulation with a yellow insulation core under an outer red insulation layer
- The holding function holds screws securely on the tool
- Plastic sleeve protects surfaces from damage

VDE 3/8" bit socket with holding function for particularly comfortable screwdriving with reduced risk of screw loss when feeding to the component. With increased safety due to yellow insulation core, which becomes visible in case of damage to the outer red VDE insulation layer. Individually tested tool as per IEC 60900 at 10,000 V for safe working at the approved voltage of 1,000 V.

Web link
<https://www.wera.de/en/05004922001>

Wera - 8767 B VDE HF
05004922001 - 4013288210197

Wera Werkzeuge GmbH
Korzter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

Increased safety







The Zyklop sockets and extensions for electricians offer increased safety thanks to their 2-component insulation with a yellow insulation core under an outer red insulation layer.

Bit sockets with holding function for TORX® screws



The HF tools developed by Wera are ideal because they feature an optimised geometry of the original TORX® profile. The wedging forces resulting from the surface pressure between the drive tip and the screw profile mean that TORX® screws made according to Camcar Innovations, Michigan, USA specifications are securely held on the tool!

Further versions in this product family:

| |  |  |  |  |
|--------------------|---|---|---|---|
| | | mm | mm | mm |
| 05004920001 | TX 20 | 55.0 | 23.0 | 9.0 |
| 05004921001 | TX 25 | 55.0 | 23.0 | 9.0 |
| 05004922001 | TX 27 | 55.0 | 23.0 | 9.0 |
| 05004923001 | TX 30 | 55.0 | 23.0 | 9.0 |
| 05004924001 | TX 40 | 55.0 | 23.0 | 9.0 |
| 05004925001 | TX 45 | 59.0 | 23.0 | 13.0 |

Web link

<https://www.wera.de/en/05004922001>

Wera - 8767 B VDE HF
05004922001 - 4013288210197

Wera Werkzeuge GmbH
Korzter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de