

SECTION 1: Identification

1.1. Identification

Product form : Mixture
 Trade name : REVvive by RSG Matte Trim Black
 Other means of identification : UPC - 66623391014

1.2. Recommended use and restrictions on use

Recommended use : For professional use only

1.3. Supplier

United States

Saint-Gobain Abrasives Inc
 1 New Bond Street
 Worcester, MA 01615
 T 800-551-4413
www.Nortonabrasives.com

1.4. Emergency telephone number

Emergency number : 508-795-5000. For emergencies in the US call 800-424-9300

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS Classification

Flammable aerosol Category 1	Extremely flammable aerosol
Serious eye damage/eye irritation Category 2	Causes serious eye irritation
Skin sensitization, Category 1	May cause an allergic skin reaction
Specific target organ toxicity (single exposure) Category 3	May cause drowsiness or dizziness

2.2. GHS Label elements, including precautionary statements

GHS Labelling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : Extremely flammable aerosol
 May cause an allergic skin reaction
 Causes serious eye irritation
 May cause drowsiness or dizziness

Precautionary statements (GHS-US) : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 Pressurized container: Do not pierce or burn, even after use.
 Avoid breathing spray, vapors, fume.
 Wear eye protection, protective gloves, protective clothing.
 If on skin: Wash with plenty of water
 IF IN EYES: Rinse first with plenty of water and if necessary take medical advice
 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

REVvive by RSG Matte Trim Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS-US classification
methyl acetate	(CAS-No.) 79-20-9	5 - 23	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
acetone	(CAS-No.) 67-64-1	5 - 23	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
xylene	(CAS-No.) 1330-20-7	< 5	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315
ethyl methyl ketone	(CAS-No.) 78-93-3	< 5	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
solvent naphtha (petroleum), light aromatic	(CAS-No.) 64742-95-6	< 5	Flam. Liq. 3, H226 STOT SE 3, H336 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
cyclohexanone	(CAS-No.) 108-94-1	< 5	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Dam. 1, H318
reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)		< 5	Skin Sens. 1, H317 Aquatic Chronic 2, H411

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

- First-aid measures general : Call a poison center/doctor/physician if you feel unwell.
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
- First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

- Symptoms/effects : May cause drowsiness or dizziness.
- Symptoms/effects after skin contact : May cause an allergic skin reaction.
- Symptoms/effects after eye contact : Eye irritation.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

- Fire hazard : Extremely flammable aerosol.
- Explosion hazard : Pressurized container: may burst if heated.
- Reactivity : Extremely flammable aerosol. Pressurized container: may burst if heated.

5.3. Special protective equipment and precautions for fire-fighters

- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

REVvive by RSG Matte Trim Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing spray, fume, vapors. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Mechanically recover the product.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing vapors, spray, fume. Avoid contact with skin and eyes. Wear personal protective equipment.

Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

ethyl methyl ketone (78-93-3)		
ACGIH	Local name	Methyl ethyl ketone (MEK)
ACGIH	ACGIH TWA (ppm)	200 ppm
ACGIH	ACGIH STEL (ppm)	300 ppm
ACGIH	Remark (ACGIH)	URT irr; CNS & PNS impair
ACGIH	Regulatory reference	ACGIH 2018
OSHA	OSHA PEL (TWA) (mg/m ³)	590 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	200 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA
solvent naphtha (petroleum), light aromatic (64742-95-6)		
Not applicable		
xylene (1330-20-7)		
ACGIH	Local name	Xylene
ACGIH	ACGIH TWA (ppm)	100 ppm
ACGIH	ACGIH STEL (ppm)	150 ppm
ACGIH	Remark (ACGIH)	URT & eye irr; CNS impair
ACGIH	Regulatory reference	ACGIH 2018
OSHA	OSHA PEL (TWA) (mg/m ³)	435 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	100 ppm

REVvive by RSG Matte Trim Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

xylene (1330-20-7)		
OSHA	Regulatory reference (US-OSHA)	OSHA
reaction mass of α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-hydroxypoly(oxyethylene) and α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)		
Not applicable		
cyclohexanone (108-94-1)		
ACGIH	Local name	Cyclohexanone
ACGIH	ACGIH TWA (ppm)	20 ppm
ACGIH	ACGIH STEL (ppm)	50 ppm
ACGIH	Remark (ACGIH)	Eye & URT irr
ACGIH	Regulatory reference	ACGIH 2018
OSHA	OSHA PEL (TWA) (mg/m ³)	200 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	50 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA
methyl acetate (79-20-9)		
ACGIH	Local name	Methyl acetate
ACGIH	ACGIH TWA (ppm)	200 ppm
ACGIH	ACGIH STEL (ppm)	250 ppm
ACGIH	Remark (ACGIH)	eye & URT irr
ACGIH	Regulatory reference	ACGIH 2018
OSHA	OSHA PEL (TWA) (mg/m ³)	610 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	200 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA
acetone (67-64-1)		
ACGIH	Local name	Acetone
ACGIH	ACGIH TWA (ppm)	250 ppm
ACGIH	ACGIH STEL (ppm)	500 ppm
ACGIH	Remark (ACGIH)	eye irr; CNS impair; BEI
ACGIH	Regulatory reference	ACGIH 2018
OSHA	OSHA PEL (TWA) (mg/m ³)	2400 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

REVvive by RSG Matte Trim Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

In case of insufficient ventilation, wear suitable respiratory equipment

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Black
Odor	: There may be no odour warning properties, odour is subjective and inadequate to warn of overexposure. Mixture contains one or more component(s) which have the following odour: Sweet odour Acetone odour Pleasant odour Aromatic odour Petroleum-like odour Almost odourless Fruity odour Peppermint odour Mild odour Ether-like odour Odourless Commercial/unpurified substance: unpleasant odour
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: -60 °C
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Extremely flammable aerosol.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Specific gravity / density	: 0.732 g/cm ³
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: Pressurized container: may burst if heated.
Oxidizing properties	: No data available

9.2. Other information

VOC content	: 660 g/l
MIR	: 1.7

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurized container: may burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

REVvive by RSG Matte Trim Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Acute toxicity : Not classified

ethyl methyl ketone (78-93-3)	
LD50 oral rat	2193 mg/kg body weight (Equivalent or similar to OECD 423, Rat, Male/female, Read-across)
LD50 dermal rabbit	> 10 ml/kg (Equivalent or similar to OECD 402, 24 h, Rabbit, Male, Experimental value)
ATE US (oral)	2193 mg/kg body weight

xylene (1330-20-7)	
LD50 oral rat	3523 mg/kg body weight (Equivalent or similar to EU Method B.1: Acute Toxicity (Oral), Rat, Male, Experimental value)
ATE US (oral)	3523 mg/kg body weight
ATE US (dermal)	1100 mg/kg body weight
ATE US (dust, mist)	1.5 mg/l/4h

cyclohexanone (108-94-1)	
LD50 oral rat	1890 mg/kg body weight (BASF test, Rat, Experimental value)
LC50 inhalation rat (mg/l)	> 6.2 mg/l air (BASF test, 4 h, Rat, Male/female, Experimental value)
ATE US (oral)	1890 mg/kg body weight
ATE US (dermal)	1100 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h

methyl acetate (79-20-9)	
LD50 oral rat	6482 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male, Experimental value)
LD50 dermal rat	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male/female, Experimental value)
ATE US (oral)	6482 mg/kg body weight

acetone (67-64-1)	
LD50 oral rat	5800 mg/kg (Equivalent or similar to OECD 401, Rat, Female, Experimental value)
LD50 dermal rabbit	20000 mg/kg (Equivalent or similar to OECD 402, Rabbit, Male, Experimental value)
LC50 inhalation rat (mg/l)	76 mg/l (Other, 4 h, Rat, Female, Experimental value)
ATE US (oral)	5800 mg/kg body weight
ATE US (dermal)	20000 mg/kg body weight
ATE US (vapors)	76 mg/l/4h
ATE US (dust, mist)	76 mg/l/4h

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Causes serious eye irritation.
Respiratory or skin sensitization : May cause an allergic skin reaction.
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

xylene (1330-20-7)	
IARC group	3 - Not classifiable

cyclohexanone (108-94-1)	
IARC group	3 - Not classifiable

Reproductive toxicity : Not classified
Specific target organ toxicity – single exposure : May cause drowsiness or dizziness.

Specific target organ toxicity – repeated exposure : Not classified

Aspiration hazard : Not classified
Symptoms/effects : May cause drowsiness or dizziness.
Symptoms/effects after skin contact : May cause an allergic skin reaction.

REVvive by RSG Matte Trim Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/effects after eye contact : Eye irritation.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

ethyl methyl ketone (78-93-3)	
LC50 fish 1	2993 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Pimephales promelas, Static system, Fresh water, Experimental value)
EC50 Daphnia 1	308 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value)
ErC50 (algae)	1972 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value)

xylene (1330-20-7)	
LC50 fish 1	2.6 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Read-across)
EC50 Daphnia 1	3.82 mg/l (48 h, Daphnia magna, Flow-through system, Fresh water, Read-across)

reaction mass of α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-hydroxypoly(oxyethylene) and α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)	
LC50 fish 1	2.8 mg/l (96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value)
EC50 Daphnia 1	4 mg/l (48 h, Daphnia magna, Static system, Fresh water, Experimental value)
ErC50 (algae)	> 100 mg/l (72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value)

cyclohexanone (108-94-1)	
LC50 fish 1	527 - 732 mg/l (US EPA, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value)
EC50 Daphnia 1	> 100 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Read-across)
ErC50 (algae)	> 100 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Read-across)

methyl acetate (79-20-9)	
LC50 fish 1	250 - 350 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Brachydanio rerio, Static system, Fresh water, Experimental value)
EC50 Daphnia 1	1026.7 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value)

acetone (67-64-1)	
LC50 fish 1	5540 mg/l (EU Method C.1, 96 h, Salmo gairdneri, Static system, Fresh water, Experimental value)

12.2. Persistence and degradability

ethyl methyl ketone (78-93-3)	
Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	2.03 g O ₂ /g substance
Chemical oxygen demand (COD)	2.31 g O ₂ /g substance
ThOD	2.44 g O ₂ /g substance

solvent naphtha (petroleum), light aromatic (64742-95-6)	
Persistence and degradability	May cause long-term adverse effects in the environment.

xylene (1330-20-7)	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.

cyclohexanone (108-94-1)	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.232 g O ₂ /g substance

REVvive by RSG Matte Trim Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

cyclohexanone (108-94-1)	
Chemical oxygen demand (COD)	2.605 g O ₂ /g substance
ThOD	2.605 g O ₂ /g substance
methyl acetate (79-20-9)	
Persistence and degradability	Readily biodegradable in water. Inherently biodegradable.
acetone (67-64-1)	
Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.43 g O ₂ /g substance
Chemical oxygen demand (COD)	1.92 g O ₂ /g substance
ThOD	2.2 g O ₂ /g substance
BOD (% of ThOD)	0.872 (20 day(s), Literature study)

12.3. Bioaccumulative potential

ethyl methyl ketone (78-93-3)	
Log Pow	0.3 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 40 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
solvent naphtha (petroleum), light aromatic (64742-95-6)	
Log Pow	2.1 - 6
Bioaccumulative potential	Not established.
xylene (1330-20-7)	
BCF fish 1	7 - 26 (8 week(s), Oncorhynchus mykiss, Flow-through system, Fresh water, Experimental value)
Log Pow	3.2 (Conclusion by analogy, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
reaction mass of α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-hydroxypoly(oxyethylene) and α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)	
BCF fish 1	2658 - 3430 (502 h, Oncorhynchus mykiss, Flow-through system, Fresh water, Experimental value)
Log Pow	4.6 (Experimental value, Equivalent or similar to OECD 117, 25 °C)
cyclohexanone (108-94-1)	
BCF other aquatic organisms 1	2.4 (QSAR)
Log Pow	0.86 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
methyl acetate (79-20-9)	
BCF fish 1	< 1 (Pisces, Literature study)
Log Pow	0.37 (Calculated, KOWWIN, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
acetone (67-64-1)	
BCF fish 1	0.69 (Pisces)
BCF other aquatic organisms 1	3 (BCFWIN, Calculated value)
Log Pow	-0.24 (Test data)
Bioaccumulative potential	Not bioaccumulative.

12.4. Mobility in soil

ethyl methyl ketone (78-93-3)	
Surface tension	0.024 N/m (20 °C)
Log Koc	1.53 (log Koc, Calculated value)
Ecology - soil	Highly mobile in soil. Slightly harmful to plants.

REVvive by RSG Matte Trim Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

xylene (1330-20-7)	
Surface tension	28.01 - 29.76 mN/m (25 °C)
Ecology - soil	No (test)data on mobility of the substance available. May be harmful to plant growth, blooming and fruit formation.
cyclohexanone (108-94-1)	
Surface tension	0.034 N/m (20 °C)
Log Koc	1.18 (log Koc, SRC PCKOCWIN v1.66, Calculated value)
Ecology - soil	Highly mobile in soil.
methyl acetate (79-20-9)	
Surface tension	0.024 N/m (20 °C)
Log Koc	0.18 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value, GLP)
Ecology - soil	Highly mobile in soil.
acetone (67-64-1)	
Surface tension	0.0237 N/m
Ecology - soil	No (test)data on mobility of the substance available.

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not applicable

Transportation of Dangerous Goods

Transport document description : UN1950 AEROSOLS (flammable), 2.1
UN-No. (TDG) : UN1950
Proper Shipping Name (Transportation of Dangerous Goods) : AEROSOLS
TDG Primary Hazard Classes : 2.1 - Class 2.1 - Flammable Gas.
TDG Special Provisions : 80 - Despite section 1.17 of Part 1, Coming into Force, Repeal, Interpretation, General Provisions and Special Cases, a person must not offer for transport or transport these dangerous goods unless they are in a means of containment that is in compliance with section 5.11 of Part 5, Means of Containment, except that the requirement for aerosol containers to be tightly packed in a wood, fibreboard or plastic box does not apply to a user or purchaser who transports no more than six aerosol containers. For a similar rule respecting aerosol containers, see subparagraph 1.15(1)(a)(i) of Part 1, Coming into Force, Repeal, Interpretation, General Provisions and Special Cases. SOR/2012-245,107 - (1)These Regulations, except for Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases) and Part 2, (Classification), do not apply to the handling, offering for transport or transporting of UN1950, AEROSOLS, and UN2037, GAS CARTRIDGES, that contain dangerous goods included in Class 2.1 or Class 2.2 and that are transported on a road vehicle, a railway vehicle or a ship on a domestic voyage, if the aerosols or gas cartridges have a capacity less than or equal to 50 mL. (2)Subsection (1) does not apply to self-defence spray. SOR/2014-306
Explosive Limit and Limited Quantity Index : 1 L
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index : 75 L

REVvive by RSG Matte Trim Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Transport by sea

Transport document description (IMDG)	: UN 1950 AEROSOLS, 2.1
UN-No. (IMDG)	: 1950
Proper Shipping Name (IMDG)	: AEROSOLS
Class (IMDG)	: 2 - Gases

Air transport

Transport document description (IATA)	: UN 1950 Aerosols, flammable, 2.1
UN-No. (IATA)	: 1950
Proper Shipping Name (IATA)	: Aerosols, flammable
Class (IATA)	: 2

SECTION 15: Regulatory information

15.1. US Federal regulations

ethyl methyl ketone (78-93-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Not subject to reporting requirements of the United States SARA Section 313

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ 5000 lb

solvent naphtha (petroleum), light aromatic (64742-95-6)

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

xylene (1330-20-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Subject to reporting requirements of United States SARA Section 313

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ 100 lb

reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

cyclohexanone (108-94-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Not subject to reporting requirements of the United States SARA Section 313

CERCLA RQ 5000 lb

methyl acetate (79-20-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

acetone (67-64-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Not subject to reporting requirements of the United States SARA Section 313

CERCLA RQ 5000 lb

15.2. International regulations

CANADA

ethyl methyl ketone (78-93-3)

Listed on the Canadian DSL (Domestic Substances List)

solvent naphtha (petroleum), light aromatic (64742-95-6)

Not listed on the Canadian DSL (Domestic Substances List)/NDSL (Non-Domestic Substances List)

xylene (1330-20-7)

Listed on the Canadian DSL (Domestic Substances List)

REVvive by RSG Matte Trim Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)

Not listed on the Canadian DSL (Domestic Substances List)/NDSL (Non-Domestic Substances List)

cyclohexanone (108-94-1)

Listed on the Canadian DSL (Domestic Substances List)

methyl acetate (79-20-9)

Listed on the Canadian DSL (Domestic Substances List)

acetone (67-64-1)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

ethyl methyl ketone (78-93-3)

Listed on EPA Hazardous Air Pollutant (HAPS)

xylene (1330-20-7)

Listed on EPA Hazardous Air Pollutant (HAPS)

15.3. US State regulations

No additional information available

SECTION 16: Other information

Revision date : 06/27/2018

Full text of H-phrases:

H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H411	Toxic to aquatic life with long lasting effects

SDS US GHS (GHS HazCom2012) - U-POL

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product