



025-1756 through 025-1763

PRO+ Slate Construction Harness: Alu 3D, Alu QC Chest/Legs, Trauma Relief

FEATURES :

- Fixed dorsal D-ring
- Integrated SRL channel
- Side positioning D-rings
- Quick-connect chest
- Quick torso adjusters
- Quick-connect legs
- Shoulder pad
- Fixed comfort waist pad
- Removable leg pads
- Integrated Quick-Adjust Trauma Relief packs (022-6047) installed on the harness for temporary relief while awaiting rescue

FALL ARREST POINT(S) :

- 1 Dorsal D-ring
- 1 Integrated SRL channel

ITEM WEIGHT :

- 5.7 lbs. (2.6 kg)



BUILT-IN TRAUMA RELIEF PACKS

USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-141 kg)
OSHA	Up to 420 lbs. (191 kg)

STANDARD COMPLIANT WITH	
ANSI	Z359.11-2021
OSHA	1926.502, 1910.140

SIZE(S)	
025-1756	X-Small
025-1757	Small
025-1758	Medium
025-1759	Large
025-1760	X-Large
025-1761	2X
025-1762	3X
025-1763	4X

COMPONENT	MATERIAL SPECIFICATION
Webbing	Polyester
D-ring(s)	Anodized aluminum
Adjuster buckles	Anodized aluminum
Chest connection	Anodized aluminum
Leg connection	Anodized aluminum
SRL channel	HDPE
Pads	Nubuck synthetic; Spandex; Poly mesh; EVA
Belt	Polyester; Steel; Stainless steel
Trauma Relief	Polyester, EP coated stainless steel, velcro