



<b>EAN:</b>	4013288139290	<b>Size:</b>	112x7x3 mm
<b>Part number:</b>	05022042001	<b>Weight:</b>	5 g
<b>Article number:</b>	950 PKLS	<b>Country of origin:</b>	CZ
		<b>Customs tariff number:</b>	82041100

- L-keys for hexagonal socket screws
- Hex-Plus allows socket head screws to live longer
- Extra-short arm for use on difficult-to-access screws
- Hexagonal ballpoint on the long arm
- High corrosion protection thanks to chrome-plating

High quality L-keys with extra-short arm for applications on difficult-to-access screws. For hexagonal socket screws, Hex-Plus offers a larger contact surface within the screw head. This reduces the notching effects to a minimum and almost completely eliminates the risk of destroying the screw recess. The ball-end on the long arm allows for reliable working even in difficult installation situations. The precise chrome-plated design ensures high corrosion protection. The tools are quickly to hand thanks to the laser-engraved and thereby wear-resistant size markings on the L-keys.


**Web link**
<https://www.wera.de/en/05022042001>
**Wera - 950 PKLS**

05022042001 - 4013288139290

**Wera Werkzeuge GmbH**

Korzter Straße 21-25

D-42349 Wuppertal

Tel: +49 (0)2 02 / 40 45-0

E-Mail: [info@wera.de](mailto:info@wera.de)

### L-Keys



We questioned the classic L-key design, since all too often the screw head recess is rounded out, meaning screws can no longer be tightened or loosened - and so the user finds the L-key slipping out of the recess. Wera Hex-Plus tools have a larger contact surface in the screw head. The notching effects are reduced and thereby the deformation of the screws. At the same time, as much as 20 % more torque can be applied.

### With extra short arm



All users will recognise the need to saw or grind down L-keys to make them shorter for particularly confined screwdriving jobs. This has the disadvantage that they no longer have any corrosion protection at the separation point and secondly, they can become "soft" and therefore useless due to an alteration in the hardening during the shortening process.

### Hex-Plus



Hexagon screws can endure a problem because the contact surfaces delivering the power from the conventional tool, is transferred to the screw via very small surface areas. The consequence: the screw can become damaged (rounding out). Hex-Plus tools have a greater contact surface that prevents this from happening! At the same time, as much as 20 % more torque can be applied. Good to know: Hex-Plus tools fit into every standard hexagon socket screw!

### Ball tip



The spherical drive profile means that it is possible to swivel the axis of the tool to that of the screw, and therefore enable angled, "around-the-corner" screwdriving jobs.

### Size identification



The size of each L-keys has been engraved by a laser. In addition Take it easy L-keys have a colour coding according to sizes - for simple and rapid accessing of the required tool. Making it easy to find the right tool.

### Surface protection



Chrome-plated hexagon L-keys for outstanding surface protection and long service life. High corrosion protection.






### Web link

<https://www.wera.de/en/05022042001>

Wera - 950 PKLS  
05022042001 - 4013288139290

Wera Werkzeuge GmbH  
Korzter Straße 21-25  
D-42349 Wuppertal  
Tel: +49 (0)2 02 / 40 45-0  
E-Mail: [info@wera.de](mailto:info@wera.de)

## Further versions in this product family:

	 mm	 mm	 mm	 inch	 inch
05022040001 <sup>1)</sup>	1.5	90	4.5	3 1/2"	11/64"
05022041001	2.0	100	5.5	4"	7/32"
<b>05022042001</b>	<b>2.5</b>	<b>112</b>	<b>6.5</b>	<b>4 7/16"</b>	<b>1/4"</b>
05022043001	3.0	126	7.5	5"	19/64"
05022044001	4.0	140	10.0	5 1/2"	25/64"
05022045001	5.0	160	12	6 5/16"	15/32"
05022046001	6.0	180	15	7 1/16"	19/32"
05022047001	8.0	200	19	8"	3/4"
05022048001	10.0	219	22	8 5/8"	7/8"

1) Regular hexagon

## Web link

<https://www.wera.de/en/05022042001>

Wera - 950 PKLS

05022042001 - 4013288139290

Wera Werkzeuge GmbH

Korzter Straße 21-25

D-42349 Wuppertal

Tel: +49 (0)2 02 / 40 45-0

E-Mail: [info@wera.de](mailto:info@wera.de)