

## Section 1 Identification.

Product name:

**NOCO® NCP-2 Battery Corrosion Preventative Spray**

Product code:

**A202**

Other means of identification: Not available.

Product type: Aerosol

Relevant identified uses of the substance or mixture and uses advised against: Paint or paint related material.

Manufacturer: The NOCO Company  
30339 Diamond Parkway, #102  
Glenwillow, OH 44139

Emergency telephone number of the company: (800) 424-9300

Product Information Telephone Number: (800) 456-6626

Transportation Emergency Telephone Number: (800) 424-9300

## Section 2 Hazards identification.

OSHA/HCS status: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture: FLAMMABLE AEROSOLS - Category 1  
GASES UNDER PRESSURE - Compressed gas  
SKIN CORROSION/IRRITATION - Category 2  
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A  
CARCINOGENICITY - Category 2  
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3  
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3  
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2  
ASPIRATION HAZARD - Category 1

Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 15% (oral), 15% (dermal), 15% (inhalation)

## Section 2 Hazards identification continued.

Hazard pictograms:

GHS label elements:



Signal Word: Danger

Hazard statements: Extremely flammable aerosol.  
Contains gas under pressure; may explode if heated.  
May be fatal if swallowed and enters airways.  
Causes skin irritation.  
Causes serious eye irritation.  
May cause respiratory irritation.  
May cause drowsiness or dizziness.  
Suspected of causing cancer.  
May cause damage to organs through prolonged or repeated exposure.

Precautionary statements:

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Use only outdoors or in a well-ventilated area. Do not breathe dust or mist. Wash thoroughly after handling. Pressurized container: Do not pierce or burn, even after use.

Response: IF EXPOSED OR CONCERNED: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting. Take off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

Storage: Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place. Keep container tightly closed.

Disposal: Dispose of contents and container in accordance with all local, regional, national and international regulations.

Supplemental label elements: DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. FOR INDUSTRIAL USE ONLY.

Please refer to the SDS for additional information. Keep out of reach of children. Keep upright in a cool, dry place. Do not discard empty can in trash compactor.

Hazards not otherwise classified: None known.

## Section 3 Composition/information on ingredients.

Substance/mixture: None known.

Other means of identification: Not available.

CAS number/other identifiers:

| Ingredient name       | % by weight | CAS Number |
|-----------------------|-------------|------------|
| Paraffin oil          | ≥25 - ≤50   | 64742-62-7 |
| Acetone               | ≥10 - ≤25   | 67-64-1    |
| Propane               | ≥10 - ≤25   | 74-98-6    |
| Xylene, mixed isomers | ≥10 - ≤20   | 1330-20-7  |
| Methyl Ethyl Ketone   | ≥10 - ≤23   | 78-93-3    |
| Ethylbenzene          | ≤3          | 100-41-4   |

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health of the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4 First aid measures.

Description of necessary first aid measures:

- Eye contact: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should

## Section 4 First aid measures continued.

Ingestion continued: be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms and effects, both acute and delayed.

Potential acute health effects

Eye Contact: Causes serious eye irritation.

Inhalation: Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.

Skin Contact: Causes skin irritation.

Ingestion: Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.

Over-exposure signs and symptoms

Eye Contact: Adverse symptoms may include the following:  
pain or irritation  
watering  
redness

Inhalation: Adverse symptoms may include the following:  
respiratory tract irritation  
coughing  
nausea or vomiting  
headache  
drowsiness/fatigue  
dizziness/vertigo  
unconsciousness

Skin Contact: Adverse symptoms may include the following:  
irritation  
redness

Ingestion: Adverse symptoms may include the following:  
nausea or vomiting

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Specific treatments: No specific treatment.

Protection of first-aiders: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

## Section 5 Fire-fighting measures.

### Extinguishing media:

Suitable extinguishing media: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media: None known.

Specific hazards arising from the chemical: Extremely flammable aerosol. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed.

Hazardous thermal decomposition products: Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide

Special protective actions for fire-fighters: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Remark: Flammable aerosol.

## Section 6 Accidental release measures.

### Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel."

Environmental precautions: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

## Section 6 Accidental release measures continued.

Methods and materials for containment and cleaning up:

- Small spill: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7 Handling and storage.

Precautions for safe handling:

Protective measures: Put on appropriate personal protective equipment (see Section 8). Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not swallow. Avoid breathing gas. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.

Advice on general occupational hygiene: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities: Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Protect from sunlight. Store locked up. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination.

## Section 8 Exposure controls/personal protection.

Control parameters:

Occupational exposure limits (OSHA United States)

| Ingredient Name       | CAS #      | Exposure Limits                                                                                                                                                                                                                                                                                                                                                                                                 |
|-----------------------|------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Paraffin Oil          | 64742-62-7 | ACGIH TLV (United States, 1/2024). [Mineral Oil, pure, highly and severely refined]<br>TWA: 5 mg/m <sup>3</sup> 8 hours. Form: Inhalable fraction<br>OSHA PEL (United States, 5/2018). [Oil mist, mineral]<br>TWA: 5 mg/m <sup>3</sup> 8 hours.<br>NIOSH REL (United States, 10/2020). [OIL MIST MINERAL]<br>TWA: 5 mg/m <sup>3</sup> 10 hours. Form: Mist<br>STEL: 10 mg/m <sup>3</sup> 15 minutes. Form: Mist |
| Acetone               | 67-64-1    | ACGIH TLV (United States, 1/2024).<br>TWA: 250 ppm 8 hours.<br>STEL: 500 ppm 15 minutes.<br>NIOSH REL (United States, 10/2020).<br>TWA: 250 ppm 10 hours.<br>TWA: 590 mg/m <sup>3</sup> 10 hours.<br>OSHA PEL (United States, 5/2018).<br>TWA: 1000 ppm 8 hours.<br>TWA: 2400 mg/m <sup>3</sup> 8 hours.                                                                                                        |
| Propane               | 74-98-6    | NIOSH REL (United States, 10/2020).<br>TWA: 1000 ppm 10 hours.<br>TWA: 1800 mg/m <sup>3</sup> 10 hours.<br>OSHA PEL (United States, 5/2018).<br>TWA: 1000 ppm 8 hours.<br>TWA: 1800 mg/m <sup>3</sup> 8 hours.<br>ACGIH TLV (United States, 1/2024). Oxygen Depletion [Asphyxiant]. Explosive potential.                                                                                                        |
| Xylene, mixed isomers | 1330-20-7  | OSHA PEL (United States, 5/2018). [Xylenes]<br>TWA: 100 ppm 8 hours.<br>TWA: 435 mg/m <sup>3</sup> 8 hours.<br>ACGIH TLV (United States, 1/2024).<br>[pxylene and mixtures containing p-xylene] Ototoxicant.<br>TWA: 20 ppm 8 hours.                                                                                                                                                                            |
| Methyl Ethyl Ketone   | 78-93-3    | ACGIH TLV (United States, 1/2024).<br>Absorbed through skin.<br>TWA: 75 ppm 8 hours.<br>STEL: 150 ppm 15 minutes.<br>NIOSH REL (United States, 10/2020).<br>TWA: 200 ppm 10 hours.<br>TWA: 590 mg/m <sup>3</sup> 10 hours.<br>STEL: 300 ppm 15 minutes.<br>STEL: 885 mg/m <sup>3</sup> 15 minutes.<br>OSHA PEL (United States, 5/2018).<br>TWA: 200 ppm 8 hours.<br>TWA: 590 mg/m <sup>3</sup> 8 hours.         |

## Section 8 Exposure controls/personal protection continued.

Control parameters:

Occupational exposure limits (OSHA United States)

| Ingredient Name | CAS #    | Exposure Limits                                                                                                                                                                                                                                                                                                                                                  |
|-----------------|----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Ethylbenzene    | 100-41-4 | ACGIH TLV (United States, 1/2024).<br>Ototoxicant.<br>TWA: 20 ppm 8 hours.<br>NIOSH REL (United States, 10/2020).<br>TWA: 100 ppm 10 hours.<br>TWA: 435 mg/m <sup>3</sup> 10 hours.<br>STEL: 125 ppm 15 minutes.<br>STEL: 545 mg/m <sup>3</sup> 15 minutes.<br>OSHA PEL (United States, 5/2018).<br>TWA: 100 ppm 8 hours.<br>TWA: 435 mg/m <sup>3</sup> 8 hours. |

Occupational exposure limits (Canada)

| Ingredient Name | CAS #   | Exposure Limits                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|-----------------|---------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Acetone         | 67-64-1 | CA Alberta Provincial (Canada, 3/2023).<br>OEL: 1200 mg/m <sup>3</sup> 8 hours.<br>OEL: 1800 mg/m <sup>3</sup> 15 minutes.<br>OEL: 500 ppm 8 hours.<br>OEL: 750 ppm 15 minutes.<br>CA British Columbia Provincial (Canada, 8/2023).<br>TWA: 250 ppm 8 hours.<br>STEL: 500 ppm 15 minutes.<br>CA Ontario Provincial (Canada, 6/2019).<br>TWA: 250 ppm 8 hours.<br>STEL: 500 ppm 15 minutes.<br>CA Quebec Provincial (Canada, 2/2024).<br>TWA <sub>EV</sub> : 250 ppm 8 hours.<br>STEV: 500 ppm 15 minutes.<br>CA Saskatchewan Provincial (Canada, 4/2021).<br>STEL: 750 ppm 15 minutes.<br>TWA: 500 ppm 8 hours. |
| Normal propane  | 74-98-6 | CA Alberta Provincial (Canada, 3/2023).<br>OEL: 1000 ppm 8 hours.<br>CA Saskatchewan Provincial (Canada, 4/2021).<br>STEL: 1250 ppm 15 minutes.<br>TWA: 1000 ppm 8 hours.<br>CA British Columbia Provincial (Canada, 8/2023). Oxygen Depletion [Asphyxiant]. Explosive potential.<br>CA Ontario Provincial (Canada, 6/2019). Oxygen Depletion [Asphyxiant]. Explosive potential.<br>CA Quebec Provincial (Canada, 2/2024).<br>Oxygen Depletion [Asphyxiant]. Explosive potential.                                                                                                                               |

## Section 8 Exposure controls/personal protection continued.

Control parameters:

Occupational exposure limits (Canada)

| Ingredient Name     | CAS #     | Exposure Limits                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|---------------------|-----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Xylene              | 1330-20-7 | <p>CA Alberta Provincial (Canada, 3/2023). [Dimethylbenzene]<br/> OEL: 100 ppm 8 hours.<br/> OEL: 651 mg/m<sup>3</sup> 15 minutes.<br/> OEL: 150 ppm 15 minutes.<br/> OEL: 434 mg/m<sup>3</sup> 8 hours.<br/> CA British Columbia Provincial (Canada, 8/2023). [Xylene (o, m &amp; p isomers)]<br/> TWA: 100 ppm 8 hours.<br/> STEL: 150 ppm 15 minutes.<br/> CA Quebec Provincial (Canada, 2/2024). [Xylene]<br/> TWA: 100 ppm 8 hours.<br/> TWA: 434 mg/m<sup>3</sup> 8 hours.<br/> STEV: 150 ppm 15 minutes.<br/> STEV: 651 mg/m<sup>3</sup> 15 minutes.<br/> CA Ontario Provincial (Canada, 6/2019). [Xylene (o-, m-, p-isomers)]<br/> STEL: 150 ppm 15 minutes.<br/> TWA: 100 ppm 8 hours.<br/> CA Saskatchewan Provincial (Canada, 4/2021). [Xylene]<br/> STEL: 150 ppm 15 minutes.<br/> TWA: 100 ppm 8 hours.</p> |
| Methyl ethyl ketone | 78-93-3   | <p>CA Alberta Provincial (Canada, 3/2023).<br/> OEL: 300 ppm 15 minutes.<br/> OEL: 200 ppm 8 hours.<br/> OEL: 590 mg/m<sup>3</sup> 8 hours.<br/> OEL: 885 mg/m<sup>3</sup> 15 minutes.<br/> CA British Columbia Provincial (Canada, 8/2023). Absorbed through skin.<br/> TWA: 50 ppm 8 hours.<br/> STEL: 100 ppm 15 minutes.<br/> CA Ontario Provincial (Canada, 6/2019).<br/> TWA: 200 ppm 8 hours.<br/> STEL: 300 ppm 15 minutes.<br/> CA Quebec Provincial (Canada, 2/2024).<br/> TWA: 50 ppm 8 hours.<br/> TWA: 150 mg/m<sup>3</sup> 8 hours.<br/> STEV: 100 ppm 15 minutes.<br/> STEV: 300 mg/m<sup>3</sup> 15 minutes.<br/> CA Saskatchewan Provincial (Canada, 4/2021).<br/> STEL: 300 ppm 15 minutes.<br/> TWA: 200 ppm 8 hours.</p>                                                                             |

## Section 8 Exposure controls/personal protection continued.

Control parameters:

### Occupational exposure limits (Canada)

| Ingredient Name | CAS #    | Exposure Limits                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|-----------------|----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Ethylbenzene    | 100-41-4 | CA Alberta Provincial (Canada, 3/2023).<br>OEL: 100 ppm 8 hours.<br>OEL: 434 mg/m <sup>3</sup> 8 hours.<br>OEL: 543 mg/m <sup>3</sup> 15 minutes.<br>OEL: 125 ppm 15 minutes.<br>CA British Columbia Provincial (Canada, 8/2023).<br>TWA: 20 ppm 8 hours.<br>CA Ontario Provincial (Canada, 6/2019).<br>TWA: 20 ppm 8 hours.<br>CA Quebec Provincial (Canada, 2/2024).<br>TWA/EV: 20 ppm 8 hours.<br>CA Saskatchewan Provincial (Canada, 4/2021).<br>STEL: 125 ppm 15 minutes.<br>TWA: 100 ppm 8 hours. |

### Occupational exposure limits (Mexico)

| Ingredient Name       | CAS #     | Exposure Limits                                                                           |
|-----------------------|-----------|-------------------------------------------------------------------------------------------|
| Acetone               | 67-64-1   | NOM-010-STPS-2014 (Mexico, 4/2016).<br>TWA: 500 ppm 8 hours.<br>STEL: 750 ppm 15 minutes. |
| Xylene, mixed isomers | 1330-20-7 | NOM-010-STPS-2014 (Mexico, 4/2016).<br>STEL: 150 ppm 15 minutes.<br>TWA: 100 ppm 8 hours. |
| Methyl Ethyl Ketone   | 78-93-3   | NOM-010-STPS-2014 (Mexico, 4/2016).<br>TWA: 200 ppm 8 hours.<br>STEL: 300 ppm 15 minutes. |
| Ethylbenzene          | 100-41-4  | NOM-010-STPS-2014 (Mexico, 4/2016).<br>TWA: 20 ppm 8 hours.                               |

### Biological exposure indices (United States)

| Ingredient Name       | Exposure indices                                                                                                                                                       |
|-----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Acetone               | ACGIH BEI (United States, 1/2024)<br>BEI: 25 mg/l, acetone [in urine]. Sampling time: end of shift.                                                                    |
| Xylene, mixed isomers | ACGIH BEI (United States, 1/2024) [xylenes (technical or commercial grades)]<br>BEI: 0.3 g/g creatinine, methylhippuric acids [in urine]. Sampling time: end of shift. |
| Methyl Ethyl Ketone   | ACGIH BEI (United States, 1/2024)<br>BEI: 2 mg/l, methyl ethyl ketone [in urine].<br>Sampling time: end of shift.                                                      |
| Ethylbenzene          | ACGIH BEI (United States, 1/2024)<br>BEI: 150 mg/g creatinine, sum of mandelic acid and phenylglyoxylic acid [in urine].<br>Sampling time: end of shift.               |

## Section 8 Exposure controls/personal protection continued.

### Biological exposure indices (Canada)

No exposure indices known.

### Biological exposure indices (Mexico)

#### Ingredient Name

#### Exposure indices

Acetone

Official Mexican STANDARD NOM- 047-SSA1-2011, Environmental Health- Biological exposure indices for personnel occupationally exposed to chemical substances. (Mexico, 6/2012)

BEI: 50 mg/L [non-specific. The determinant is nonspecific, since it can be found after exposure to other chemicals.], acetone [in urine].

Sampling time: at the end of the work shift.

Xylene, mixed isomers

Official Mexican STANDARD NOM- 047-SSA1-2011, Environmental Health- Biological exposure indices for personnel occupationally exposed to chemical substances. (Mexico, 6/2012) [xylenes (technical or commercial grade)]

BEI: 1.5 g/g creatinine, methyl hippuric acids [in urine].

Sampling time: at the end of the work shift.

Methyl Ethyl Ketone

Official Mexican STANDARD NOM- 047-SSA1-2011, Environmental Health- Biological exposure indices for personnel occupationally exposed to chemical substances. (Mexico, 6/2012)

BEI: 2 mg/L, MEK [in urine].

Sampling time: at the end of the work shift.

Ethylbenzene

Official Mexican STANDARD NOM- 047-SSA1-2011, Environmental Health- Biological exposure indices for personnel occupationally exposed to chemical substances. (Mexico, 6/2012)

BEI: 0.7 g/g creatinine [non-specific. The determinant is nonspecific, since it can be found after exposure to other chemicals.; semi-quantitative. The biological determinant is an indicator of chemical exposure, but the quantitative interpretation of the measure is ambiguous. These biological determinants should be used as a screening test if a quantitative test is not possible.], Sum of mandelic acid and acid phenylglyoxylic [in urine]. Sampling time: at the end of the shift at the end of the work week.

BEI: semi-quantitative. The biological determinant is an indicator of chemical exposure, but the quantitative interpretation of the measure is ambiguous. These biological determinants should be used as a screening test if a quantitative test is not possible., ethylbenzene [in exhaled air]. Sampling time: uncritical.

**Appropriate engineering controls:** Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

**Environmental exposure controls:** Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## Section 8 Exposure controls/personal protection continued.

### Individual protection measures:

**Hygiene measures:** Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection:** Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

### Skin protection:

**Hand protection:** Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Body protection:** Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear antistatic protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

**Other skin protection:** Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection:** Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

## Section 9 Physical and chemical data.

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### Appearance

**Physical state:** Liquid.

**Color:** Clear.

**Odor:** Not available.

**Odor Threshold:** Not available.

**pH:** Not available.

## Section 9 Physical and chemical data continued.

Melting point/freezing point: Not available.

Flash point: Closed cup: -29°C (-20.2°F) [Pensky-Martens Closed Cup]

Evaporation Rate: 5.6 (butyl acetate = 1)

Flammability: Flammable aerosol.

Lower and upper explosive (flammable) limits: Lower: 1%  
Upper: 12.8%

Vapor Pressure: 101.3 kPa (760 mm Hg)

Relative vapor density: 1.55 [Air = 1]

Relative Density: 0.77

| Solubility(ies): | Media      | Result      |
|------------------|------------|-------------|
|                  | Cold water | Not soluble |

Partition coefficient n-octanol/water: Not available.

Auto-ignition Temperature: Not available.

Decomposition Temperature: Not available.

Viscosity: Kinematic (40°C (104°F)): <20.5 mm<sup>2</sup>/s (<20.5 cSt)

Molecular Weight: Not available.

Aerosol product

Type of aerosol: Spray

Heat of combustion: 32.788 kJ/g

## Section 10 Stability and reactivity data.

Reactivity: No specific test data related to reactivity available for this product or its ingredients.

Chemical stability: The product is stable.

Possibility of hazardous reactions: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid: Avoid all possible sources of ignition (spark or flame).

Incompatible materials: No specific data.

Hazardous decomposition products: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11 Toxicological information.

Information on toxicological effects:

Acute toxicity:

| Product/<br>ingredient name | Result              | Species | Dose        | Exposure |
|-----------------------------|---------------------|---------|-------------|----------|
| Acetone                     | LD50 Oral           | Rat     | 5800 mg/kg  | -        |
| Xylene, mixed isomers       | LD50 Inhalation Gas | Rat     | 6700 ppm    | 4 hours  |
|                             | LD50 Oral           | Rat     | 4300 mg/kg  | -        |
| Methyl Ethyl Ketone         | LD50 Dermal         | Rabbit  | 6480 mg/kg  | -        |
|                             | LD50 Oral           | Rat     | 2737 mg/kg  | -        |
| Ethylbenzene                | LD50 Dermal         | Rabbit  | >5000 mg/kg | -        |
|                             | LD50 Oral           | Rat     | 3500 mg/kg  | -        |

Irritation/Corrosion:

| Product/<br>ingredient name | Result                   | Species | Score | Exposure                 | Observation |
|-----------------------------|--------------------------|---------|-------|--------------------------|-------------|
| Acetone                     | Eyes - Mild irritant     | Human   | -     | 186300 parts per million | -           |
|                             | Eyes - Mild irritant     | Rabbit  | -     | 10 microliters           | -           |
|                             | Eyes - Moderate irritant | Rabbit  | -     | 24 hours 20 milligrams   | -           |
|                             | Eyes - Severe irritant   | Rabbit  | -     | 20 milligrams            | -           |
|                             | Skin - Mild irritant     | Rabbit  | -     | 24 hours 500 milligrams  | -           |
|                             | Skin - Mild irritant     | Rabbit  | -     | 395 milligrams           | -           |
| Xylene, mixed isomers       | Eyes - Mild irritant     | Rabbit  | -     | 87 milligrams            | -           |
|                             | Eyes - Severe irritant   | Rabbit  | -     | 24 hours 5 milligrams    | -           |
|                             | Skin - Mild irritant     | Rat     | -     | 8 hours 60 microliters   | -           |
|                             | Skin - Moderate irritant | Rabbit  | -     | 24 hours 500 milligrams  | -           |
|                             | Skin - Moderate irritant | Rabbit  | -     | 100 Percent              | -           |
| Methyl Ethyl Ketone         | Skin - Mild irritant     | Rabbit  | -     | 24 hours 14 milligrams   | -           |
|                             | Skin - Moderate irritant | Rabbit  | -     | 24 hours 500 milligrams  | -           |
| Ethylbenzene                | Eyes - Severe irritant   | Rabbit  | -     | 500 milligrams           | -           |
|                             | Skin - Mild irritant     | Rabbit  | -     | 24 hours 15 milligrams   | -           |

Sensitization:

Not available.

Mutagenicity:

Not available.

Carcinogenicity:

Not available.

Classification:

| Product/<br>ingredient name | OSHA | IARC | NTP |
|-----------------------------|------|------|-----|
| Xylene, mixed isomers       | -    | 3    | -   |
| Ethylbenzene                | -    | 2B   | -   |

## Section 11 Toxicological information continued.

Reproductive toxicity:

Not available.

Teratogenicity:

Not available.

Specific target organ toxicity (single exposure):

| Name                  | Category   | Route of exposure | Target organs                |
|-----------------------|------------|-------------------|------------------------------|
| Acetone               | Category 3 | -                 | Narcotic effects             |
| Xylene, mixed isomers | Category 3 | -                 | Respiratory tract irritation |
| Methyl Ethyl Ketone   | Category 3 | -                 | Narcotic effects             |
| Ethylbenzene          | Category 3 | -                 | Narcotic effects             |

Specific target organ toxicity (repeated exposure):

| Name                  | Category   | Route of exposure | Target organs |
|-----------------------|------------|-------------------|---------------|
| Xylene, mixed isomers | Category 2 | -                 | -             |
| Ethylbenzene          | Category 2 | -                 | -             |

Aspiration hazard:

| Name                  | Result                       |
|-----------------------|------------------------------|
| Xylene, mixed isomers | ASPIRATION HAZARD-Category 1 |
| Ethylbenzene          | ASPIRATION HAZARD-Category 1 |

Information on the likely routes of exposure: Not available.

Potential acute health effects:

Eye contact: Causes serious eye irritation.

Inhalation: Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.

Skin contact: Causes skin irritation.

Ingestion: Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.

## Section 11 Toxicological information continued.

Symptoms related to the physical, chemical and toxicological characteristics:

Eye contact: Adverse symptoms may include the following:  
pain or irritation  
watering  
redness

Inhalation: Adverse symptoms may include the following:  
respiratory tract irritation  
coughing  
nausea or vomiting  
headache  
drowsiness/fatigue  
dizziness/vertigo  
unconsciousness

Skin contact: Adverse symptoms may include the following:  
irritation  
redness

Ingestion: Adverse symptoms may include the following:  
nausea or vomiting

Delayed and immediate effects and also chronic effects from short and long term exposure:

Short term exposure:

Potential immediate effects Not available.

Potential delayed effects Not available.

Long term exposure:

Potential immediate effects Not available.

Potential delayed effects Not available.

Potential chronic health effects:

Not available.

General: May cause damage to organs through prolonged or repeated exposure.

Carcinogenicity: Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.

Mutagenicity: No known significant effects or critical hazards.

Teratogenicity: No known significant effects or critical hazards.

Developmental effects: No known significant effects or critical hazards.

Fertility effects: No known significant effects or critical hazards.

## Section 11 Toxicological information continued.

Numerical measures of toxicity:

Acute toxicity estimates:

| Route               | ATE value      |
|---------------------|----------------|
| Oral                | 11721.22 mg/kg |
| Dermal              | 16721.83 mg/kg |
| Inhalation (vapors) | 415.56 mg/l    |

## Section 12 Ecological information.

Toxicity:

| Product/ ingredient name | Result                               | Species                                 | Exposure |
|--------------------------|--------------------------------------|-----------------------------------------|----------|
| Acetone                  | Acute EC50 7200000 µg/l Fresh water  | Algae - Selenastrum sp.                 | 96 hours |
|                          | Acute LC50 4.42589 ml/L Marine water | Crustaceans - Acartia tonsa - Copepodid | 48 hours |
|                          | Acute LC50 7460000 µg/l Fresh water  | Daphnia - Daphnia cucullata             | 48 hours |
|                          | Acute LC50 5600 ppm Fresh water      | Fish - Poecilia reticulata              | 96 hours |
|                          | Chronic NOEC 4.95 mg/l Marine water  | Algae - Ulva pertusa                    | 96 hours |
|                          | Chronic NOEC 0.016 ml/L Fresh water  | Crustaceans - Daphniidae                | 21 days  |
|                          | Chronic NOEC 0.1 ml/L Fresh water    | Daphnia - Daphnia magna - Neonate       | 21 days  |
|                          | Chronic NOEC 5 µg/l Marine water     | Fish - Gasterosteus aculeatus - Larvae  | 42 days  |
| Xylene, mixed isomers    | Acute LC50 8500 µg/l Marine water    | Crustaceans - Palaemonetes pugio        | 48 hours |
|                          | Acute LC50 13400 µg/l Fresh water    | Fish - Pimephales promelas              | 96 hours |
| Methyl Ethyl Ketone      | Acute EC50 >500000 µg/l Marine water | Algae - Skeletonema costatum            | 96 hours |
|                          | Acute EC50 5091000 µg/l Fresh water  | Daphnia - Daphnia magna - Larvae        | 48 hours |
|                          | Acute LC50 3220000 µg/l Fresh water  | Fish - Pimephales promelas              | 96 hours |
| Ethylbenzene             | Acute EC50 4600 µg/l Fresh water     | Algae - Pseudokirchneriella subcapitata | 72 hours |
|                          | Acute EC50 3600 µg/l Fresh water     | Algae - Pseudokirchneriella subcapitata | 96 hours |
|                          | Acute EC50 6.53 mg/l Marine water    | Crustaceans - Artemia sp. - Nauplii     | 48 hours |
|                          | Acute EC50 2.93 mg/l Fresh water     | Daphnia - Daphnia magna - Neonate       | 48 hours |
|                          | Acute LC50 4200 µg/l Fresh water     | Fish - Oncorhynchus mykiss              | 96 hours |

## Section 12 Ecological information continued.

Persistence and degradability:

| Product/ingredient name | Aquatic half-life | Photolysis | Biodegradability |
|-------------------------|-------------------|------------|------------------|
| Acetone                 | -                 | -          | Readily          |
| Xylene, mixed isomers   | -                 | -          | Readily          |
| Methyl Ethyl Ketone     | -                 | -          | Readily          |
| Ethylbenzene            | -                 | -          | Readily          |

Bioaccumulative potential:

| Product/ingredient name | LogP <sub>ow</sub> | BCF         | Potential |
|-------------------------|--------------------|-------------|-----------|
| Xylene, mixed isomers   | -                  | 8.1 to 25.9 | low       |

Mobility in soil:

Soil/water partition coefficient (K<sub>oc</sub>): Not available.

Other adverse effects: No known significant effects or critical hazards.

## Section 13 Disposal considerations.

**Disposal methods:** The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

## Section 14 Transport information.

|                         | DOT Classification | TDG Classification | Mexico Classification | IATA                | IMDG     |
|-------------------------|--------------------|--------------------|-----------------------|---------------------|----------|
| UN number               | UN1950             | UN1950             | UN1950                | UN1950              | UN1950   |
| UN proper shipping name | AEROSOLS           | AEROSOLS           | AEROSOLS              | AEROSOLS, flammable | AEROSOLS |

## Section 14 Transport information continued.

|                                                 | DOT Classification                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | TDG Classification                                                                                                         | Mexico Classification                                                                               | IATA                                                                                                | IMDG                                                                                                |
|-------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| Transport hazard class(es)                      | 2.1<br>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 2.1<br>                                   | 2.1<br>            | 2.1<br>          | 2.1<br>          |
| Packing group                                   | -                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | -                                                                                                                          | -                                                                                                   | -                                                                                                   | -                                                                                                   |
| Environmental hazards                           | No.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | No.                                                                                                                        | No.                                                                                                 | No.                                                                                                 | No.                                                                                                 |
| Additional information                          | -                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.13-2.17 (Class2). | -                                                                                                   | -                                                                                                   | Emergency schedules F-D, S-U                                                                        |
|                                                 | ERG No.<br>126                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | ERG No.<br>126                                                                                                             | ERG No.<br>126                                                                                      |                                                                                                     |                                                                                                     |
|                                                 | Dependent upon container size, this product may ship under the Limited Quantity shipping exception.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Dependent upon container size, this product may ship under the Limited Quantity shipping exception.                        | Dependent upon container size, this product may ship under the Limited Quantity shipping exception. | Dependent upon container size, this product may ship under the Limited Quantity shipping exception. | Dependent upon container size, this product may ship under the Limited Quantity shipping exception. |
| Special precautions for user:                   | Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations. |                                                                                                                            |                                                                                                     |                                                                                                     |                                                                                                     |
| Transport in bulk according to IMO instruments: | Not available.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                                                                                                                            |                                                                                                     |                                                                                                     |                                                                                                     |
| Proper shipping name:                           | Not available.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                                                                                                                            |                                                                                                     |                                                                                                     |                                                                                                     |

## Section 15 Regulatory information.

SARA 313: All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED and rely on information provided to us by our raw material suppliers. Our suppliers often provide an estimated value or range less than a certain upper limit. We calculate MAXIMUM THEORETICAL VALUES using defined values, if provided, or the upper limit reported by our supplier. Additionally, the suppliers' information may include amounts present in the product as unintentional byproducts or impurities. Variations may occur in individual batches due to adjustments made during production.

| Ingredient Name       | % by Weight | CAS Number |
|-----------------------|-------------|------------|
| Ethylbenzene          | 2           | 100-41-4   |
| Xylene, mixed isomers | 13          | 1330-20-7  |

California Prop. 65: WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

### International regulations:

Montreal Protocol: Not listed.

Stockholm Convention on  
Persistent Organic Pollutants: Not listed.

International lists: Australia inventory (AIIIC): Not determined.  
China inventory (IECSC): Not determined.  
Japan inventory (CSCL): Not determined.  
Japan inventory (ISHL): Not determined.  
Korea inventory (KECI): Not determined.  
New Zealand Inventory of Chemicals (NZIoC): Not determined.  
Philippines inventory (PICCS): Not determined.  
Taiwan Chemical Substances Inventory (TCSI): Not determined.  
Thailand inventory: Not determined.  
Turkey inventory: Not determined.  
Vietnam inventory: Not determined.

## Section 16 Other information.

Hazardous Material Information System (U.S.A.):

|                  |   |   |
|------------------|---|---|
| Health           | * | 3 |
| Flammability     |   | 4 |
| Physical hazards |   | 3 |

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

### Classification

FLAMMABLE AEROSOLS - Category 1  
 GASES UNDER PRESSURE - Compressed gas  
 SKIN CORROSION/IRRITATION - Category 2  
 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A  
 CARCINOGENICITY - Category 2  
 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3  
 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) -Category 3  
 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2  
 ASPIRATION HAZARD - Category 1

### Justification

On basis of test data  
 Calculation method  
 Calculation method  
 Calculation method  
 Calculation method  
 Calculation method  
 Calculation method  
 Calculation method  
 Calculation method

History:

Date of printing: 5/8/2025

Date of issue/Date of revision: 5/8/2025

Date of previous issue: 12/13/2024

Version: 22

Key to abbreviations: ATE = Acute Toxicity Estimate  
 BCF = Bioconcentration Factor  
 GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
 IATA = International Air Transport Association  
 IBC = Intermediate Bulk Container  
 IMDG = International Maritime Dangerous Goods

## Section 16 Other information continued.

Key to abbreviations: LogPow = logarithm of the octanol/water partition coefficient  
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973  
as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
N/A = Not available  
SGG = Segregation Group  
UN = United Nations

Indicates information that has changed from previously issued version.

### Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.