



EAN:	4013288038562	Size:	25x7x7 mm
Part number:	05056343001	Weight:	4 g
Article number:	840/1 Z Hex-Plus B0	Country of origin:	CZ
		Customs tariff number:	82079030

- For hexagon socket screws with safety pin (B0 = with bore hole)
- Hex-Plus allows socket head screws to live longer
- Tough for hard materials
- 1/4" hexagon drive (Wera connecting series 1)

Tough viscous Wera bits for hexagon socket screws and universal use. Hex-Plus offers a greater contact surface in the head of the screw. The notching effect is therefore reduced to a minimum and damage to the screw head more or less eliminated. Hexagon socket B0 screws have a protruding pin in their drive profile. This prevents any unauthorised loosening since the "normal" hex tools cannot move these screws. 1/4" hexagon, suitable for holders as per DIN ISO 1173-D 6.3.

Web link
<https://www.wera.de/en/05056343001>

Wera - 840/1 Z Hex-Plus B0
05056343001 - 4013288038562

Wera Werkzeuge GmbH
Korzerter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

With safety pin



For hexagon socket screws with safety pin.

Hex-Plus



Hexagon socket screws are a problem, because the contact surfaces that transfer the force of the tool to the screw are very narrow. The consequence: the head of the screw can be damaged, usually rounding out the recess. Hex-Plus tools have larger contact surfaces to prevent this, driving from the flats of the recess, rather than the corners. Good to know: Hex-Plus tools fit into every standard hexagon socket screw!

Tough bits



Tough Wera bits prevent the tip from breaking prematurely. Z-bits usually are the bit for universal screwdriving applications.

Further versions in this product family:

			
	mm	mm	inch
05056341001	2.0	25	1"
05056342001	2.5	25	1"
05056343001	3.0	25	1"
05056344001	4.0	25	1"
05056345001	5.0	25	1"
05056346001	6.0	25	1"

Web link

<https://www.wera.de/en/05056343001>

Wera - 840/1 Z Hex-Plus B0
 05056343001 - 4013288038562

Wera Werkzeuge GmbH
 Korzelter Straße 21-25
 D-42349 Wuppertal
 Tel: +49 (0)2 02 / 40 45-0
 E-Mail: info@wera.de