




K2A31U, AL Universal Terminal, 2-Conductor, 1-Hole

By Burndy
Catalog # [K2A31U](#)



2 Conductor, #6 AWG-350 kcmil Class B&C, #6 AWG-300 kcmil Class G,H,I,K, DLO, 1-Hole, 1/2" Stud, Tin Plated, Dual Rated

Features

- Dual rated panelboard lugs
- Constructed from high strength, extruded aluminum alloy
- Electro tin-plated to provide low contact resistance

Application

For Aluminum And Copper Conductors

Specifications

Buy American Compliant	Contact Manufacturer
EU RoHS Indicator	No
Buy America(n) Qualified	TAA Compliant (All status valid till December 2026)
Industry Standard(s)	UL 486A-486B
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	NC
Certification - UL Listed Direct Burial	No
UL Listed	Yes
Certification - CSA Approved	Yes

Conductor

Conductor - AL Str Size	• 6 AWG • 4 AWG • 3 AWG • 2 AWG • 1 AWG • 1/0 AWG • 2/0 AWG • 3/0 AWG • 4/0 AWG • 250 kcmil • 266 kcmil • 300 kcmil • 336 kcmil • 350 kcmil
Conductor - AL Str Size Range	6 Str.- 350 Kcmil
Conductor - Copper Str Size	• 6 AWG • 5 AWG • 4 AWG • 3 AWG • 2 AWG • 1 AWG

Conductor Size	• 1/0 • 2/0 AWG • 3/0 AWG • 4/0 AWG • 250 kcmil • 300 kcmil • 350 kcmil
Number Of Conductors	6 AWG-350 KCMIL
Conductor Type	2
Conductor - Copper Str Size Range	• AL C Str-Size • CU C Str-Size 6 Str.- 350 Kcmil

Configuration

Physical Attribute - Number of Holes	1
Connector Type	Parallel Set-Screw

Dimensions

Dimension - Pad Width inch	1.94 in
Package Height	2.250 in
Dimension - Height mm	32 mm
Dimension - Height inch	1.26 in
Dimension - Height fraction	1.25 in
Package Weight	1.690 lb.
Package Length	8.100 in
Package Width	3.450 in
Dimension - L Length Overall mm	73 mm
Dimension - Width fraction	1-47/50 in
Dimension - Hole Size mm	14 mm
Dimension - Hole Size inch	0.56 in
Dimension - Screw Size inch	3/8
Dimension - Stud Size inch	1/2 in
Dimension - Bolt Hole Size inch	0.50 in
Dimension - Bolt Size fraction	1/2
Dimension - Width mm	49 mm
Dimension - Width inch	1.94 in
Dimension - D inch	1.69 in
Dimension - N inch	0.88 in
Dimension - Length Overall inch	2.88 in

Force Related

Installation Torque	275 LBS/in	Hardware Type	3/8 UNC Slotted Set Screw
Recommended in-lb		UPC 14 Digit GTIN	00781810600153
General		Logistics	
Material - Hardware	Aluminum	Minimum Pack Quantity	1
Physical Attribute - Screw Type	Slot	Pallet Quantity	3264
Plated	N	Carton Quantity	132
Sub Brand	UNIVERSAL TERM	Operational	
UPC	781810600153	Temperature Rating	194
Type	Bolted Lugs & Terminals	Product Assets	
Material	Aluminum	Catalog [English]	
Plating Type	Tin plated		
UPC 12 Digit	781810600153		



A Hubbell brand