

Motorbike 4T SAE 10W-40 Street

Description

Fully synthetic high-performance motor oil provides optimum performance and engine protection in all operating conditions. Ensures outstanding engine cleanliness, excellent friction behavior and minimum wear together with perfect clutch operation, and smooth gear shifting.



Properties

- outstanding engine cleanliness
- optimum stability to aging
- high wear resistance
- high shear stability
- ideal with catalytic converters
- especially suitable for wet clutches
- guarantees low oil consumption
- optimum lubrication under all operating conditions

Specifications

API SP • JASO MA2

Technical data

SAE class (engine oils)	10W-40 SAE J300
Density at 59 °F	0,860 g/cm ³ DIN 51757
Viscosity at 104 °F	96,0 mm ² /s ASTM D 7042-04
Viscosity at 212°F	14,6 mm ² /s ASTM D 7042-04
Viscosity at -13 °F (CCS)	<= 7000 mPas ASTM D 5293
Viscosity index	158 DIN ISO 2909
HTHS at 302 °F	≥ 3,5 mPas ASTM D 5481
Pour point	-32 °F DIN ISO 3016
Evaporation loss (Noack)	10,0 % ASTM D 5800-08 Method B
Flash point	460 °F DIN ISO 2592
Total base number	7,0 mg KOH/g DIN ISO 3771
Sulfate ash	0,8 g/100g DIN 51575
Color number (ASTM)	L 2,0 DIN ISO 2049
Oil base	Advanced Full Synthetic

Areas of application

For 4-stroke gasoline engines, with or without a wet clutch, when a motor oil equivalent to current specifications is required or recommended. Safe with catalytic converters.

Application

Observe the manufacturers instructions! Optimum effectiveness only when the product is used in undiluted form.

Available pack sizes

1 l Canister plastic	20054 CAEN-CAFR-USEN
4 l Canister plastic	20056 CAEN-CAFR-USEN
20 l Canister plastic	20302 CAEN-CAFR-USEN
60 l Black plate barrel	22054 CAEN-CAFR-USEN
205 l Black plate barrel	22055 CAEN-CAFR-USEN

Our information is based on thorough research and may be considered reliable, although not legally binding.