

8767 A VDE HF TORX® Zyklop Bit socket, insulated, with 1/4" drive, with holding function, TX 15 x 46 mm



<b>EAN:</b>	4013288233745	<b>Size:</b>	160x120x18 mm
<b>Part number:</b>	05005921001	<b>Weight:</b>	28 g
<b>Article number:</b>	8767 A VDE HF	<b>Country of origin:</b>	CZ
		<b>Customs tariff number:</b>	82079030

- For TORX® socket screws
- Individually tested tools as per IEC 60900 at 10,000 V for safe working up to 1,000 volt
- Extremely short and compact insulated 1/4" bit socket for easy working even in very confined spaces
- Increased safety thanks to 2-component insulation with a yellow insulation core under an outer red insulation layer
- The holding function holds screws securely on the tool
- Plastic sleeve protects surfaces from damage

VDE 1/4" bit socket with holding function for TORX® screws for particularly comfortable screwdriving thanks to a reduced risk of losing the screw when feeding it into the workpiece. With increased safety thanks to the yellow insulation core, which becomes visible if the outer red VDE insulation layer is damaged. Individually tested tools as per IEC 60900 at 10,000 V for safe working at the approved voltage of 1,000 V.

**Web link**

<https://www.wera.de/en/05005921001>

Wera - 8767 A VDE HF  
05005921001 - 4013288233745

Wera Werkzeuge GmbH  
Korzter Straße 21-25  
D-42349 Wuppertal  
Tel: +49 (0)2 02 / 40 45-0  
E-Mail: [info@wera.de](mailto:info@wera.de)

**Bit sockets with holding function for TORX® screws**



The HF tools developed by Wera are ideal because they feature an optimised geometry of the original TORX® profile. The wedging forces resulting from the surface pressure between the drive tip and the screw profile mean that TORX® screws made according to Camcar Innovations, Michigan, USA specifications are securely held on the tool!

**Individually tested**



The individual testing at 10,000 volts, in accordance with IEC 60900, ensures safe working with loads up to 1,000 volts.

**Increased safety**



The Zyklop sockets and extensions for electricians offer increased safety thanks to their 2-component insulation with a yellow insulation core under an outer red insulation layer.

**Further versions in this product family:**



mm



mm



mm

05005920001	TX 10	46.0	18.0	9.0
<b>05005921001</b>	<b>TX 15</b>	<b>46.0</b>	<b>18.0</b>	<b>9.0</b>
05005922001	TX 20	46.0	18.0	9.0
05005923001	TX 25	46.0	18.0	9.0
05005924001	TX 27	46.0	18.0	9.0
05005925001	TX 30	46.0	18.0	9.0
05005926001	TX 40	46.0	18.0	9.0

**Web link**

<https://www.wera.de/en/05005921001>

Wera - 8767 A VDE HF  
05005921001 - 4013288233745

Wera Werkzeuge GmbH  
Korzter Straße 21-25  
D-42349 Wuppertal  
Tel: +49 (0)2 02 / 40 45-0  
E-Mail: info@wera.de