



jalas® EXALTER 9925

ASTM F2413-18 M/I/C/SD 35/PR EN ISO 20345:2011 S1P, SRC, HRO

Learn more

LOW-CUT WITH VENTILATION AND BOA®

This low-cut safety shoe has the features you need for most work situations, such as PTC-textile nail protection, toecap in aluminum and high-grip Vibram Nitrile rubber outsole. The midsole and JALAS FX3 Supreme multilayer insole together with the sock-like construction provide ultimate comfort. PORON® XRD™ shock-absorption prevents injuries to foot and back. The upper has net-covered ventilation holes to keep feet cool and prevent particles from entering the shoes. BOA® Fit System makes it easy to put on and take off the shoe.

CHARACTERISTICS

- Excellent grip
- Perfect fit
- Extra comfortable
- Very breathable
- Excellent shock absorption

FUNCTIONS

- Breathable mesh
- Heat-resistant outsole
- Oil-resistant outsole
- Anti-static properties
- Polstered shaft edge
- Ventilating insole
- BOA® Fit System
- Quick-tie
- Stabilizator
- Ergonomically shaped
- Soft
- Specially designed details
- Double shock absorption zones
- Conforms with IEC 61340-5-1 (ESD)
- Free from animal-derived materials

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

PREVENTS RISK OF

Toe injuries, Nail penetration, Sprain injuries, Antistatic

PRIMARY ENVIRONMENTS OF USE

Outdoors, Indoors, Environments with risk for outsole penetration, Dry environments, Clean environments, Warm environments

SPECIFICATION

TYPE Safety footwear, Low shoes
CATEGORY Cat. II
NAIL PROTECTION MATERIAL Plasma-treated composite (PTC) textile
FITTING Regular
COLLECTION Exalter
UPPER MATERIAL Microfiber, Textile
TOECAP MATERIAL Aluminium
LINING MATERIAL Polyester
INSOLE JALAS 8303 FX3 Supreme
INNERSOLE MATERIAL Textile, Soft EVA, Rigid EVA, Polyester-based conductive thread, Neo foam, Double shock absorption zones in PORON® XRD®
MIDSOLE MATERIAL PU midsole
OUTSOLE MATERIAL Nitrile rubber outsole
FASTENING BOA® Fit System
COLOUR Black
NET WEIGHT, (SIZE 42) 1.31 kg

COMPLIANCE

CE Cat. II

EAC TP TC 019:2011

ASTM F2413-18
M/I/C/SD 35/PR

EN ISO 20345:2011
S1P, SRC, HRO

FEATURES

- Anti-static properties
- Ergothan Shock Absorption System
- ESD
- Aluminium toecap
- Oil-resistant outsole
- Nail protection in plasma-treated composite (PTC) textile
- Stabilizator
- Heat-resistant outsole

SIZE				ARTICLE NUMBER	EAN
EU	UK	US M	US W		
34	1.5	2.5	3.5	9925-34	6408487513473
35	2	3.5	4	9925-35	6408487513480
36	3	4	5	9925-36	6408487513497
37	4	5	6	9925-37	6408487513503
38	5	5.5	6.5	9925-38	6408487513510
39	6	6.5	7.5	9925-39	6408487513527
40	6.5	7.5	8.5	9925-40	6408487513534
41	7	8	9	9925-41	6408487513541
42	8	9	10	9925-42	6408487513558
43	9	9.5	11	9925-43	6408487513565
44	10	10.5	11.5	9925-44	6408487513572
45	10.5	11	12.5	9925-45	6408487513589
46	11	12	13	9925-46	6408487513596
47	12	13	14	9925-47	6408487513602

ejendals
Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.