ABB BALDOR RELIANCE

Customer information packet

XL050745A

.75HP, 1760RPM, 1PH, 60HZ, 56, 3528L, XPFC, F1
Class - CLI GP C,D; CLII GP F,G
Division - Division I

Copyright © All product information within this document is subject to ABB Motors and Mechanical Inc. copyright © protection, unless otherwise noted.
11/5/2026 11:09:01 AM

Specifications

Enclosure	XPFC
Frame	56
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	CLI GP C,D; CLII GP F,G
Haz Area Division	Division I
Motor Letter Type	Cap Start, Induction Run
Output @ Frequency	.750 HP @ 60 HZ
Phase	1
Synchronous Speed @ Frequency	1800 RPM @ 60 HZ
Voltage @ Frequency	115.0 V @ 60 HZ
	230.0 V @ 60 HZ
Agency Approvals	UL
	CSA
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	10.400 A @ 115.0 V
	5.200 A @ 230.0 V
Design Code	N
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	66.0 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Shaft Indicator	None
Haz Area Temp Code	T4
Heater Indicator	No Heater
High Voltage Full Load Amps	5.2 a

Part Detail

Revision	B
Type	AC
Mech. spec.	35U585
Base	
Status	PRD/A
Elec. spec.	35WGF218
Layout	35LYU585
Eff. date	03-24-2026
CD Diagram	CD0008
Poles	04
Leads	6#18,1#14 #4TH
Proprietary	False
Created date	11-14-2024

Insulation Class	F
Inverter Code	Not Inverter
KVA Code	M
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	No Locked Bearing
Motor Lead Quantity/Wire Size	6 @ 18 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	X3528L
Mounting Arrangement	F1
Number of Poles	4
Overall Length	15.17 IN
Power Factor	68
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Pulley Shaft Indicator	Standard
Rodent Screen	None
RoHS Status	ROHS COMPLIANT
Service Factor	1.00
Shaft Diameter	0.625 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	1760 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	Automatic Thermal Overload
Winding Thermal 1 Location	EP
Winding Thermal 2	None

Nameplate

NP0301XPSL							
NO.			**CC**				
SER.							
SPEC.	35U585F218G1						
CAT.NO.	XL050745A						
HP	.75		**T. CODE**	T4			
VOLTS	115/230						
AMPS	10.4/5.2						
RPM	1760						
HZ	60	**PH**	1	**CL**	F		
SER.F.	1.00	**DES**	N	**CODE**	M		
RATING	40C AMB-CONT						
FRAME	56		**NEMA-NOM-EFF**	66			
		PF	68				
BLANK	NEMA MG-1 PART 5, IP54						


AC Induction Motor Performance Data
Record # 112532
Typical performance - not guaranteed values


Winding: 35WGF218-R001	**Type:** 3528L	**Enclosure:** XPFC

Nameplate Data				**115 V, 60 Hz: Low Voltage Connection**	
Rated Output (HP)			.75	**Full Load Torque**	2.236 LB-FT
Volts			115/230	**Start Configuration**	direct on line
Full Load Amps			10.4/5.2	**Breakdown Torque**	9.31 LB-FT
R.P.M.			1740	**Pull-up Torque**	7.75 LB-FT
Hz	60	**Phase**	1	**Locked-rotor Torque**	10.8 LB-FT
NEMA Design Code	N	**KVA Code**	N	**Starting Current**	73 A
Service Factor (S.F.)			1	**No-load Current**	7.7 A
NEMA Nom. Eff.	66	**Power Factor**	69	**Line-line Res. @ 25ºC**	0.75553 Ω A Ph 1.79 Ω B Ph
Rating - Duty			40C AMB-CONT	**Temp. Rise @ Rated Load**	52°C


Load Characteristics 115 V, 60 Hz, 0.75 HP

% of Rated Load	**25**	**50**	**75**	**100**	**125**	**150**
Power Factor	34	48	59	68	74	80
Efficiency	46.1	61.4	67.6	70.4	70.9	70
Speed	1788.9	1780.5	1771.8	1761	1749.6	1734.2
Line amperes	7.89	8.38	9.21	10.3	11.6	13.3


ABB Motors and Mechanical Inc.
WINDING # 35WGF218
Typical performance - not guaranteed values.
0.75 HP 1 PH 60 HZ 1740 RPM 115 V 3528L
TORQUES(LB-FT): PO=9.31 PU=7.75 LR=10.8 LRA=73
TORQUE
RPM
WATTS
AMPS
EFF
PF
%EFF %PF
TORQUE (LB-FT)
RPM
WATTS
AMPS
PERCENT OF RATED OUTPUT (0.75 HP)
11/5/2026 ACPERF, record # 112532


35LYU585
510-520 = 14.30
521-528 = 15.17
529-535 = 16.04
536-546 = 17.42
4.73
2.41
1.88
.19 KEY
1.38 LONG
FOR HAZARDOUS LOCATIONS
X-PROOF NAMEPLATE
Ø .6250
.6245
3.00
.66
2.76
4.32
4 SLOTS
.34 WIDE
6.85
7.19
7.07
3.50
3.44
2.49
2.49
LEAD HOLE
.75 N.P.T.
4.81
3.31
6.62
CUSTOMER IS RESPONSIBLE FOR DETERMINING THAT THE PRODUCT WILL PERFORM SUITABLY IN THE INTENDED APPLICATION
REV. DESC: CONVERT AUTOCAD DRW TO SWD DRW
REV: A
VERSION: 01
REVISED: 10:58:22 04/21/2023
TDR: 000001207032
MODEL NO. 35LYU585
REF: -
BY: ENALEM0
B
BALDOR - RELIANCE®
HORZ 56 XPFC X35L CLI GP C&D CLII GP F&G
35LYU585

CD0008



	LINE A	LINE B	JOIN	JOIN
HIGH STD	1	4	2,3,8	J,5
HIGH OPP	1	4	2,3,5	J,8
LOW STD	1,3,8	4	—	2,J,5
LOW OPP	1,3,5	4	—	2,J,8

NOTES:

1. STANDARD ROTATION IS CCW FACING END OPPOSITE SHAFT EXTENSION.
2. MULTIPLE CAPACITORS ARE CONNECTED IN PARALLEL UNLESS OTHERWISE SPECIFIED.
3. LEAD COLORS ARE OPTIONAL. LEADS MUST ALWAYS BE NUMBERED AS SHOWN.

CD0008

REV. DESC: REMOVE 2—TERMINAL THERMAL DETAIL, SEE CD0008A02			BALDOR ELECTRIC Co.
REV. LTR: F	VERSION: 01	TDR: 000000360649	
CD0008	FILE: \AAA\00007\408	REVISED: 10:56:54 04/18/2005	TYPE L, DV, REV, THERMAL, 7 LEADS
	MTL: —	BY: ENJOEP0	