

Hard Drive Enclosure for 3.5in SATA Drives - USB 3.0

Product ID: S3510SMU33



The S3510SMU33 USB 3.0 hard drive enclosure enables you to connect a 3.5in SATA hard drive through an available USB port.

With support for UASP, the enclosure performs up to 70% faster than conventional USB 3.0, when paired with a UASP-enabled host controller to utilize the full potential of your SATA III hard drives. See our UASP testing results below for further details.

The HDD enclosure offers a versatile solution for increasing the storage/backup capabilities of your computer, with support for SATA I/II/III hard drives at capacities of up to 4TB. Plus, the enclosure features high-quality aluminum construction and a stylish silver design that looks great in any application.

To ensure compatibility with your computer system, the S3510SMU33 supports all of the leading operating systems, including: Windows, OSX, Linux and Google Chrome.

The S3510SMU33 USB 3.0 HDD enclosure is backed by a 2-year StarTech.com warranty and free lifetime technical support.

UASP is supported in Windows 8, Mac OSX (10.8 or above), and Linux. In testing UASP performs with a 70% faster read speed and 40% faster write speed over traditional USB 3.0 at peak performance.

At the same peak in testing UASP also shows an 80% reduction in required processor resources.

Testing results were obtained using an Intel Ivy Bridge system, a UASP enabled StarTech.com Enclosure, and a SATA III solid state drive.

Certifications, Reports and Compatibility

Applications



- Take advantage of new laptops and desktops with USB 3.0 (UASP) connectivity
- Turn a high capacity SATA hard drive into portable, external storage
- Create a fast, portable external storage solution for desktops, laptops or ultrabooks
- Upgrade from a USB 2.0 drive enclosure to faster USB 3.0
- Add on extra storage to almost any USB-enabled computer system
- Share large files between computers quickly and securely without a network
- Retrieve data from an old SATA drive, or turn the unused drive into additional external storage space

Features

- Compliant with USB Attached SCSI Protocol (UASP) Transport Specifications
- Lightweight and durable aluminum enclosure
- SuperSpeed USB 3.0 compliant host interface supporting data transfer rates up to 5Gbps
- Backward compatible with high Speed USB 2.0 host interface, with transfer rates up to 480Mbps
- Power/Activity LED indicator
- Compatible with SATA revision I/II/III (1.5/3.0/6.0 Gbps) drives
- Plug-and-Play and Hot-Swap compatible

| Hardware | | |
|----------|------------------------|--------------------|
| | Warranty | 2 Years |
| | Fan(s) | No |
| | Interface | USB 3.0 |
| | Number of Drives | 1 |
| | Drive Size | 3.5in |
| | Compatible Drive Types | SATA |
| | Drive Installation | Fixed |
| | Chipset ID | ASMedia - ASM1153E |

Performance



| | Type and Rate | USB 3.0 - 5 Gbit/s |
|---------------------------------|----------------------------------|---|
| | UASP Support | Yes |
| | Type and Rate | SATA III (6 Gbps) |
| | Hardware Raid Supported | No |
| | Max Drive Capacity | No maximum currently known; tested with up to 14TB 7200 RPM hard drive. |
| Connector(s) | | |
| | Drive Connectors | SATA Data & Power Combo (7+15 pin) |
| | Host Connectors | USB Type-B (9 pin) USB 3.0 |
| Software | OS Compatibility | OS independent; No software or drivers required |
| Special Notes / Requirements | System and Cable Requirements | Available USB port |
| Indicators | LED Indicators | Power & Activity |
| Power | | |
| | Power Source | AC Adapter Included |
| | Input Voltage | 100 - 240 AC |
| | Input Current | 0.6 A |
| | Output Voltage | 12V DC |
| | Output Current | 2 A |
| | Center Tip Polarity | Positive |
| | Power Consumption (In Watts) | 24 |
| Environmental | | |
| | Operating Temperature | 0C to 40C (32F to 104F) |
| | Storage Temperature | -10C to 65C (14E to 149E) |

Storage Temperature -10C to 65C (14F to 149F)



| Humidity: 10% ~ 90% RH |
|---------------------------------------|
| umidity: 5% ~ 95% RH |
| |
| |
| and Plastic |
| 2 cm] |
| ⊧mm] |
| i cm] |
| 21 g] |
| |
| sm] |
| 5 cm] |
| 5 cm] |
| 97 g] |
| |
| 0.0 SATA III HDD Enclosure |
| |
| Power Adapter (NA/JP / UK / EU / ANZ) |
| |
| able (1m) |
| |
| |

*Product appearance and specifications are subject to change without notice.