


Swing clamp cylinder CLR-50-20-L-P-A-K11-R8

Part number: 535500

FESTO



Data sheet

| Feature | Value |
|--|--|
| Complete stroke | 41 mm |
| Piston diameter | 50 mm |
| Piston rod thread | M10 |
| Swivel angle | 90 deg +/- 2 deg |
| Clamping stroke | 20 mm |
| Type code | CLR |
| Cushioning | Elastic cushioning rings/pads at both ends |
| Mounting position | Any |
| Structural design | Piston Piston rod Cylinder barrel |
| Position sensing | For proximity sensor |
| Swivel direction | Left |
| Symbol | 00991217 |
| Variants | Weld spatter protection Dust protection |
| Operating pressure | 2 bar ... 10 bar |
| Mode of operation | Double-acting |
| Operating medium | Compressed air as per ISO 8573-1:2010 [7:4:4] |
| Information on operating and pilot media | Operation with oil lubrication possible (required for further use) |
| Corrosion resistance class (CRC) | 2 - Moderate corrosion stress |
| Ambient temperature | -10 °C ... 80 °C |
| Effective clamping force at 2 bar | 271 N |
| Effective clamping force at 4 bar | 508 N |
| Effective clamping force at 6 bar | 716 N |
| Max. clamping finger screw tightening torque | 47 Nm |
| Theoretical clamping force at 6 bar | 990 N |
| Product weight | 1690 g |
| Type of mounting | Optionally: With through-hole With internal thread With accessories |
| Pneumatic connection | G1/8 |
| Scraper material | PPS |
| Flange screws material | Steel Galvanized |
| Cover material | Wrought aluminum alloy Coated |

| Feature | Value |
|-----------------------------|---|
| Seals material | NBR TPE-U(PU) |
| Housing material | Wrought aluminum alloy Smooth anodized |
| Piston rod material | Coated High-alloy stainless steel |
| Material of cylinder barrel | Wrought aluminum alloy Smooth anodized |