


Compact air cylinder ADNGF-3"-1 1/2"-P-A

Part number: 557275

FESTO



Data sheet

Feature	Value
Stroke	38.1 mm
Piston diameter	3"
Type code	ADNGF
Based on norm	ISO 21287
Cushioning	Elastic cushioning rings/pads at both ends
Mounting position	Any
Structural design	Piston Piston rod Profile barrel
Position sensing	For proximity sensor
Protection against torsion/guide	Guide rod with yoke
Operating pressure	0.1 MPa ... 1 MPa
Operating pressure	1 bar ... 10 bar
Mode of operation	Double-acting
Operating medium	Compressed air as per ISO 8573-1:2010 [7:4:4]
Information on operating and pilot media	Operation with oil lubrication possible (required for further use)
Corrosion resistance class (CRC)	2 - Moderate corrosion stress
Ambient temperature	-20 °C ... 80 °C
Impact energy in the end positions	1.79917 J
Theoretical force at 6 bar, retracting	2827.001 N
Theoretical force at 6 bar, advancing	3016.002 N
Moving mass at 0 mm stroke	780.787 g
Additional weight per 10 mm stroke	43.149 g
Basic weight with 0 mm stroke	1684.018 g
Additional moving mass per 10 mm stroke	97.354 g
Type of mounting	Optionally: With through-hole With internal thread With accessories
Pneumatic connection	1/8 NPT
Flange screws material	Steel
Cover material	Wrought aluminum alloy Anodized
Seals material	NBR
Material of dynamic seals	TPE-U(PU)
Piston rod material	High-alloy steel

Feature	Value
Material of cylinder barrel	Wrought aluminum alloy Smooth anodized