



Ball screw linear actuator ELGC-BS-KF-60-500-12P

Part number: 8061495

FESTO



Data sheet

| Feature | Value |
|--|---|
| Working stroke | 500 mm |
| Size | 60 |
| Stroke reserve | 0 mm |
| Screw diameter | 12 mm |
| Spindle pitch | 12 mm/U |
| Type code | ELGC |
| Mounting position | Any |
| Guide | Recirculating ball bearing guide |
| Structural design | Electromechanical linear axis with ball screw |
| Motor type | Stepper motor Servo motor |
| Spindle type | Ball screw drive |
| Symbol | 00991211 |
| Max. acceleration | 15 m/s ² |
| Max. rotational speed | 4000 1/min |
| Max. speed | 0.8 m/s |
| Repetition accuracy | ±0.01 mm |
| Degree of protection | IP40 |
| Ambient temperature | 0 °C ... 50 °C |
| 2nd moment of area Iy | 441000 mm ⁴ |
| 2nd moment of area Iz | 542000 mm ⁴ |
| No-load torque at maximum travel speed | 0.246 Nm |
| No-load torque at minimum travel speed | 0.042 Nm |
| Max. force Fy | 600 N |
| Max. force Fz | 1800 N |
| Fy with theoretical service life of 100 km (from a guide perspective only) | 2208 N |
| Fz with theoretical service life of 100 km (from a guide perspective only) | 6624 N |
| Max. torque Mx | 29.1 Nm |
| Max. torque My | 31.8 Nm |
| Max. torque Mz | 31.8 Nm |
| Mx with theoretical service life of 100 km (from a guide perspective only) | 107 Nm |
| My with theoretical service life of 100 km (from a guide perspective only) | 117 Nm |
| Mz with theoretical service life of 100 km (from a guide perspective only) | 117 Nm |
| Max. feed force Fx | 200 N |

| Feature | Value |
|---|--|
| Torsion moment of inertia It | 29800 mm ⁴ |
| Mass moment of inertia JH per meter of stroke | 0.10779 kgcm ² |
| Mass moment of inertia JL per kg of payload | 0.036476 kgcm ² |
| Mass moment of inertia JO | 0.02235 kgcm ² |
| Feed constant | 12 mm/U |
| Moving mass | 525 g |
| Additional weight per 10 mm stroke | 51 g |
| Dynamic deflection (load moved) | 0.05% of axis length, maximum 0.5 mm |
| Static deflection (load at standstill) | 0.1 % of axis length |
| Interface code, actuator | T42 |
| Material of end caps | Die cast aluminum, painted |
| Profile material | Wrought aluminum alloy, anodized |
| Note on materials | Contains paint-wetting impairment substances RoHS-compliant |
| Cover strip material | High-alloy stainless steel |
| Drive cover material | Die cast aluminum, painted |
| Slide carriage material | Steel |
| Guide rail material | Steel |
| Slide material | Die-cast aluminum |
| Spindle nut material | Steel |
| Spindle material | Steel |