



A CSW Industrials Company

PRODUCT DATA SHEET

RECTORSEAL® PTFE TAPE  
Pipe Thread Sealant Tape

Description

RectorSeal PTFE Tape can be used on all metal and plastic threaded pipe joints to seal against internal pressure at temperatures from -100°F to +550°F. Available in a wide variety of sizes.

Packaging

Product Code	Size	Quantity (per case)	Lbs/Case	Cubic Feet/Case
35942	1/2" x 260"	12	1	0.67
35943	1/2" x 520"	12	1	0.72
35944	1/2" x 1296"	12	1	1.20
35945	3/4" x 260"	12	1	1.13
35946	3/4" x 520"	12	1	1.13
35947	3/4" x 1296"	12	2	1.17
35949	1" x 520"	12	2	0.67
66687	1/2" x 520"	100	4	0.22
66688	1/2" x 260"	100	3	0.18
66689	1/2" x 260" (Yellow)	100	3	0.18



Applications

- Can be used on all metal and plastic threaded pipe joints.

Characteristics | Features

- Resistant to most liquids or gases
- Non-toxic
- Completely inert
- Non-flammable

Instructions

READ ALL DIRECTIONS, SDS AND WARNINGS ON LABEL BEFORE USING

1. Clean pipe threads of all debris and oils.
2. Wrap tape tightly onto the threads in the direction the fitting will be threaded when making the joint.
3. Use enough layers of wrapping to ensure a good seal will be made. This will depend on how good the threads on the pipe and fitting have been made.
4. Tighten in the normal manner.
5. Do not reuse a taped joint without removing the old tape and replacing it with new.

For additional technical information, call Toll Free 1-800-231-3345

# RECTORSEAL® PTFE TAPE

Pipe Thread Sealant Tape

## PRECAUTIONS

**FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT, CALL CHEMTREC - DAY OR NIGHT 1-800-424-9300**

This product is chemically inert and non-toxic. Precaution should be taken, however to ensure persons do not take this material orally. KEEP OUT OF REACH OF CHILDREN. If not applied to pipe threads correctly, shreds of this product may come loose in the pipe and stop up valves, faucets, and spray nozzles.

**For additional information, refer to Safety Data Sheet.**

## SPECIFICATIONS

Shelf Life - Unlimited

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances.

## Limited Warranty

RectorSeal, LLC makes the Limited Express Warranty that when the instructions for storage and handling of our products are followed we warrant our products to be free from defects. THIS LIMITED EXPRESS WARRANTY IS EXPRESSLY IN LIEU OF ANY OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND OF ANY OTHER OBLIGATION ON THE PART OF RectorSeal, LLC. The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and RectorSeal, LLC shall not be liable for incidental or consequential damages.

Manufactured by

**RectorSeal® LLC • 2601 Spenwick Drive, Houston, TX 77055, USA • 800-231-3345 • Fax 800-441-0051 • [rectorseal.com](http://rectorseal.com)**

A CSW Industrials Company. RectorSeal, the logos and other trademarks are property of RectorSeal, LLC, its affiliates or its licensor's and are protected by copyright, trademark and other intellectual property laws, and may not be used without permission. RectorSeal reserves the right to change specifications without prior notice. ©2019 RectorSeal. All rights reserved. R50410-0719