



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center
Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center
Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support
Phone: 1-800-733-4755

PRODUCT DATA

LUBRIPLATE PAN DIVIDER OIL

"This product is certified OU Kosher Pareve"
"This product is Halal certified"

*NSF International H-1 & 3H Registered
NSF ISO21469 Certification

DESCRIPTION

LUBRIPLATE Pan Divider Oil Meets U.S. FDA Regulation 21 CFR 172.878 for direct contact with food.

APPLICATIONS

It is recommended for pan divider oil applications.

ADVANTAGES

"LUBRIPLATE Pan Divider Oil contains no components derived from TSE/BSE relevant animal species; therefore, it is compliant with the requirements of the TSE Note for Guidance EMA/410/01 Rev. 3 July 2011".

STORAGE RECOMMENDATIONS

1. Products should be stored between 40°F-120°F.
2. Products should be stored in a dry covered environment.
3. Products should not be stored in warm, direct sunlight.
4. improper storage conditions can significantly alter the shelf life of the product. Such conditions would include temperature, moisture, open containers, etc.

Typical Test Data

| PROPERTY | TEST METHOD | TYPICAL RESULTS* |
|-------------------------|-------------|------------------|
| Viscosity cSt @ 40°C | ASTM D-445 | 25.2 |
| Viscosity SUS @ 100°F | ASTM D-2161 | 130 |
| Viscosity SUS @ 210°F | ASTM D-2161 | 58.1 |
| Gravity °API | ASTM D-4052 | 33.3 |
| Specific Gravity @ 25°C | ASTM D-1298 | 0.853 |
| Flash Point | ASTM D-92 | 410°F/210°C |
| Pour Point | ASTM D-97 | 0°F/-18°C |
| Color, Saybolt | ASTM D-156 | +30, Clear |

PACKAGING AVAILABLE

55 Gallon Drum
5 Gallon Pail

Part No.

L0747-062
L0747-060

*NSF International H1 & 3H Registration No. **139787**
(Meets former USDA 1998 Guidelines)

*Registered H-1 by NSF International for use in food processing facilities as a lubricant or anti-rust agent on equipment in which there may be incidental contact involving the lubricated part and the edible product.

*Registered 3H by NSF International - This product is acceptable for use as a Release Agent on grills, ovens, loaf pans, boning benches, chopping boards or other hard surfaces in contact with meat and poultry food products to prevent food from adhering during processing.

