

# XL TIMING BELTS

0.200" Pitch

Standard Widths:

1/4" and 3/8"

Neoprene Construction

Fiberglass Reinforcements

(Note: Custom belt widths are available upon request.)



Timing Belts



Part Number	No. of Teeth	Pitch Length (in)
456XL	228	45.600
460XL	230	46.000
468XL	234	46.800
470XL	235	47.000
480XL	240	48.000
486XL	243	48.600
490XL	245	49.000
492XL	246	49.200
496XL	248	49.600
498XL	249	49.800
500XL	250	50.000
506XL	253	50.600
510XL	255	51.000
514XL	257	51.400
522XL	261	52.200
524XL	262	52.400
532XL	266	53.200

Part Number	No. of Teeth	Pitch Length (in)
540XL	270	54.000
554XL	277	55.400
560XL	280	56.000
564XL	282	56.400
570XL	285	57.000
580XL	290	58.000
592XL	296	59.200
608XL	304	60.800
612XL	306	61.200
630XL	315	63.000
638XL	319	63.800
648XL	324	64.800
670XL	335	67.000
672XL	336	67.200
686XL	343	68.600
690XL	345	69.000
736XL	368	73.600

Part Number	No. of Teeth	Pitch Length (in)
770XL	385	77.000
810XL	405	81.000
828XL	414	82.800
850XL	425	85.000
860XL	430	86.000
888XL	444	88.800
900XL	450	90.000
908XL	454	90.800
914XL	457	91.400
926XL	463	92.600
1014XL	507	101.400
1020XL	510	102.000

Neoprene XL timing belt part numbers can be determined as follows:  
 Pitch Length Code + XL + Width Code + (G for fiberGlass reinforcements)  
 Example: 532XL025G



For XL pitch pulley stock and flanges, see page 258



For matching XL pitch timing pulleys, see page 15.