

VB.639 | Three-arm knobs

Technopolymer

INCH

RoHS

PA

+270 °F
-20 °F

- 1
- 2
- 3
- 4
- 5
- 6
- 7
- 8
- 9
- 10
- 11
- 12
- 13
- 14
- 15
- RH

MATERIAL

Glass-fibre reinforced polyamide (PA) technopolymer, black colour, matte finish.

VB.639/130: glass-fibre reinforced polypropylene based (PP) technopolymer, black colour, matte finish.

STANDARD EXECUTIONS

- **VB.639-A:** black-oxide steel boss, plain blind hole.
- **VB.639-B:** brass boss, threaded blind hole.
- **VB.639-FP:** brass boss, threaded pass-through hole.
- **VB.639-p:** zinc-plated steel threaded stud, chamfered flat end according to ISO 4753 (see Technical Data on page -).

APPLICATIONS


This knob has been designed for heavy duty work where the use of a hammer for a firmer clamping action is required.

OTHER EXECUTIONS ON REQUEST

Metric plain or threaded blind holes.



ELESA Original design



VB.639-A


INCH

Code	Description	D	d	L	d1	d2	d3	l1	l2	h	C# [ft lb]	L* [ft lb]	⚖
965631	VB.639/63 A-5/16	2.48	0.312	1.1	1.02	0.59	0.71	0.98	0.91	0.71	22	5	0.12
965672	VB.639/80 A-3/8	3.15	0.375	1.38	1.26	0.59	0.83	1.18	0.98	0.79	59	4	0.17
965701	VB.639/100 A-3/8	3.94	0.375	1.65	1.42	0.79	0.98	1.42	1.29	0.98	81	6	0.29
965702	VB.639/100 A-1/2	3.94	0.500	1.65	1.42	0.79	0.98	1.42	1.29	0.98	81	6	0.29
965742	VB.639/130 A-1/2	5.12	0.500	1.85	1.69	0.79	1.14	1.57	1.22	0.94	99	7	0.4

"Max limit Tightening torque" means the max torque value at which the metal insert, in normal conditions of use, is perfectly and strongly anchored to the plastic material.

* For impact strength (L) see Technical Data on page .

Clamping knobs



VB.639-B

INCH

Code	Description	D	d2B	L	d1	d3	l1	h	C# [ft lb]	L* [ft lb]	⚖
965635	VB.639/63 B-5/16-18	2.48	5/16-18	1.1	1.02	0.71	0.98	0.59	22.11	5.16	0.11
965637	VB.639/63 B-3/8-16	2.48	3/8-16	1.1	1.02	0.71	0.98	0.67	22.11	5.16	0.09
965675	VB.639/80 B-3/8-16	3.15	3/8-16	1.38	1.26	0.83	1.18	0.67	58.96	4.42	0.13
965677	VB.639/80 B-1/2-13	3.15	1/2-13	1.38	1.26	0.83	1.18	0.67	58.96	4.42	0.15
965703	VB.639/100 B-3/8-16	3.94	3/8-16	1.65	1.42	0.98	1.42	0.79	81.07	5.9	0.21
965705	VB.639/100 B-1/2-13	3.94	1/2-13	1.65	1.42	0.98	1.42	0.79	81.07	5.9	0.23
965743	VB.639/130 B-1/2-13	5.12	1/2-13	1.85	1.69	1.14	1.57	0.87	99.5	6.63	0.36
965745	VB.639/130 B-5/8-11	5.12	5/8-11	1.85	1.69	1.14	1.57	0.87	99.5	6.63	0.36

VB.639-FP

INCH

Code	Description	D	d2B	L	d1	d2	d3	l1	l2	C# [ft lb]	L* [ft lb]	⚖
965591	VB.639/45 FP-1/4-20	1.77	1/4-20	0.98	0.75	0.35	0.35	0.89	0.47	8.11	1.47	0.07
965642	VB.639/63 FP-5/16-18	2.48	5/16-18	1.1	1.06	0.63	0.51	0.98	0.83	22.11	5.16	0.1
965682	VB.639/80 FP-3/8-16	3.15	3/8-16	1.38	1.26	0.71	0.67	1.18	0.98	58.96	5.16	0.18
965684	VB.639/80 FP-1/2-13	3.15	1/2-13	1.38	1.26	0.71	0.67	1.18	0.98	58.96	5.16	0.17
965712	VB.639/100 FP-1/2-13	3.94	1/2-13	1.65	1.42	0.79	0.79	1.46	1.22	81.07	5.9	0.23
965752	VB.639/130 FP-5/8-11	5.12	5/8-11	1.85	1.69	0.94	0.87	1.57	1.34	99.5	6.63	0.35

VB.639-p

INCH

Code	Description	D	d2A	L	d1	d3	l	l1	C# [ft lb]	L* [ft lb]	⚖
965604	VB.639/45 p-1/4-20x1	1.77	1/4-20	0.98	0.75	0.47	1.000	0.89	7.37	1.47	0.06
965621	VB.639/45 p-3/8-16x3/4	1.77	3/8-16	0.98	0.75	0.47	0.750	0.89	16.95	1.47	0.07

"Max limit Tightening torque" means the max torque value at which the metal insert, in normal conditions of use, is perfectly and strongly anchored to the plastic material.

* For impact strength (L) see Technical Data on page .

