



## Body Filter 95+®

Provides breathable protection with a holdout of particulate size down to 0.3 microns at up to 99% efficiency– that's similar performance to that of an N-95 respirator!

Body Filter 95+® protects the wearer against dangerous particulates while providing additional relief from heat build-up. Exceptional abrasion and tear strength makes this garment suitable for many tough environments including dirt, mold, dust in addition to the grease and grime found in many tough industrial settings.

### Available Garments



**Coverall with Elastic  
Wrists & Open Ankles**

#4012  
25 per case



**Coverall with  
Attached Hood**

#4028  
25 per case



**Coverall with Attached  
Hood & Boots**

#4014  
25 per case



**Sleeves,  
18" Length**

#4065  
200 per case



**Shoe Covers with  
Vinyl Sole**

#4100  
200 per case



**Lab Coat, No Pockets,  
with Knit Wrists**

#4026KW  
50 per case

## Body Filter 95+®

Filters down to 0.3 microns  
at up to 99% efficiency

### Common Workplace Particle Sizes



## Body Filter 95+®

TEST CONDUCTED	TEST METHOD	TEST RESULT
Tensile Strength - Machine Direction	ASTM D5034	79.5 lbs
Tensile Strength - Cross Direction	ASTM D5034	57.0 lbs
Trapezoidal Tear - Machine Direction	ASTM D5587	12.8 lbs
Trapezoidal Tear - Cross Direction	ASTM D5587	21.0 lbs
Mullen Burst	ASTM D3786	109 psi
Fabric Thickness	ASTM D1777	0.47 mm
Air Permeability	Method D737 (20 Pa)	8.65 cfm
Penetration*	TSI 8130	0.0548%

\* Tested at a flow rate of 2.3 liters/min., 100 cm² filter area using a sodium chloride aerosol having a mean particle size of 0.3 microns



### Exceptional breathability

Designed for superior airflow and breathability compared to many competitive fabrics.



### Enhanced mobility

Wider, gusseted crotch gives the wearer more room to move in all directions without ripping fabric.



### Durable design

Roomy, seamless shoulder area resists tears and provides more protection in key exposure areas.



### Superior protection

Holdout of particulate size down to 0.3 microns at up to 99% efficiency.



(800) 345-5972



2400 Skyline Dr., Suite 400  
Mesquite, Texas 75149



int-enviroguard.com