Product data sheet
Characteristics

NF600SFBH
NF Panelboard Acc. Subfeed Breaker Kit 600A, H Frame

Main

Product	Circuit Breaker Sub-Feed Lug
Provided equipment	Cover plate 1 Mounting plate 1 Bracket for support 2 Screw set 1 Rail extension 2 Rail splice 2 Lug 5 Cables 6 Closing plate 1
Circuit breaker type	H-frame

Complementary

Current Rating	600 A
Tightening torque	60.18…64.61 lbf.in (6.8…7.3 N.m)

Environment

Product certifications	CULus

Ordering and shipping details

Category	08338 - NF (& SHARED) RTI ACCESSORIES
Discount Schedule	PE1A
GTIN	00785901834649
Nbr. of units in pkg.	1
Package weight(Lbs)	1 lb(US) (0.45 kg)
Returnability	Yes
Country of origin	US

Packing Units

Package 1 Height	7.20 in (18.288 cm)
Package 1 width	13.30 in (33.782 cm)
Package 1 Length	26.20 in (66.548 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Contractual warranty

Warranty	18 months