



Safety Data Sheet

SAKRETE Trowelable Blacktop Repair

©Roberts Concrete Products (a TCC Materials company)
Version 1.1

Roberts Concrete Products
2025 Centre Pointe Boulevard, Suite 300
Mendota Heights, MN 55120-1221

Emergency Telephone Number:
651-688-9116
Information Telephone Number
651-905-8137

Revision Date
December 2017

Section 1: Product Identification

Product Name:
SAKRETE Trowelable Blacktop Repair

Section 2: Hazard Identification



These products pose little harm as used. Dust from the dried product is harmful to breathe, because it will contain crystalline silica.

Danger: Crystalline silica may cause cancer when inhaled. Crystalline silica causes damage to lungs through prolonged or repeated exposure from inhaling dust.

This product has been evaluated according to GHS and 29CFR1910.1200, Appendix A. It is categorized as a Health Hazard Carcinogen Category 1A, because it contains crystalline silica (quartz).

Applicable hazard statements:

H350: May cause cancer from inhaling dust.

H372: Causes damage to respiratory system (silicosis) through prolonged or repeated exposure to inhaled dust.

Applicable Precautionary Statements:

P201: Obtain special instructions before use.

P202: Do not handle until all safety precautions have been read and understood.

P260: Do not breathe dusts

P270: Do not eat, drink or smoke when using this product.

P280: Wear eye protection

P308+313/314. If exposed or concerns, or if you feel unwell: Get medical advice

P501: Dispose of contents in accord with local regulations

HMIS® Rating: Health: 0* Fire: 0 Reactivity: 0

Hazard Rating: 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

HMIS® is a registered trademark of the National Paint and Coatings Association



Section 3: Hazardous Ingredients/Composition

Ingredient	Typical Percentage	CAS #
Limestone.....	25-50%	1317-65-3
Crystalline silica (quartz)	30-60%	14808-60-7
Aqueous acrylate emulsion	11-16%	*
Water.....	1-10%	7732-18-5
Plasticizer	0-4%	*

*Specific chemical identities withheld as trade secret. It is available upon request to health professionals, employees and their designated representatives in accord with 29CFR1910.1200(i).

Section 4: First Aid Measures

Inhalation:

Typically not an inhalation hazard until material dries out and dust is created. If any irritation develops, move to fresh air.

Eye contact:

Hold eyelids apart and flush eyes with plenty of water. At least fifteen minutes of flushing is recommended for any chemical contact. If any irritation persists, get medical attention.

Skin Contact:

Promptly wash off with pH-neutral soap and water. Get medical attention for any irritation or persistent dry skin.

Ingestion:

Check with the Poison Control Center or a doctor. Do not induce vomiting unless directed to do so by medical personnel.

Symptoms of overexposure:

Inhalation: No symptoms likely from normal use. If material dries out, breathing the dust may cause coughing, nose and throat irritation, wheezing. Repeated exposure to the dust can cause chronic coughing and impaired lung function. Long term exposure to respirable crystalline silica in the dust can cause silicosis (lung scarring) and lung cancer.

Eye contact: Eye irritation may develop from direct contact.

Skin Contact: May cause some drying of skin. Extensive contact could cause mild skin irritation.

Note to physician: Treat according to symptoms. No known specific antidote.



Section 5: Fire Fighting Measures

Fire extinguishing media: Appropriate for surrounding materials. Product is not flammable.

Special fire fighting procedures: None.

Unusual fire and explosion hazards: None.

Hazardous combustion products: None expected.

Section 6: Accidental Release Measures

Contain and clean up. May be slippery. Contain spills with inert material such as sand. Avoid creating dust. Do not allow product to enter sewers. Clean area with water.

Section 7: Handling and Storage

Do not breathe dust, which can be created when product dries.

Wash hands after use.

Do not eat, drink, or use tobacco products when handling any chemical products.

Storage: Keep from freezing. Keep container tightly closed.

Section 8: Exposure Controls/Personal Protection

Occupational Exposure Limits:

	OSHA PEL	ACGIH TLV	NIOSH REL
Crystalline silica (quartz)	50 µg/m ³ (8-hr TWA)	25 µg/m ³ (respirable)	50 µg/m ³ (respirable)
Limestone	15 mg/m ³ (total) 5 mg/m ³ (respirable)		
Acrylate emulsion	None established		
Plasticizer	None established		

Engineering Controls:

Avoid creating dust. Water can be used as a dust suppressant if material must be abraded or cut after it has dried.

Personal protective equipment

Respiratory protection: Not needed unless dust is created.

For protection against irritation from dust or up to ten times the recommended exposure limits, use a NIOSH-approved N-95 filtering facepiece or a half mask respirator



Safety Data Sheet

SAKRETE Trowelable Blacktop Repair

©Roberts Concrete Products (a TCC Materials company)
Version 1.1

equipped with N-95 filters. A more protective respirator (e.g., P100 filters or full face respirator) may be substituted.

Skin protection: None usually required. Any water-impermeable gloves such as PVC gloves are recommended for prolonged contact. Promptly wash off of skin and remove contaminated clothing.

Eye protection: Safety glasses with side shields. If used in dusty or windy conditions, goggles are recommended.

Section 9: Physical and Chemical Properties

Appearance:	Gray or black paste.
Odor:	May have slight acrylic odor (akin to latex paint)
Flash point:	Noncombustible.
Flammable limits:	N/A
Boiling Point:	~212°F (100°C) (of liquid component)
Freezing point:	~32°F (0°C) (of liquid component)
Solubility in water:	Can be diluted with or dispersed in water
Evaporation Rate:	Not available
Evaporation rate (butyl acetate = 1):	Not applicable
Percent solids:	80-90%

Section 10: Stability and Reactivity

Stability: stable.

Conditions to avoid: none known.

Incompatibility: strong oxidizers, strong acids, strong alkalis.

Hazardous polymerization: will not occur.

Hazardous decomposition products: Thermal decomposition may yield acrylic monomers.

Section 11: Toxicological Information

Not considered acutely toxic.

No listed ingredients are classified as irritants, per skin or eye irritation criteria of GHS

Not considered respiratory or skin sensitizer

No ingredients have been associated with reproductive toxicity

Respirable crystalline silica is categorized as a Health Hazard Carcinogen Category 1A (known to have carcinogenic potential for humans) and a Health Hazard Specific Target Organ Toxicity – Repeated Exposure Category 1. Respirable crystalline silica (quartz) can cause silicosis, a fibrosis (scarring) of the lungs. There is evidence that exposure to



Safety Data Sheet

SAKRETE Trowelable Blacktop Repair

©Roberts Concrete Products (a TCC Materials company)
Version 1.1

respirable silica or the disease silicosis is associated with an increased incidence of Scleroderma, tuberculosis and kidney disorders.

Crystalline silica is listed as carcinogenic according to IARC. ACGIH classified crystalline silica as a suspected human carcinogen

Section 12: Ecological Information

Product as a whole has not been tested but is expected to have low acute toxicity.

Ecotoxicity:

Not considered hazardous to the aquatic environment or to the ozone layer.

Persistence and degradability: Not likely to biodegrade.

Mobility in soil: No information available.

Bioaccumulation: Based on ingredients, not likely to bioaccumulate.

Section 13: Disposal Considerations

Do not sewer or dump on the ground.

As provided, not a RCRA-regulated waste.

Dispose of in accordance with federal, state, and local regulations.

Section 14: Transportation

Not a DOT-regulated hazardous material. Not classified as dangerous goods for DOT, IATA, IMDG, TDG

Section 15: Regulatory Information

Component Analysis

U.S. Federal Regulations

This product contains one or more of the following chemical components or ingredients that may require identification and/or reporting under SARA Section 302, SARA Sections 311/312/313, CERCLA, and/or TSCA. An examination of the components of this product should be conducted by a qualified environmental professional to determine if such identification or reporting is required by federal law.

Component: Silica (Crystalline)

U.S. State Regulations

This product contains one or more of the following chemical components or ingredients that are included on the hazardous materials list for one or more of the following states: California, Maine, Minnesota, New Jersey, Pennsylvania and Rhode Island. An examination of the components of this product should be conducted by a qualified



Safety Data Sheet

SAKRETE Trowelable Blacktop Repair

©Roberts Concrete Products (a TCC Materials company)
Version 1.1

environmental or safety and health professional to determine the specific requirements for those states.

Components: Limestone (calcium carbonate), Silica (Crystalline)

The state of California requires the following statement (Proposition 65) in regards to this material:



WARNING: This product can expose you to chemicals including crystalline silica which are known to the State of California to cause cancer, birth defects, or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Section 16: Other Information

Additional information on the products is available at. www.tccmaterials.com

Date of Preparation: December 6, 2017
Version: 1.1

Roberts Concrete Products®, a TCC Materials® company, is a licensed manufacturer of SAKRETE®

SAKRETE® is a registered trademark of SAKRETE of North America, LLC.

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.