



Flap wheel Fleece (A), coarse, Head \varnothing ×head width: 30X20mm



Order data

Order number	554950 30X20
GTIN	4045197679765
Item class	52E

Description

Version:

Flap strips of fleece around the shank of the tool. Shank \varnothing 6 mm.

Fleece impregnated with Aluminium Oxide (A). Creates a **consistent matt finish**.

Application:

For removal of dirt and oxide layers on metals as well as for matt finishing of Cr-Ni, other stainless steels, and also non-ferrous metals.

Technical description

maximum speed	14000 min ⁻¹
recommended speed	7500 min ⁻¹
Head width	20 mm
Shank \varnothing	6 mm
Head \varnothing	30 mm
Grinding medium code	A
Grit equivalent	100
Grit designation	coarse

Product name attribute	coarse
Type of product	Flap wheel

User data

	Suitability	V _c	ISO code
Alu Mg	suitable only under restricted conditions		
Steel < 900 N/mm ²	suitable		
Steel < 1400 N/mm ²	suitable		
Steel < 55 HRC	suitable		
Steel < 60 HRC	suitable only under restricted conditions		
Steel < 67 HRC	suitable only under restricted conditions		
INOX	suitable		
Ti	suitable only under restricted conditions		
GG(G)	suitable		
CuZn	suitable		
Plastic, GRP	suitable		
Wood	suitable		
Paint	suitable only under restricted conditions		
dry	suitable		