



Pull stud Haas-Mikron R 3 / 45° with bore and fit sealed, suitable for steep tapers: 40



Order data

Order number	308680 40
GTIN	4045197701008
Item class	32Z

Description

Description:

The toolholder is securely pulled into the spindle by the spindle's clamping gripper using the pull stud. Pull studs come in different versions. They are an important link between the machine and tool. Stringent requirements apply for the accuracy, strength and reliability of pull studs.

Application:

For tools with taper shanks see also **DIN 69871 / ISO 7388-1**.

Note:

Sealed – with O-ring.

Look in the eShop – you will find the right clamping wrench and width for every job.

When installing the pull stud, cheque the correct tightening torque.

Technical description

maximum tightening torque	50 Nm
Thread M	M16
Overall length L	57 mm
Collar Ø D	23 mm
L ₁	32 mm
Head Ø D ₁	15 mm
suitable for taper arbors with colour code	SK 40

suitable for steep tapers	40
Width across flats	19 mm
Pull stud standard	MAS 403
Type of product	Pull Stud

Accessories

Wrench for pull studsDIN ISO 7388-1 (formerly DIN 69872) suitable for ISO taper size 40	308825 40
Wrench for pull studsDIN ISO 7388-1 (formerly DIN 69872) suitable for ISO taper size 40	308820 40