

**Garant**
**Solid carbide HPC drill, plain shank DIN 6535 HA, DLC, Ø DC h7: 8,8mm**

**Order data**

|              |               |
|--------------|---------------|
| Order number | 122602 8,8    |
| GTIN         | 4045197752963 |
| Item class   | 11E           |

**Description**
**Version:**

**DLC coating sp<sup>2</sup>** of the latest generation with **low coefficient of friction** results in **outstanding chip clearance**. For **high-performance milling** of **aluminium materials**. **High alignment accuracy** and **roundness of the hole**, thanks to **6 guide chamfers**.

Size 1 - 1.5 with 4 guide chamfers.

**Note:**

Flute length  $L_c = L_2 + 1.5 \times D_c$ .

Form HB and HE supplied at the same price as HA.

Form **HB**: order with **No. 122603**.

Form **HE**: order with **No. 122602 + 129100HE**.

**Technical description**

|   |              |
|---|--------------|
| Number of cutting edges Z                         | 2            |
| Tolerance nominal Ø                               | h7           |
| Overall length L                                  | 103 mm       |
| Shank Ø D <sub>s</sub>                            | 10 mm        |
| Flute length L <sub>c</sub>                       | 61 mm        |
| Standard  | DIN 6537     |
| Nominal Ø D <sub>c</sub>                          | 8.8 mm       |
| Feed f in aluminium short-chipping                | 0.55 mm/rev. |
| Shank tolerance                                   | h6           |
| recommended maximum drilling depth L <sub>2</sub> | 47.8 mm      |

|                    |                   |
|--------------------|-------------------|
| Coating            | DLC               |
| Tool material      | solid carbide     |
| Version            | 6xD               |
| Type               | W                 |
| Point angle        | 135 degrees       |
| Shank              | DIN 6535 HA to h6 |
| Through-coolant    | yes, with 25 bar  |
| Machining strategy | HPC               |
| Semi-Standard      | yes               |
| Colour ring        | yellow            |
| Type of product    | Jobber drill      |

## User data

|                            | Suitability | V <sub>c</sub> | ISO code |
|----------------------------|-------------|----------------|----------|
| Alu plastics               | suitable    | 360 m/min      | N        |
| Aluminium (short chipping) | suitable    | 400 m/min      | N        |
| Alu > 10% Si               | suitable    | 350 m/min      | N        |
| PMMA acrylic               | suitable    | 150 m/min      | N        |
| PEEK                       | suitable    | 120 m/min      | N        |
| PVDF GF20                  | suitable    | 90 m/min       | N        |
| PA 66 GF30                 | suitable    | 80 m/min       | N        |
| PEEK GF30                  | suitable    | 70 m/min       | N        |
| PTFE CF25                  | suitable    | 80 m/min       | N        |
| Cu                         | suitable    | 160 m/min      | N        |
| CuZn                       | suitable    | 200 m/min      | N        |
| GRP                        | suitable    | 80 m/min       | N        |
| CRP                        | suitable    | 80 m/min       | N        |
| wet maximum                | suitable    |                |          |

wet minimum  
**Services**

suitable

Shank grinding Type HE

129100 HE