



3,000 g x 0.1 g

5,000 g x 0.1 g



- CALQUICK SINGLE BUTTON CALIBRATION
- READS IN: G, OZ, CT, LB, GN, %, COUNTING
- RECHARGEABLE BATTERY
- FILTERING LEVELS
- DUST COVER INCLUDED

| PART NUMBER | PD-3000 | PD-5000 |
|---------------------------|---|---|
| Capacity | 3000 g / 105 oz / 15,000 ct / 6.5 lb / 46,000 GN | 5000 g / 176 oz / 24,990 ct / 11 lb / 76,600 GN |
| Readability | 0.1 g / 0.001 oz / 0.5 ct / 0.001 lb / 0.1 GN | 0.1 g / 0.001 oz / 0.5 ct / 0.001 lb / 0.1 GN |
| Recommended Minimum Load | 1 g | 1 g |
| Repeatability (Std. Dev.) | ± 0.2 g | ± 0.2 g |
| Linearity | ± 0.2 g | ± 0.2 g |
| Stabilization Time | ≈ 2 seconds | |
| Weighing Units | g, oz, ct, lb, GN | |
| Functions | %, counting, below balance weighing | |
| Tare Range | To capacity by subtraction | |
| Power Source | 120V AC/DC adapter with rechargeable 6 Volt battery | |
| Construction | Steel base with ABS housing | |
| Display | LCD display 5/8 inch / 15 mm high with configurable backlight | |
| Pan Size | 6.5 x 6.5 inch / 165 x 165 mm stainless steel | |
| Overall Dimensions | 7 x 9.4 x 3.6 inch / 178 x 240 x 70 mm | |
| Operating Environment | 41 °F to 95 °F / 5 °C to 35 °C Temperature fluctuation ≤5 °C / hour Humidity 50% to 85% RH | |
| Net Weight | 4 lb / 1.8 kg | |
| Shipping Weight | 6 lb / 2.7 kg | |

| FEATURES | BENEFITS |
|------------------------------------|--|
| Adjustable filter levels | Allows you to speed up or slow down weighing to account for environmental conditions |
| Adjustable zero tracking | Allows for evaporation applications |
| Counting program | Allows for piece counting applications |
| Percentage program | Allows for formulation weighing |
| Configurable backlight | Saves battery power |
| CalQuick single button calibration | Calibration is simple, ensuring that the balance will be calibrated often during use |
| Large stainless steel pan | Allows for easy weighing of large objects |
| Bright, backlit LCD display | Easy to read in all lighting conditions including bright sunlight |
| Below Balance Weighing | Allows for weighing of bulky items and allows density calculations |
| Multiple weighing units | Allows flexibility of weighing |
| Battery operation | Portability - can be used in various locations without access to 120 Volt power |