

SYSTEMTHREE

Safety Data Sheets (SDS)

Updated: June 20, 2023

This file contains Safety Data Sheets for Gel Magic. This is a two-component system. It is imperative that you know whether you need information on the Resin or the Hardener.

Resin: Pages 2-9

Hardener: Pages 10-18

If this is a medical emergency, call 911 or your local poison control center. Seek medical attention.

For technical assistance, call System Three Technical Support at 253-333-8118 option 2.

These SDS are provided pursuant to 29 CFR 1910.1200(g).

1. Product Identification

Product name	GelMagic Resin, Part A
SDS Number	1230A00
Product type	Epoxy polymer mixture.
Manufacturer/Supplier information	Directed at, but not limited to, the adhesive of similar and dissimilar substrates.
Company name	SYSTEM THREE RESINS, INC.
Address	8517 Commerce Place Dr NE Lacey, WA 98516 United States
Telephone	1-253-333-8118
Website	www.systemthree.com
Email	support@systemthree.com
Emergency Contact	CHEMTEL (U.S. and CANADA) 1-800-704-9215 CHEMTEL (Outside the U.S.) – Call Collect accepted +1-360-256-7365

2. Hazard(s) Identification

Classification of substance or mixture/Signal Word	WARNING Skin Corrosion/Irritation - Category 2 Serious Eye Damage/Eye Irritation - Category 2 Skin Sensitization - Category 1 Specific Target Organ Toxicity (Single Exposure) [Respiratory tract irritation] – Category 3
<u>GHS Label Elements</u> Hazard Pictograms	
Hazard Statements/Classification of substance or mixture	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H335 May cause respiratory irritation.
Precautionary statements	
<u>Precautionary Statements</u> Prevention	P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P264 Wash hands thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P272 Contaminated work clothing should not be allowed out of the workplace. P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response	P304 + 340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P313 Call a POISON CENTER or doctor/physician if you feel unwell. P302+352+363 IF ON SKIN: Wash with soap and water. Take off contaminated clothing and wash before reuse. P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
Storage	P308 + P313 If exposed or concerned: Get medical attention.
Disposal	P401 Store at room temperature in a well-ventilated area. P501 Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazards not otherwise classified (HNOC)	None Available.

3. Composition/Information On Ingredients

Chemical Name	CAS Number	Content (%)
Diglycidyl Ether of Bisphenol A	25068-38-6	70 – 80 %
Benzyl Alcohol	100-51-6	5 – 10 %
Alkyl Glycidyl Ether	17557-23-2	5 – 10 %

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section. Occupational exposure limits, if available, are listed in Section 8.

4. First-Aid Measures

Skin contact	Remove contaminated clothing and shoes and wipe excess off skin. Flush skin with water. Follow by washing in soap and water. If irritation occurs, seek medical attention. Do not reuse clothing until cleaned. Contaminated leather articles (shoes) cannot be decontaminated and should be destroyed.
Eye contact	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Ingestion	Do not induce vomiting unless directed to do so by medical personnel. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately.
Inhalation	Remove victim to fresh air and provide oxygen if breathing is difficult. Give artificial respiration if not breathing. Get medical attention.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	No specific treatment.

5. Fire-Fighting Measures

Suitable extinguishing media	Alcohol-resistant foam, carbon dioxide (CO ₂), dry chemical, water fog.
Unsuitable extinguishing media	None known.

Specific hazards arising from the chemical	In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous decomposition products	Decomposition products may include the following materials: Carbon dioxide Carbon monoxide
Special protective actions for fire-fighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
Further information	Do not allow run-off from firefighting to enter drains or water courses. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

6. Accidental Release Measures

Personal precautions	Wear proper personal protective equipment (PPE). Avoid direct contact with material. Proper PPE includes: disposable gloves, eye protection and skin protection.
Emergency procedures	If materials is spilled, avoid contact with material. Persons not wearing appropriate protective equipment should leave the area of the spill until cleanup is complete.
Methods and materials for containment/cleanup	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.
Environmental precautions	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

7. Handling and Storage

Precautions for safe handling	Avoid contact with skin and eyes. Emergency showers and eye wash stations should be readily accessible. Adhere to work practice rules established by government regulations. Use personal protective equipment. When using, do not eat, drink or smoke.
Precautions/Recommendations for safe/proper storage	Store epoxy products in temperature stable environment, out of the reach of pets or children. Securely fasten container lids and tops, and prevent products from sitting and below freezing temperatures.

8. Exposure Controls/Personal Protection

Permissible exposure limit (OSHA)	None established.
Threshold limit value (ACGIH)	None established.
Appropriate engineering controls	Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other

	engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls	Use appropriate containment to avoid environmental contamination. Do not allow spill to enter sewers or waterways.
Individual protection measures/Personal protective equipment	
Eye/face protection	Splash-proof goggles or safety spectacles with side shields are recommended. Always wear eye protection when sanding cured epoxy resins to avoid dust in eyes.
Hand protection	Always wear impervious gloves: butyl rubber, nitrile rubber, Neoprene, PVC disposable gloves,
Skin protection	Wear clean, body-covering clothing to avoid skin contact.
Respiratory protection	Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Special instructions for protection and hygiene	Wear gloves at all times when handling product, avoid direct contact with skin. When finished using product, dispose of gloves properly and wash hands with warm, soapy water.

9. Physical and Chemical Properties

Chemical family	Epoxy Resin
Appearance	Blue paste
Physical State	Epoxy polymer mixture
Form	Paste
Color	Blue
Odor	Mild
Density (Specific Gravity)	9.78 lb/gal (1.17)
Viscosity	90,000 cps at 77 °F (25 °C)
pH	N/A
Melting point/freezing point	N/A
Initial boiling point and boiling range	N/A
Flash point	>300°F, Pensky-Martens Closed Cup
Evaporation rate	Slower than ether
Flammability (solid, gas)	Data not available
Upper/lower flammability limit (by volume)	N/A
Upper flammability limit (by volume)	N/A
Lower flammability limit (by volume)	N/A
Material VOC	None
Vapor density	Heavier than air
Relative density	Not determined
Solubility in water	Negligible
Partition coefficient: n-octanol/water	3

Auto-ignition temperature	300°C (572.00°F)
Decomposition temperature	N/A

10. Stability and Reactivity

Reactivity	No specific test data related to reactivity available for this product.
Chemical Stability	Stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization will not occur.
Conditions to avoid	Epoxy resins and epoxy resin hardeners react with each other producing heat. They should not be mixed with each other under uncontrolled conditions or in large mass as the ensuing exotherm may result in heat and smoke, resulting in hazardous decomposition products.
Incompatible materials	Strong oxidizing and reducing agents. Lewis and mineral acids.
Hazardous decomposition products	Oxides of carbon, aldehydes, and acids.

11. Toxicological Information

Acute Toxicity No comprehensive data is available on the product itself.

Component	Result	Species	Dose	Exposure
Diglycidyl Ether of Bisphenol A	LD50 Oral	Rat	11,400 mg/kg	-
	LD50 Dermal	Rat	2,000 mg/kg	-
Alkyl Glycidyl Ether	LD50 Oral	Rat	4,500 mg/kg	-
	LD50 Dermal	Rabbit	>2,000 mg/kg	-
Benzyl Alcohol	LD50 Oral	Rat	1620 mg/kg	-
	LC50 Inhalation	Rat	>4178 mg/m3	4 h, aerosol

Irritation/Corrosion (components) No information on product itself.

Component	Result	Species	Test	Exposure
Diglycidyl Ether of Bisphenol A	Moderate to severe irritation	Rabbit	Skin	4 h
	Mild irritation	Rabbit	Eye	24 h
Benzyl Alcohol	Irritant	Rabbit	Eye	-

Sensitization No information on product itself.

Mutagenicity No information on product itself.

Carcinogenicity No information on product itself.

Reproductive Toxicity No information on product itself.

Teratogenicity No information on product itself.

Specific target organ toxicity (single exposure) No information on product itself.

Component	Category	Route of exposure	Target organs
Diglycidyl Ether of Bisphenol A	Category 3		Respiratory tract irritation
Alkyl Glycidyl Ether	Category 3		Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

No information on product itself.

Aspiration hazard

No information on product itself.

Potential acute health effects

Eye Contact

Causes serious eye irritation.

Inhalation

May cause respiratory irritation.

Skin Contact

Causes skin irritation. May cause an allergic skin reaction.

Ingestion

Irritating to mouth, throat and stomach.

Symptoms related to the physical, chemical and toxicological characteristics

Eye Contact

Adverse symptoms may include the following:

Pain

Watering

Redness

Inhalation

Adverse symptoms may include the following:

Respiratory tract irritation

Coughing

Skin Contact

Adverse symptoms may include the following:

Irritation

Redness

Ingestion

No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Not available.

Potential chronic health effects

General

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity

No known significant effects or critical hazards.

Mutagenicity

No known significant effects or critical hazards.

Teratogenicity

No known significant effects or critical hazards.

Developmental effects

No known significant effects or critical hazards.

Fertility effects

No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates (ATE_{mix})

No specific data.

12. Ecological Information

Ecotoxicity

No information on product itself.

Component	Result	Species	Exposure
Diglycidyl Ether of Bisphenol A	Acute LC50 1.3 mg/l	Fish	96 h
	Acute LC50 2.1 mg/l	Daphnia	48 h
Benzyl Alcohol	Acute LC50 460 mg/l	Fish	96 h
	Acute EC50 230 mg/l	Invertebrates	48 h
	Chronic NOEC 310 mg/l	Algae	72 h

Persistence and degradability No information on product itself.

Bioaccumulative Potential No information on product itself.

Component	LogPow	BCF	Potential
Diglycidyl Ether of Bisphenol A	2.64 – 3.78	3 – 31 31.00	Low
Benzyl Alcohol	1.05	1.37 (calculated)	-

Mobility in Soil

Soil/water partition coefficient (KOC) No information on product itself.

Other adverse effects No known significant effects or critical hazards.

13. Disposal Considerations

Waste from residues/ unused products The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Product should not be allowed to enter drains, water courses or the soil; dispose of this material and its containers in a safe way. Contact supplier if guidance is required.

Contaminated packaging Dispose of container and unused contents in accordance with federal, state and local requirements.

14. Transport Information

The data provided in this section is for information only and may not be specific to your package size or mode of transport. You will need to apply the appropriate regulations to properly classify your shipment for transportation.

International Transport Regulations

Regulatory information	UN/NA number	Proper Shipping Name	Classes/*PG	Additional Information
DOT		Non-regulated		
TDG		Non-regulated		
IMO/IMDG	UN3082	Environmentally hazardous substance, liquid, n.o.s. (Bisphenol-A Epichlorohydrin Resin)	Class 9 III	
IATA	UN3082	Environmentally hazardous substance, liquid, n.o.s. (Bisphenol-A Epichlorohydrin Resin)	Class 9 III	

*PG: Packing group

Special precautions for user: Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

15. Regulatory Information

UNITED STATES

U.S. Federal Regulations

United States – TSCA 12(b) – Chemical export notification: None Required.
United States – TSCA 5(a)2 – Final significant new use rules: Not Listed.
United States – TSCA 12(b) – Proposed significant new use rules: None Required.

Clean Air Act – Ozone Depleting Substances (ODS)	United States – TSCA 5(e) – Substance consent order: Not listed.
California Prop. 65	This product does not contain nor is it manufactured with ozone depleting substances.
EPA SARA 302/304/311/312 Substances	WARNING: This product can expose you to chemicals including Oxirane, 2-(chloromethyl)- that is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov .
EPA SARA 313	Acute Health Hazard
United States inventory (TSCA 8b)	None Required
CANADA	All components are listed or exempted.
WHMIS (Canada)	Class D-2B: Material causing other toxic effects (Toxic).
Canadian NPRI	None Required
CEPA Toxic substances	None Required
INTERNATIONAL REGULATIONS	
International Lists	<p>Australia inventory (AICS): All components are listed or exempted.</p> <p>Canada inventory: All components are listed or exempted.</p> <p>Korea inventory: All components are listed or exempted.</p> <p>Japan inventory: All components are listed or exempted.</p> <p>China inventory (IECSC): All components are listed or exempted.</p> <p>New Zealand inventory (NZIoC): All components are listed or exempted.</p> <p>Philippines inventory (PICCS): All components are listed or exempted.</p> <p>Taiwan inventory (CSNN): All components are listed or exempted.</p>

16. Other Information, Including Date of Preparation or Last Revision

HMIS Rating

Health	2
Flammability	1
Physical Hazard	0

Date of Preparation	March 1, 2023
Date of Last Revision	January 16, 2020
Revision #	7.0
More Information	1-253-333-8118
Prepared by	System Three Resins Inc.

The information contained herein is based on the data available to us and is believed to be correct. However, System Three Resins, Inc. makes no warranty, expressed or implied, regarding the accuracy of these data or the results to be obtained from the use thereof. System Three assumes no responsibility for injury from the use of the product described herein.

1. Product Identification

Product name	GelMagic Hardener, Part B	
SDS Number	1230B00	
Product type	Amine/Butadiene mixture	
Manufacturer/Supplier information	Directed at, but not limited to, the adhesive bonding of similar and dissimilar substrates.	
Company name	SYSTEM THREE RESINS, INC.	
Address	8517 Commerce Place Dr NE Lacey, WA 98516 United States	
Telephone	1-253-333-8118	
Website	www.systemthree.com	
Email	support@systemthree.com	
Emergency Contact	CHEMTEL (U.S. and CANADA)	1-800-704-9215
	CHEMTEL (Outside the U.S.) – Call Collect accepted	+1-360-256-7365

2. Hazard(s) Identification

Classification of substance or mixture/Signal Word	DANGER Acute Toxicity: oral – Category 4 Acute Toxicity: dermal – Category 4 SKIN CORROSION/IRRITATION – Category 2 SERIOUS EYE DAMAGE/EYE IRRITATION – Category 1 SKIN SENSITIZATION – Category 1 ACUTE AQUATIC HAZARD – Category 2 LONG-TERM AQUATIC HAZARD – Category 2
---	---

GHS Label Elements
Hazard Pictograms



Hazard Statements/Classification of substance or mixture	H302 Harmful if swallowed. H312 Harmful in contact with skin. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H401 Toxic to aquatic life. H411 Toxic to aquatic life with long lasting effects.
---	--

Precautionary statements

Precautionary Statements
Prevention

P261	Avoid breathing vapors.
P264	Wash hands thoroughly after handling.
P270	Do not eat, drink or smoke when using this product
P272	Contaminated work clothing should not be allowed out of the workplace.

Response	<p>P273 Avoid release to the environment.</p> <p>P280 Wear protective gloves/protective clothing/eye protection/face protection.</p> <p>P281 Use personal protective equipment as required.</p> <p>P285 In case of inadequate ventilation wear respiratory protection.</p> <p>P313 Call a POISON CENTER or doctor/physician if you feel unwell.</p> <p>P308 + P313 If exposed or concerned: Get medical attention.</p> <p>P301 + P312 If Swallowed: Call a poison center or doctor/physician if you feel unwell.</p> <p>P302+352+363 IF ON SKIN: Wash with soap and water. Take off contaminated clothing and wash before reuse.</p> <p>P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.</p> <p>P330 Rinse mouth</p> <p>P333+P313 If skin irritation or rash occurs: Get medical advice/attention.</p> <p>P362+P364 Take off contaminated clothing and wash it before reuse.</p> <p>P391 Collect spillage.</p>
Storage	P401 Store at room temperature in a well-ventilated area.
Disposal	P501 Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazards not otherwise classified (HNOC)	None Available.

3. Composition/Information On Ingredients

Chemical Name	CAS Number	Content (%)
Modified Polyamines	Trade Secret	60-70%
ATBN Polymer	68683-29-4	20-30%
Nonyl Phenol	84852-15-3	0-5%

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section. Occupational exposure limits, if available, are listed in Section 8.

4. First-Aid Measures

Skin contact	Remove contaminated clothing and shoes and wipe excess off skin. Flush skin with water. Follow by washing in soap and water. If irritation occurs, seek medical attention. Do not reuse clothing until cleaned. Contaminated leather articles (shoes) cannot be decontaminated and should be destroyed.
Eye contact	Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.
Ingestion	Do not induce vomiting unless directed to do so by medical personnel. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately.
Inhalation	Remove victim to fresh air and provide oxygen if breathing is difficult. Give artificial respiration if not breathing. Get medical attention.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	No specific treatment.

5. Fire-Fighting Measures

Suitable extinguishing media	Alcohol-resistant foam, carbon dioxide (CO ₂), dry chemical, water fog.
Unsuitable extinguishing media	None known.
Specific hazards arising from the chemical	In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous decomposition products	Decomposition products may include the following materials: Carbon dioxide, carbon monoxide, nitrogen oxides
Special protective actions for fire-fighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
Further information	Do not allow run-off from firefighting to enter drains or water courses. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

6. Accidental Release Measures

Personal precautions	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear proper protective clothing, gloves and eye/face protection. Use self-contained breathing apparatus and chemically protective clothing.
Emergency procedures	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.
Methods and materials for containment/cleanup	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.
Environmental precautions	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

7. Handling and Storage

Precautions for safe handling	Avoid contact with skin and eyes. Emergency showers and eye wash stations should be readily accessible. Adhere to work practice rules established by government regulations. Use personal protective equipment. When using, do not eat, drink or smoke.
--------------------------------------	---

Precautions/Recommendations for safe/proper storage

Store epoxy products in temperature stable environment, out of the reach of pets or children. Securely fasten container lids and tops, and prevent products from sitting and below freezing temperatures.

8. Exposure Controls/Personal Protection

Permissible exposure limit (OSHA)	None established.
Threshold limit value (ACGIH)	None established.
Appropriate engineering controls	Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls	Use appropriate containment to avoid environmental contamination. Do not allow spill to enter sewers or waterways.
Individual protection measures/Personal protective equipment	
Eye/face protection	Splash-proof goggles or safety spectacles with side shields are recommended. Always wear eye protection when sanding cured epoxy resins to avoid dust in eyes.
Hand protection	Always wear impervious gloves: butyl rubber, nitrile rubber, Neoprene, PVC disposable gloves,
Skin protection	Wear clean, body-covering clothing to avoid skin contact.
Respiratory protection	Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Special instructions for protection and hygiene	Wear gloves at all times when handling product, avoid direct contact with skin. When finished using product, dispose of gloves properly and wash hands with warm, soapy water.

9. Physical and Chemical Properties

Chemical family	Polyamine
Appearance	Amber colored paste
Physical State	Amine/Butadiene mixture
Form	Paste
Color	Amber
Odor	Mild
Density (Specific Gravity)	8.40 lb/gal (1.01)
Viscosity	60,000 cps at 77 °F (25 °C)
pH	N/A
Melting point/freezing point	N/A
Initial boiling point and boiling range	N/A
Flash point	>250°F, Pensky-Martens Closed Cup
Evaporation rate	Slower than ether
Flammability (solid, gas)	Data not available

Upper/lower flammability limit (by volume)	N/A
Material VOC	None
Vapor density	Heavier than air
Relative density	Not determined
Solubility in water	Negligible
Partition coefficient: n-octanol/water	N/A

10. Stability and Reactivity

Reactivity	No specific test data related to reactivity available for this product.
Chemical Stability	Stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization will not occur.
Conditions to avoid	Epoxy resins and epoxy resin hardeners react with each other producing heat. They should not be mixed with each other under uncontrolled conditions or in large mass as the ensuing exotherm may result in heat and smoke, resulting in hazardous decomposition products.
Incompatible materials	Strong oxidizing and reducing agents. Lewis and mineral acids.
Hazardous decomposition products	Oxides of carbon and nitrogen.

11. Toxicological Information

<u>Acute Toxicity</u>	No comprehensive data is available on the product itself.
<u>Irritation/Corrosion (components)</u>	Classifies as non-corrosive to skin per negative Corrositex Dermal Testing. Classifies as Serious Eye Damage Category 1 per GHS calculations of additivity.

Component	Test	Species	Result
Modified Polyamines	OECD 404 Acute Dermal Irritation/Corrosion	Rabbit	Skin – Corrosive
	OECD 405 Acute Eye Irritation/Corrosion	Rabbit	Eyes - Corrosive

Sensitization No information on product itself.

Component	Species	Result
ATBN Polymer	Guinea Pig	Strong Sensitizer

Mutagenicity No information on product itself.

Carcinogenicity No information on product itself.

Reproductive Toxicity No information on product itself.

Teratogenicity No information on product itself.

Specific target organ toxicity (single exposure) No information on product itself.

Specific target organ toxicity (repeated exposure) No information on product itself.

Aspiration hazard No information on product itself.

Potential acute health effects

Eye Contact	Causes serious eye damage.
Inhalation	May give off vapor that is irritating to the respiratory system.

Skin Contact Causes skin irritation. May cause an allergic skin reaction.

Ingestion Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Eye Contact Adverse symptoms may include the following:
Pain
Watering
Redness

Inhalation No data available.

Skin Contact Adverse symptoms may include the following:
Pain or irritation

Ingestion No data available.

Delayed and immediate effects and also chronic effects from short and long term exposure No data available.

Potential chronic health effects

General Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity No known significant effects or critical hazards.

Mutagenicity No known significant effects or critical hazards.

Teratogenicity No known significant effects or critical hazards.

Developmental effects No known significant effects or critical hazards.

Fertility effects No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates (ATE_{mix})

Route	ATE value
Oral	3207.3 mg/kg
Dermal	2266.3 mg/kg
Inhalation (vapors)	N/A

12. Ecological Information

Ecotoxicity

No information on product itself.

Component	Test	Endpoint	Exposure	Species	Result
ATBN Polymer	OECD 202 Invertebrates	Acute EC50	48 h	Invertebrates	>1000 mg/l
	OECD 201 Algae, Growth Inhibition Test	Acute EC50	72 h	Algae	>1000 mg/l
Nonyl Phenol		Acute EC50	96 hrs	Fish	0.209 mg/l
		Acute EC50	48 hrs	Daphnia	0.085 mg/l

Persistence and degradability

No information on product itself.

Component	Test	Period	Result
Nonyl phenol	OECD 301B Ready Biodegradability – CO2 Evolution Test	35 days	48.2%

Bioaccumulative Potential

No information on product itself.

Component	LogPow	BCF	Potential
Nonyl Phenol	5.4	740	High

Mobility in Soil

Soil/water partition coefficient (KOC)	No information on product itself.
Other adverse effects	No known significant effects or critical hazards.

13. Disposal Considerations

Waste from residues/ unused products	The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Product should not be allowed to enter drains, water courses or the soil; dispose of this material and its containers in a safe way. Contact supplier if guidance is required.
Contaminated packaging	Dispose of container and unused contents in accordance with federal, state and local requirements.

14. Transport Information

The data provided in this section is for information only and may not be specific to your package size or mode of transport. You will need to apply the appropriate regulations to properly classify your shipment for transportation.

International Transport Regulations

Regulatory information	UN/NA number	Proper Shipping Name	Classes/*PG	Additional Information
DOT		Non-regulated		
TDG		Non-regulated		
IMO/IMDG	UN3082	Environmentally hazardous substance, liquid, n.o.s. (Nonyl Phenol)	Class 9 III	Marine pollutant
IATA	UN3082	Environmentally hazardous substance, liquid, n.o.s. (Nonyl Phenol)	Class 9 III	

*PG: Packing group

Special precautions for user:	Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
--------------------------------------	--

15. Regulatory Information

UNITED STATES

U.S. Federal Regulations

United States – TSCA 12(b) – Chemical export notification:

Phenol, 4-Nonyl-, branched 84852-15-3

Phenol, 2-Nonyl-, branched 91672-41-2

United States – TSCA 5(a) – Significant New Use Rule List of Chemicals:

This product is subject under TSCA 5(a) to Significant New Use Restrictions (SNUR).

Phenol,4-nonyl-, branched 84852-15-3

United States – TSCA 5(e) – Substance consent order: Not listed.

Clean Air Act – Ozone Depleting Substances (ODS)

This product does not contain nor is it manufactured with ozone depleting substances.

Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs)

Product Name	Concentration %
Phenol	0 – 1%
Diethanolamine	

Pennsylvania – RTK

Phenol.

California Prop. 65

WARNING: This product can expose you to chemicals including Diethanolamine that is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

EPA SARA 302/304/311/312 Substances

Acute Health Hazard, Chronic Health Hazard

EPA SARA 313

Form R – Reporting requirements

Product Name	Concentration %
Phenol	0 – 1%
Diethanolamine	0 – 1%

CERCLA Hazardous Substances

Component	%	Section 304 CERCLA Hazardous Substance	CERCLA Reportable Quantity (Lbs)	Product Reportable Quantity (Lbs)
Phenol	1	Listed		
Diethanolamine	1		100	

United States inventory (TSCA 8b)

All components are listed or exempted.

CANADA

WHMIS (Canada)

Class D-2B: Material causing other toxic effects (Toxic).

Class E: Corrosive material.

Canadian NPRI

None Required

CEPA Toxic substances

None Required

INTERNATIONAL REGULATIONS

International Lists

Australia inventory (AICS): All components are listed or exempted.

Canada inventory: All components are listed or exempted.

Korea inventory: All components are listed or exempted.

Japan inventory: All components are listed or exempted.

China inventory (IECSC): All components are listed or exempted.

New Zealand inventory (NZIoC): All components are listed or exempted.

Philippines inventory (PICCS): All components are listed or exempted.

Taiwan inventory (CSNN): All components are listed or exempted.

16. Other Information, Including Date of Preparation or Last Revision

HMIS Rating

Health 3
Flammability 1
Physical Hazard 0

Date of Preparation

March 1, 2023

Date of Last Revision

May 27, 2021

Revision #

8.0

More Information

1-253-333-8118

Prepared by

System Three Resins Inc.

The information contained herein is based on the data available to us and is believed to be correct. However, System Three Resins, Inc. makes no warranty, expressed or implied, regarding the accuracy of these data or the results to be obtained from the use thereof. System Three assumes no responsibility for injury from the use of the product described herein.