



PIDG Ring Tongue Terminals for Thin Wall Cables
High Temperature Range
Related Product Data


Application Tooling — page 9023



Style A



Style B



Style C

Wire Size	Stud Size				Dimensions (Max.)			Color Code	Wire Insulation Outside Dia.	Style	Part Number								
	+/- .03 [+/- 0.8]	Metric	BA #	UN #	W	L	C												
22-24	.119 3.02	M2.5	6	4	.218 5.54	.657 16.68	.166 4.22	Brown	.035-.075 0.90-1.90	A	152642								
					.281 7.14	.787 19.98	.25 6.35				152644								
					.218 5.54	.751 19.08	.25 6.35				152648								
	.145 3.68	M3	4	6	.218 5.54	.657 16.68	.166 4.22				152643								
					.281 7.14	.787 19.98	.25 6.35				152645								
					.171 4.34	M4	3				8	.281 7.14	.787 19.98	.25 6.35	152646				
	1.97 5.00	—	2	10	.281 7.14	.787 20.0	.244 6.20				152647								
	20	.093 2.36	M2	8	2	.218 5.54	.680 17.27				.166 4.22	Grey	.043-.079 1.10-2.00	A	152660				
						.122 3.10	M2.5				6				4	.281 7.14	.787 19.98	.26 6.60	152654
																.218 5.54	.680 17.27	.166 4.22	152659
.148 3.76		M3	4	6	.281 7.14	.787 19.98	.25 6.35	152655											
					.218 5.54	.680 17.27	.166 4.22	152658											
					.171 4.34	M4	3	8	.281 7.14	.787 19.98	.26 6.60				152656				
1.99 5.06		—	2	10					.281 7.14	.787 19.98	.26 6.60				152657				
18-16		.268 6.81	M6	0	1/4	.469 11.91	1.08 27.58	.447 11.35	Orange	.055-.106 1.40-2.70	A				152661				
						.331 8.41	M8	5/16							5/16	.469 11.91	1.08 27.58	.447 11.35	152662
		.393 9.98	M9.5	3/8	3/8	.469 11.91	1.08 27.58	.447 11.35							152663				
	.122 3.10	M2.5	6	4	.218 5.54	.746 18.94	.26 6.60	B				153493							
					.122 3.10	M3	6						4	.218 5.54	.681 17.30	.166 4.22	153103		
	.145 3.68	M3	4	6	.281 7.10	.807 20.50	.26 6.60	153104											
					.171 4.34	M4	3	8				.312 7.92	.854 21.70	.291 7.39	153105				
	.197 5.00	—	2	10	.312 7.92	.854 21.70	.291 7.39	153106											
					.265 6.73	M6	0	1/4				.469 11.91	1.09 27.70	.447 11.35	153107				
	.328 8.33	M8	5/16	5/16	.469 11.91	1.09 27.70	.447 11.35	153108											
.390 9.90					M9.5	3/8	3/8	.531 13.48	1.21 30.79	.531 13.48	153109								
								.125 3.17	—	—	—	.223 5.66	.902 22.90	.359 9.11	C	153475			