

1717268-1 ✓ ACTIVE




Positive Lock | Positive Lock 250

TE Internal #: 1717268-1

Insulation Boots & Sleeves, Insulation Sleeve, Flag, PVC, Blue, Bag,
-40 – 221 °F [-40 – 105 °C], Positive Lock 250

[View on TE.com >](#)

Terminals & Splices > Terminal Housings, Insulation Sleeves & Blocks > Insulation Boots & Sleeves



Insulation Boot & Sleeve Product Type: **Insulation Sleeve**

Terminal Orientation: **Flag**

Primary Product Material: **PVC**

Primary Product Color: **Blue**

Packaging Method: **Bag**

Features

Product Type Features

Insulation Boot & Sleeve Applies To	Wire/Cable
Insulated	Yes
Insulation Boot & Sleeve Product Type	Insulation Sleeve

Configuration Features

Number of Insulation Boot & Sleeve Positions	1
--	---

Body Features

Primary Product Material	PVC
Primary Product Color	Blue

Contact Features

Terminal Orientation	Flag
----------------------	------

Housing Features

Housing Material	Soft PVC
------------------	----------

Dimensions

Length	17.2 mm[.677 in]
--------	------------------

Usage Conditions

Operating Temperature Range	-40 – 105 °C[-40 – 221 °F]
-----------------------------	----------------------------

Industry Standards

UL Flammability Rating	UL 94V-0
------------------------	----------

Packaging Features

Packaging Quantity	1000
Packaging Method	Bag

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JAN 2021 (211) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability





Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



Also in the Series | Positive Lock 250



Documents

Product Drawings

PL EX 250 INSULATED FLAG REC PVC V-0

English

CAD Files

3D PDF

3D

Customer View Model

[ENG_CVM_CVM_1717268-1_O.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_CVM_1717268-1_O.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_1717268-1_O.3d_stp.zip](#)

English

1717268-1

Insulation Boots & Sleeves, Insulation Sleeve, Flag, PVC, Blue, Bag, -40 – 221 °F [-40 – 105 °C], Positive Lock 250



By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.