



Heat Shrink Tubing > Dual Wall DSPL Stick Heat Shrink Tubing



Primary Product Color: **Black**

Wall Type: **Dual**

Expanded Inside Diameter (Min): **3.18 mm [.125 in]**

Recovered Inside Diameter (Max): **1.02 mm [.04 in]**

Shrink Ratio: **3:1**

[All Dual Wall DSPL Stick Heat Shrink Tubing \(19\)](#)

Features

Product Type Features

| | |
|----------------|---------|
| Product Family | DWP-125 |
| Wall Type | Dual |

Electrical Characteristics

| | |
|---------------|-------|
| Voltage (Max) | .6 kV |
|---------------|-------|

Body Features

| | |
|--------------------------|---|
| Fluid Type | Hydraulic Fluid, Lubricating Oil, Water |
| Primary Product Color | Black |
| Shrink Ratio | 3:1 |
| Primary Product Material | Irradiated Modified Polyolefin |
| Flexibility | Flexible |

Dimensions

| | |
|--------------------------------------|----------------------------------|
| Recovered Wall Thickness (Tolerance) | 1.02 mm[.04 in] |
| Cut Length | 1220 – 1245.4 mm[48.031 – 49 in] |
| Expanded Inside Diameter (Min) | 3.18 mm[.125 in] |
| Recovered Inside Diameter (Max) | 1.02 mm[.04 in] |

Usage Conditions

| | |
|--|--|
| | |
|--|--|



| | |
|---------------------------------|-------------------|
| Shrink Temperature (Min) | 80 °C |
| Fluid Resistance | Splash Protection |
| Heat Shrink Tubing Flammability | Flame-Retardant |
| Operating Temperature Range | -40 – 110 °C |
| Heat Shrink Tubing Resistance | Fluids |
| Recovery Temperature | 125 °C |

Product Availability

| | |
|-------------------|--------|
| Applicable Region | Global |
|-------------------|--------|

Packaging Features

| | |
|------------------|-------|
| Packaging Method | Stick |
|------------------|-------|

Other

| | |
|-----------------------------------|----|
| Meets Low Outgassing Requirements | No |
| Product Source | US |

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

| | |
|---|---|
| EU RoHS Directive 2011/65/EU | Compliant |
| EU ELV Directive 2000/53/EC | Compliant |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold |
| EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC |
| Halogen Content | Not Low Halogen - contains Br or Cl > 900 ppm. |
| Solder Process Capability | Not applicable for solder process capability |

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>



Compatible Parts



Also in the Series | RAYCHEM DWP-125



Documents

Product Drawings

[DWP-125-1/8-0-STK](#)

English

Datasheets & Catalog Pages

[DWP-125 Pages from 9-1773447-9](#)

English

[Flexible, Flame-Retardant, Adhesive-lined, Polyolefin Heat-Shrinkable Tubing](#)

English

[Measuring_Single_Wall_Tubing](#)

English

[Selecting_Correct_Tubing](#)

English

Product Specifications

[Quality Specification](#)

English