

5745076-6 ✓ ACTIVE




AMPLIMITE

TE Internal #: 5745076-6

PCB D-Sub Connectors, Receptacle, Board-to-Board, 9 Position,
2.74 mm [.108 in] Centerline, 2 Row, Size 1, Round, Standard Profile,
Vertical

[View on TE.com >](#)

Connectors > D-Shaped Connectors > D-Sub Connectors > PCB D-Sub Connectors > D-Sub Receptacle Assembly: Vertical, Shell Size 1, 2.74mm



Connector & Housing Type: **Receptacle**

Connector System: **Board-to-Board**

Number of Positions: **9**

Centerline (Pitch): **2.74 mm [.108 in]**

Number of Rows: **2**

[All D-Sub Receptacle Assembly: Vertical, Shell Size 1, 2.74mm \(59\)](#)

Features

Product Type Features

| | |
|-----------------------------------|-----------------------|
| Grounding Straps | Without |
| Grounding Indents | Without |
| Grounded | No |
| Shell Type | All Plastic |
| Connector & Housing Type | Receptacle |
| Connector System | Board-to-Board |
| D-Sub Shell Size | 1 |
| Sealable | No |
| Connector & Contact Terminates To | Printed Circuit Board |
| Shielded | No |
| Product Type | Connector |

Configuration Features

| | |
|---------------------|---|
| Number of Positions | 9 |
|---------------------|---|



| | |
|-----------------------|----------|
| Number of Rows | 2 |
| PCB Mount Orientation | Vertical |
| Preloaded | Yes |

Body Features

| | |
|-----------------------------------|--------------------------|
| Plastic | Yes |
| Female Screwlock Material | Brass |
| Female Screwlock Plating Material | Nickel over Copper Flash |
| Connector Profile | Standard |
| Post Size | .66 mm[.026 in] |

Contact Features

| | |
|---|-----------------|
| Contact Mating Area Plating Material | Gold |
| Contact Underplating Material | Nickel |
| PCB Contact Termination Area Plating Material | Tin |
| Contact Base Material | Phosphor Bronze |
| Contact Shape & Form | Round |
| Contact Current Rating (Max) | 6 A |
| | 30 μ m |

Termination Features

| | |
|---|-----------------------|
| Grounding Clips | Without |
| Termination Method to Printed Circuit Board | Through Hole - Solder |
| Termination Post Length | 4.32 mm[.17 in] |

Mechanical Attachment

| | |
|--------------------------|--------------------------|
| Panel Mount Feature | Without |
| PCB Mount Retention | With |
| PCB Mount Retention Type | Mounting Hole |
| Mating Retention | With |
| Mating Retention Type | Female Screwlocks, Fixed |
| Connector Mounting Type | Board Mount |
| Mounting Hole Diameter | 3.05 mm[.12 in] |

Housing Features

| | |
|--------------------|------------------|
| Centerline (Pitch) | 2.74 mm[.108 in] |
| Housing Material | Polyester |



| | |
|---------------|-------|
| Housing Color | Black |
|---------------|-------|

Dimensions

| | |
|-----------------------------|---------------------------------|
| Row-to-Row Spacing | 2.84 mm [.112 in] |
| PCB Thickness (Recommended) | 2.36 – 3.18 mm [.093 – .125 in] |

Usage Conditions

| | |
|-----------------------------|-----------------------------|
| Operating Temperature Range | -55 – 105 °C [-67 – 221 °F] |
|-----------------------------|-----------------------------|

Operation/Application

| | |
|---------------------|--------|
| Circuit Application | Signal |
|---------------------|--------|

Industry Standards

| | |
|------------------------|----------|
| UL Flammability Rating | UL 94V-0 |
|------------------------|----------|

Packaging Features

| | |
|--------------------|------|
| Packaging Method | Tube |
| Packaging Quantity | 17 |

Other

| | |
|---------|--|
| Comment | All receptacles are preloaded with size 20 DF posted socket contacts |
|---------|--|

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

| | |
|---|--|
| EU RoHS Directive 2011/65/EU | Compliant with Exemptions |
| EU ELV Directive 2000/53/EC | Compliant with Exemptions |
| China RoHS 2 Directive MIIT Order No 32, 2016 | Restricted Materials Above Threshold |
| EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUNE 2022 (224) SVHC > Threshold: Pb (2.5% in Component Part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location. |
| Halogen Content | Not Low Halogen - contains Br or Cl > 900 ppm. |
| Solder Process Capability | Wave solder capable to 265°C |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



Documents

Product Drawings

[HD-20 RCPT 9P VERT FFSCRLK](#)

English

CAD Files

Customer View Model

[ENG_CVM_CVM_5745076-6_A.2d_dxf.zip](#)

English

3D PDF

3D

Customer View Model

[ENG_CVM_CVM_5745076-6_A.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_5745076-6_A.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[AMPLIMITE Subminiature D Connectors - Straight Posted Connectors](#)

English

Product Specifications

[Product Specification](#)



English

[Agency Approvals](#)

[UL Report](#)

English