

6450123-3 ✓ ACTIVE

MULTI-BEAM


TE Internal #: 6450123-3

Rectangular Power Connectors, Header, Plug, Board-to-Board, 3 Position, 7.62 mm [.3 in] Centerline, Printed Circuit Board, UL 94V-0

[View on TE.com >](#)



Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors



Rectangular Power Connector Type: **Header**

Connector & Housing Type: **Plug**

Connector System: **Board-to-Board**

Number of Positions: **3**

Centerline (Pitch): **7.62 mm [.3 in]**

Features

Product Type Features

| | |
|-----------------------------------|-----------------------|
| Header Type | Fully Shrouded |
| Rectangular Power Connector Type | Header |
| Connector & Housing Type | Plug |
| Connector System | Board-to-Board |
| Sealable | No |
| Connector & Contact Terminates To | Printed Circuit Board |

Configuration Features

| | |
|---------------------------|-------------|
| Number of Positions | 3 |
| PCB Mount Orientation | Right Angle |
| Number of Power Positions | 3 |
| Number of Rows | 1 |

Electrical Characteristics

| | |
|-------------------|---------|
| Operating Voltage | 300 VDC |
|-------------------|---------|

Contact Features

| | |
|--|--|
| | |
|--|--|



| | |
|--|--|
| Power Contact Base Material | Tin |
| Contact Underplating Material | Nickel |
| Contact Current Rating (Max) | 42 A |
| Contact Retention Within Housing | Without |
| Contact Type | Blade |
| PCB Contact Termination Area Plating Material | Tin |
| Contact Mating Area Plating Material | Gold Flash over Palladium Nickel |
| Contact Mating Area Plating Material Thickness | .76 μm [30 μin] |
| Underplate Material Thickness | 4.19 μm |

Termination Features

| | |
|---|-----------------------|
| Termination Post & Tail Length | 4.19 mm[.165 in] |
| Termination Method to Printed Circuit Board | Through Hole - Solder |

Mechanical Attachment

| | |
|--------------------------|-------------|
| PCB Mount Retention | With |
| PCB Mount Retention Type | Boardlock |
| Connector Mounting Type | Board Mount |
| Mating Retention Type | Boardlock |

Housing Features

| | |
|--------------------|--------------------------------|
| Centerline (Pitch) | 7.62 mm[.3 in] |
| Housing Color | Black |
| Housing Material | High Temperature Thermoplastic |

Usage Conditions

| | |
|-----------------------------|---------------------------|
| Operating Temperature Range | -20 – 105 °C[-4 – 221 °F] |
|-----------------------------|---------------------------|

Operation/Application

| | |
|---------------------|----------------|
| Circuit Application | Power & Signal |
|---------------------|----------------|

Industry Standards

| | |
|------------------------|---------------------------------------|
| UL Flammability Rating | UL 94V-0 |
| Glow Wire Rating | High Temperature Part - Not Glow Wire |

Packaging Features

| | |
|------------------|-----|
| Packaging Method | Box |
|------------------|-----|

Product Compliance


[For compliance documentation, visit the product page on TE.com>](#)

| | |
|---|---|
| EU RoHS Directive 2011/65/EU | Compliant |
| EU ELV Directive 2000/53/EC | Compliant |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold |
| EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC |
| Halogen Content | Not Low Halogen - contains Br or Cl > 900 ppm. |
| Solder Process Capability | Wave solder capable to 265°C |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

| | | | |
|--|---|---|--|
|  <p>TE Part # 6450543-6 MBXL VERT RCPT 3ACP</p> |  <p>TE Part # 1600606-2 PANEL MT RCPT HSG W/GUIDES P</p> |  <p>TE Part # 292499-1 PANEL MNT SLIDE TO LOCK CABLE</p> |  <p>TE Part # 6450173-1 MBXL R/A RCPT 3ACP+0P</p> |
|--|---|---|--|

Documents

Product Drawings

[MBXL R/A HDR 3ACP+0P](#)

English

CAD Files

[Customer View Model](#)

[ENG_CVM_CVM_6450123-3_A.2d_dxf.zip](#)



English

[3D PDF](#)

3D

Customer View Model

[ENG_CVM_CVM_6450123-3_A.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_6450123-3_A.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[POWER_CONNECTORS_CATALOG_SEC01_BOARD_TO_BOARD](#)

English

[2_PIECE_POWER_CONNECTORS_qrg_4-1773458-1](#)

English

Product Specifications

[Application Specification](#)

English

Product Environmental Compliance

[MD_6450123-3_092820161226_dmtec](#)

English

[MD_6450123-3_092820161226_dmtec](#)

English

Agency Approvals

[Agency Approval Document](#)

English