6646272-1 ✓ ACTIVE

TE Internal #: 6646272-1

Rectangular Power Connectors, Header, Receptacle, Wire-to-Board, 68 Position, 3 mm / 2.5 mm / 7.5 mm [.098 in / .11 in / .295 in] Centerline

View on TE.com >

Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors

Rectangular Power Connector Type: **Header**

Connector & Housing Type: **Receptacle**

Connector System: **Wire-to-Board**

Number of Positions: **68**

Centerline (Pitch): **2.5 mm, 3 mm, 7.5 mm [.098 in, .11 in, .295 in]**

Features

Product Type Features

Rectangular Power Connector Type	Header
Connector & Housing Type	Receptacle
Connector System	Wire-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Number of Positions	68
PCB Mount Orientation	Vertical
Number of Power Positions	20
Number of Signal Positions	48
Number of Rows	3

Electrical Characteristics

Operating Voltage	250 VDC

Contact Features

6646272-1

Rectangular Power Connectors, Header, Receptacle, Wire-to-Board, 68 Position, 3 mm / 2.5 mm / 7.5 mm [.098 in / .11 in / .295 in] Centerline

Contact Current Rating (Max)	1 A
Contact Retention Within Housing	With
Contact Type	Blade, Pin
PCB Contact Termination Area Plating Material	Tin
Contact Mating Area Plating Material	Gold
Contact Mating Area Plating Material Thickness	.76 µm[30 µin]

Termination Features

Termination Method to Printed Circuit Board	Through Hole - Press-Fit

Mechanical Attachment

Connector Mounting Type	Board Mount

Housing Features

Centerline (Pitch)	2.5 mm, 3 mm, 7.5 mm[.098 in][.11 in][.295 in]
Housing Color	Black
Housing Material	Thermoplastic

Dimensions

Row-to-Row Spacing	2.5 mm[.098 in]
Panel Thickness	30 mm
Accepts Wire Insulation Diameter Range	30 mm[30 in]
PCB Thickness (Recommended)	30 mm[30 in]

Usage Conditions

Operating Temperature Range	-40 – 105 °C[-40 – 221 °F]

Operation/Application

Circuit Application	Power & Signal

Industry Standards

UL Flammability Rating	UL 94V-0

Packaging Features

Packaging Method	Package

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant

6646272-1

Rectangular Power Connectors, Header, Receptacle, Wire-to-Board, 68 Position, 3 mm / 2.5 mm / 7.5 mm [.098 in / .11 in / .295 in] Centerline

EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224)
	Candidate List Declared Against: JAN 2021 (211)
	Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts

TE Part # 6646681-1
CONN,PIN,RT<,SLDR,FLATPAQ

Documents

Product Drawings
CONN,SKT,STR,COMPL,FLATPAQ

English

CAD Files
Customer View Model
ENG_CVM_CVM_6646272-1_B.2d_dxf.zip

English

3D PDF

3D

6646272-1

Rectangular Power Connectors, Header, Receptacle, Wire-to-Board, 68 Position, 3 mm / 2.5 mm / 7.5 mm [.098 in / .11 in / .295 in] Centerline

Customer View Model

ENG_CVM_CVM_6646272-1_B.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_6646272-1_B.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Application Specification

English