

ALBION[®]

CASTERS AND WHEELS

Heavy Duty Casters Powder Coat Finish

- Double Row Swivel Raceways
- Heat Treated and Factory Lubricated Raceways
- Blue Powder Coated Finish Over Yellow Zinc Chromate NSF Certified
-

Applications: Institutional, Hospitality, Food Service, Pharmaceuticals, Food Processing




934XA05252S-BLU



934FK05252S-BLU



934TM05252R-BLU



Overall Size: 3-3/4" x 4-5/8"
Hole Spacing: 2-5/8" x 3-5/8"
 slotted to 3" x 3"
Bolt Dia.: 3/8"

Wheel Dia. (In.)	Tread Width (In.)	Load Rating (lbs.)	Overall Height (In.)	Swivel Part Number	Rigid Part Number
Polyurethane Tread on Polyolefin Core Wheel (Delrin Bearing)					
4	2	600	5-5/8	934XA04251SBLU	934XA04251RBLU
5	2	750	6-1/2	934XA05252S-BLU	934XA05252R-BLU
6	2	900	7-1/2	934XA06252S-BLU	934XA06252R-BLU
8	2	900	9-1/2	934XA08252S-BLU	934XA08252R-BLU
Solid Polyurethane Wheel (Delrin Bearing)					
4	2	700	5-5/8	934FK04252S-BLU	934FK04252R-BLU
5	2	900	6-1/2	934FK05252S-BLU	934FK05252R-BLU
6	2	900	7-1/2	934FK06252S-BLU	934FK06252R-BLU
Phenolic Wheel (Delrin Bearing)					
4	2	800	5-5/8	934TM04251SBLU	934TM04251RBLU
5	2	900	6-1/2	934TM05252S-BLU	934TM05252R-BLU
6	2	900	7-1/2	934TM06252S-BLU	934TM06252R-BLU
8	2	900	9-1/2	934TM08252S-BLU	934TM08252R-BLU