

FEATURES

- Optical design provides one-for-one replacement 400 watt metal halide high bays at half the energy
- Advanced Thermal Management (ATM) provides optimized heat dissipation for cool ballast operation in unconditioned spaces
- Industry leading 5-year warranty for up to 65°C ambient operation
- Easy center-ballast cover allows tool-less access to electrical components without the removal of lamps, reflectors, or hardware
- Extremely low profile - only 2" overall height
- Reflector options include uplight (recommended) or solid top with either narrow or wide distribution
- Quick and simple hanging systems including chain, tong, or aircraft cable mounting
- Rotary locking lampholders
- Access cover in channel for easy wiring access
- "Plug and play" occupancy sensor and cord and plug accessories make installation simple to any standard LHV fixture
- UL listed 1598, cUL or CSA. Damp Location standard



createchange

ORDERING INFORMATION

LHV	4							
SIZE	NO. OF LAMPS	REFLECTOR	UPLIGHT	VOLTAGE	OPTIONS			
4 4'	4 Four 6 Six 8 Eight	M4R 95% Reflective Specular Aluminum (Narrow Beam) GW Gloss White (Wide Beam)	ST Solid Top U Uplight	U 120V-277V 347 347V 480 480V				

MODEL	LAMP TYPE	BALLAST	LAMPS INSTALLED
LHV VersaBay® Fluorescent High Bay	32 4', T8: 32, 30, 28 or 25 Watt 54 4', T5HO: 54, 51, or 49 Watt	NOTE: See Technical Section for other ballast options. LHV4-454 4EP (1) 4-Lamp Electronic T5HO, Programmed Start	T8 F830 3000K 80CRI F835 3500K 80CRI F841 4100K 80CRI F850 5000K 80CRI

ACCESSORIES (ORDER SEPARATELY)		LAMP TYPE	
LHVTH Tong Hanger (Pair)	LHVWG4-4 Wireguard, White, 4-Lamp Fixture	LHVWG4-6 Wireguard, White, 6-Lamp Fixture	LHVWG4-8 Wireguard, White, 8-Lamp Fixture
LHVQM5 Aircraft Cable, 5' (Pair)	LHVQM10 Aircraft Cable, 10' (Pair)	LHVSMP5 Single Point Mounting, Includes Pair of 5' Aircraft Cables	LHVSP Side Panels (Pair)
LHVOS1360 Occupancy/Daylight Sensor, with a 360° lens, 120/277/347V	LHVOS2360 Occupancy/Daylight Sensor, with a 360° lens, 120/277/347V	LHVOS480360 Occupancy/Daylight Sensor, with a 360° lens, 480V	C6TL15-120 Cord and Plug Kit (white), 6 ft., Twist Lock NEMA L5-15P, 15 amp, 120V
C6TL15-277 Cord and Plug Kit (white), 6 ft., Twist Lock NEMA L7-15P, 15 amp, 277V	C6P15-120 Cord and Plug Kit (white), 6 ft., Straight Blade NEMA 5-15P, 15 amp, 120V	LHV4-654 24EP (1) 2-Lamp and (1) 4-Lamp Electronic T5HO, Programmed Start 3EP (2) 3-Lamp and Electronic T5HO, Programmed Start	LHV4-854 4EP (2) 4-Lamp Electronic T5HO, Programmed Start
LHV4-432 4EHL (1) 4-Lamp Electronic T8, High Light Output, Instant Start EPHL (2) 2-Lamp Electronic T8, High Light Output, Programmed Start 4EPHL (1) 4-Lamp Electronic T8, High Light Output, Programmed Start	LHV4-632 3EHL (2) 3-Lamp Electronic T8, High Light Output, Instant Start 24EHL (1) 2-Lamp and (1) 4-Lamp Electronic T8, High Light Output, Instant Start 3EPHL (2) 3-Lamp Electronic T8, High Light Output, Programmed Start	LHV4-832 4EHL (2) 4-Lamp Electronic T8, High Light Output, Instant Start 4EPHL (2) 4-Lamp Electronic T8, High Light Output, Programmed Start	T5HO F5830 3000K 85CRI F5835 3500K 85CRI F5841 4100K 85CRI F5850 5000K 85CRI F5865 6500K 85CRI F51830 3000K 85CRI 51W F51835 3500K 85CRI 51W F51841 4100K 85CRI 51W F51850 5000K 85CRI 51W F51865 6500K 85CRI 51W F49830 3000K 85CRI 49W F49835 3500K 85CRI 49W F49841 4100K 85CRI 49W F49850 5000K 85CRI 49W F49865 6500K 85CRI 49W

¹Use programmed start ballast. Not recommended for use with instant start. For more occupancy/daylight harvesting sensor accessories see page 98.
²Side panels increase height to 27/8".

PRODUCT AVAILABILITY

MODEL	SOURCE	NO. OF LAMPS	UPLIGHT OPTIONS	LAMP TYPE	WIDTH	LENGTH	HEIGHT ²
LHV4	T5HO, T8	4	U, ST	32, 54	16 3/16"	48"	2"
	T5HO, T8	6	U, ST	32, 54	20 3/8"	48"	2"
	T5HO, T8	8	U, ST	32, 54	25"	48"	2"