



### THERMOMELT®

Thermomelt HEAT-STIK markers are a quick, low-cost method to accurately measure surface temperatures of various metals and equipment. Available in 88 Fahrenheit and 32 Centigrade temperatures, the stick-in-holder design provides convenience and durability for long-lasting use in the workshop or in the field.

Please note that the color of the Thermomelts are not a part of their function, since the temperature signal consists of melting. Indicator color is subject to change without notice.

---

## FEATURES & BENEFITS:

When the stick melts, the precise temperature is reached

Long-lasting stick is 33% bigger than competition

Accurate to within +/- 1% of Fahrenheit and +/- 3% Celsius rated temperatures; no need for sensor calibration

Ideal for: pre-heating, post-weld heat treating, interpass temperature monitoring, stress-relieving and annealing

Protective holder, shirt-clip and adjustment ring prevents breakage and improves handling

For low corrosion (low chlorides/halogens) applications, see [Thermomelt - Low Corrosion Temperatures](#)

Meets welding codes: AWS D1.1, ANSI/ASME Code B32.1 & B31.3, ASME Code Sec. I, III, and VII, NIST Traceable

Made in U.S.A.

---

## INDUSTRY USES:

Welding

Ship building and repair

Bridge fabrication

Metal fabrication

Forge and casting foundries

Railroad industry

Steel mills and warehouses

---

## SURFACE USES:

Steel and iron

---

## DETAILS:

86400 100°F (38°C)

86409 109°F (43°C)

86418 113°F (45°C)

86427 119°F (48°C)  
86436 125°F (52°C)  
86445 131°F (55°C)  
86454 138°F (59°C)  
86463 150°F (66°C)  
86472 163°F (73°C)  
86481 175°F (79°C)  
86490 182°F (83°C)  
86499 188°F (87°C)  
86508 194°F (90°C)  
86517 200°F (93°C)  
86522 206°F (97°C)  
86526 213°F (101°C)  
86535 219°F (104°C)  
86544 225°F (107°C)  
86553 238°F (114°C)  
86562 250°F (121°C)  
86569 256°F (124°C)  
86571 263°F (128°C)  
86580 269°F (132°C)  
86589 275°F (135°C)  
86598 282°F (139°C)  
86607 288°F (142°C)  
86616 294°F (146°C)  
86625 300°F (149°C)  
86634 306°F (152°C)  
86643 313°F (156°C)  
86652 319°F (159°C)  
86661 325°F (163°C)  
86670 331°F (166°C)  
86679 338°F (170°C)  
86688 344°F (173°C)  
86697 350°F (177°C)  
86706 363°F (184°C)  
86715 375°F (191°C)  
86724 388°F (198°C)

---

86733 400°F (204°C)  
86742 413°F (212°C)  
86751 425°F (218°C)  
86760 438°F (225°C)  
86769 450°F (232°C)  
86778 463°F (239°C)  
86787 475°F (246°C)  
86796 488°F (253°C)  
86805 500°F (260°C)  
86814 525°F (274°C)  
86823 550°F (288°C)  
86832 575°F (302°C)  
86841 600°F (316°C)  
86850 625°F (329°C)  
86859 650°F (343°C)  
86868 700°F (371°C)  
86877 750°F (399°C)  
86886 800°F (427°C)

86895 850°F (454°C)  
86904 900°F (482°C)  
86922 950°F (510°C)  
86931 1000°F (538°C)  
86940 1022°F (550°C)  
86949 1050°F (565°C)  
86958 1100°F (593°C)  
86967 1150°F (621°C)  
86976 1200°F (649°C)  
86985 1250°F (677°C)  
86994 1300°F (704°C)  
87003 1350°F (732°C)  
87012 1400°F (760°C)  
87021 1425°F (774°C)  
87030 1450°F (788°C)  
87039 1480°F (804°C)  
87048 1500°F (816°C)  
87057 1550°F (843°C)  
87066 1600°F (871°C)  
87075 1650°F (899°C)  
87084 1700°F (927°C)

---

87093 1750°F (954°C)  
87102 1800°F (982°C)  
87111 1850°F (1010°C)  
87120 1900°F (1038°C)  
87129 1950°F (1066°C)  
87138 2000°F (1093°C)  
87147 2050°F (1121°C)  
87156 2100°F (1149°C)  
87165 2150°F (1177°C)  
87174 2200°F (1204°C)  
86402 50°C  
86404 75°C  
86401 100°C  
86408 125°C  
84664 150°C  
86410 175°C  
86516 200°C  
86405 225°C  
86563 250°C  
86407 275°C  
86626 300°C  
86698 350°C  
86734 400°C  
86770 450°C  
86807 500°C  
86824 550°C  
86842 600°C  
86860 650°C  
86870 700°C  
86878 750°C  
86887 800°C  
86896 850°C  
86905 900°C

86923 950°C  
86932 1000°C  
86950 1050°C  
86960 1100°C  
86968 1150°C  
86977 1200°C

---



[Thermomelt® Product Bulletin](#)

[\*\*Click here for Thermomelt® MSDS\*\*](#)



[Thermomelt® European International Articles Letter](#)