

**DECAL & ADHESIVE REMOVER****DESCRIPTION AND USES**

Rust-Oleum® Decal & Adhesive Remover is ideal to remove decals from windows and bumper stickers. It starts to work in 10 minutes and clings to vertical surfaces.

PRODUCTS

SKU (10 ounce spray)	Description
248879	Decal & Adhesive Remover

PRODUCT APPLICATION**CAUTION!**

Protect hands with solvent-resistant gloves and eyes with chemical splash goggles.

Adhesive Remover will not harm most surfaces and we recommended to test a small inconspicuous area before attempting to remove stickers, especially on plastics and painted surfaces. The sticker has protected the paint underneath from fading and dulling due to sun exposure. You may notice a brighter color and shine where the bumper sticker was removed from the painted surface.

PRODUCT APPLICATION (cont.)**APPLICATION**

Hold can in an upright position and point the arrow on the button away from you. Apply a small amount of Decal & Adhesive Remover to the upper edge and corners of bumper sticker or decal. If overspray occurs, immediately wipe off with a clean cloth or paper towel. Let product seep behind the sticker to begin dissolving the adhesive. Allow 3-5 minutes for sticker adhesive to loosen. Lift a corner of sticker using a plastic scraper or toothpick and continue adding small amounts of product behind the sticker while gently lifting it away from the surface. After removing the sticker, remove any remaining residue by spraying Decal & Adhesive Remover onto the surface and wipe away with a clean cloth or paper towel.



TECHNICAL DATA

DECAL & ADHESIVE REMOVER

PHYSICAL PROPERTIES

	DECAL & ADHESIVE REMOVER
Composition	1-1 Difluoroethane, D-Limonene
Pigment Type	NA
Solvents	Aliphatic Hydrocarbons
MIR	0.6 Max
Fill Weight	10 ounces
Practical Coverage at Recommended DFT	5-6 sq. ft./can (0.46-0.56 m ² /can)
Dry Heat Resistance	NA
Shelf Life	5 years
Flash Point	-58°F (-50°C)
Safety Information	For additional information, see MSDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.