

# Material Safety Data Sheet

HAZARD WARNINGS	RISK PHRASES	PROTECTIVE CLOTHING
	<p>Flammable material; avoid heat and sources of ignition.                      Corrosive to eyes and skin on contact.                      Harmful compound, minimize exposure.                      Environmental hazard.                      This material is very toxic to aquatic organisms and may cause long term adverse effects to the aquatic environment.                      This compound is a respiratory sensitizer.  <b>CARCINOGEN. MINIMIZE EXPOSURE.</b>  <b>MUTAGEN. MINIMIZE EXPOSURE.</b>                      Reproductive Toxicity.                      Refrigerate.</p>	

## Section I. Chemical Product and Company Identification

Chemical Name	<b>Ammonia</b> (ca. 4% in Ethanol, ca. 2.0mol/L)		
Catalog Number	A2236	Supplier	TCI America 9211 N. Harborgate St. Portland OR 1-800-423-8616
Synonym	Not available.		
Chemical Formula	NH <sub>3</sub>		
CAS Number	7664-41-7 64-17-5 (Ethanol)	In case of Emergency Call	<b>Chemtrec®</b> <b>(800) 424-9300 (U.S.)</b> <b>(703) 527-3887 (International)</b>

## Section II. Composition and Information on Ingredients

Chemical Name	CAS Number	Percent (%)	TLV/PEL	Toxicology Data
Ammonia <small>(ca. 4% in Ethanol, ca. 2.0mol/L)</small>	7664-41-7 64-17-5 (Ethanol)	ca. 4.0% ca. 96.0 % (Ethanol)	This chemical is classified as a carcinogen. There is no acceptable exposure limit for a carcinogen. This compound is classified as a mutagen. There is no acceptable exposure limit for a mutage.	Rat LC <sub>50</sub> (inhalation) 2000 ppm/4H (Ethanol) Rat LD <sub>50</sub> (oral) 7060 mg/kg Mouse LD <sub>50</sub> (oral) 3450 mg/kg Rat LC <sub>50</sub> (inhalation) 20000 ppm/10H

## Section III. Hazards Identification

Acute Health Effects	<p>Corrosive to skin, eyes, and respiratory system. Liquid or spray mist may produce tissue damage, particularly in mucous membranes of the eyes, mouth and respiratory tract. Skin contact may produce burns. Eye contact can result in corneal damage or blindness. Inhalation of the spray mist may produce severe irritation of respiratory tract, characterized by coughing, choking, or shortness of breath. Corrosive materials may cause serious injury if ingested.                      Harmful if ingested or inhaled. Minimize exposure to this material. Severe overexposure can result in injury or death.                      Sensitizer; may cause allergy or asthma symptoms or breathing difficulties if inhaled.                      Follow safe industrial hygiene practices and always wear proper protective equipment when handling this compound.</p>
Chronic Health Effects	<p><b>CARCINOGENIC EFFECTS</b> : Carcinogenic by RTECS criteria.  <b>MUTAGENIC EFFECTS</b> : Not available.  <b>TERATOGENIC EFFECTS</b> : Tumorigenic effects.                      Rat TDLo Oral 1680 mg/kg/24 weeks continuous                      TOXIC Effects:                      Tumorigenic - Carcinogenic by RTECS criteria                      Gastrointestinal - Tumors  <b>TERATOGENIC EFFECTS</b> : Tumorigenic effects. (Ethanol)                      Mouse TDLo Oral 320 mg/kg/50 weeks intermittent                      TOXIC Effects:                      Tumorigenic - Equivocal tumorigenic agent by RTECS criteria                      Liver - Tumors                      Blood - Lymphomas including Hodgkin's disease                      Mouse TDLo Rectal 120 gm/kg/18 weeks intermittent                      TOXIC Effects:                      Tumorigenic Equivocal tumorigenic agent by RTECS criteria                      Gastrointestinal - Tumors                      Livers - Tumors  <b>DEVELOPMENTAL TOXICITY</b>: Reproductive Effects. (Ethanol)                      Rat TDLo Intraperitoneal 600 mg/kg, female 6-15 days of pregnancy                      TOXIC Effects:                      Effects on Fertility - Post-implantation mortality                      Effects on Embryo or Fetus - Extra embryonic structures                      Effects on Embryo or Fetus - Fetotoxicity                      Rat TDLo Oral 135 gm/kg, female 1 day of pregnancy - 7 days after birth                      TOXIC Effects:                      Effects on Newborn - Behavioral                      Effects on Newborn - Physical                      Rat TDLo Oral 147 mg/kg, female 1-21 days of pregnancy                      TOXIC Effects:</p>

Continued on Next Page

Emergency phone number (800) 424-9300

(ca. 4% in Ethanol, ca. 2.0mol/L)

Specific Developmental Abnormalities - Endocrine system  
 Effects on Newborn - Delayed effects  
 Repeated or prolonged contact with spray mist may produce chronic eye irritation and severe skin irritation. Repeated or prolonged exposure to spray mist may produce respiratory tract irritation leading to frequent attacks of bronchial infection.

**Section IV. First Aid Measures**

Eye Contact	Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.
Skin Contact	In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention.
Inhalation	If the victim is not breathing, perform mouth-to-mouth resuscitation. Loosen tight clothing such as a collar, tie, belt or waistband. If breathing is difficult, oxygen can be administered. Seek medical attention if respiration problems do not improve.
Ingestion	DO NOT INDUCE VOMITING. Loosen tight clothing such as a collar, tie, belt or waistband. If the victim is not breathing, perform mouth-to-mouth resuscitation. Examine the lips and mouth to ascertain whether the tissues are damaged, a possible indication that the toxic material was ingested; the absence of such signs, however, is not conclusive.

**Section V. Fire and Explosion Data**

Flammability	Flammable.	Auto-Ignition	651 °C (1203.8 °F) 363 °C (685.4 °F) (Ethanol)
Flash Points	132 °C (269.6 °F). 14 °C (57.2 °F). (Ethanol)	Flammable Limits	LOWER: 15% UPPER: 25% LOWER: 3.3% UPPER: 19% (Ethanol)
Combustion Products	These products include toxic carbon oxides (CO,CO <sub>2</sub> ), nitrogen oxides (NO <sub>x</sub> ).		
Fire Hazards	Not available.		
Explosion Hazards	Risks of explosion of the product in presence of mechanical impact: Not available. Risks of explosion of the product in presence of static discharge: Not available.		
Fire Fighting Media and Instructions	Flammable liquid. SMALL FIRE: Use DRY chemical powder. LARGE FIRE: Use alcohol foam, water spray or fog. Consult with local fire authorities before attempting large scale fire-fighting operations.		

**Section VI. Accidental Release Measures**

Spill Cleanup Instructions	Flammable material. Corrosive material. Harmful material. Environmentally hazardous material. Respiratory sensitizing material. Carcinogenic material. Mutagenic material. Reproductive toxicity. Keep away from heat. Mechanical exhaust required. Stop leak if without risk. Absorb with DRY earth, sand or other non-combustible material. DO NOT get water inside container. DO NOT touch spilled material. Use water spray curtain to divert vapor drift. Prevent entry into sewers, basements or confined areas; dike if needed. Consult federal, state, and/or local authorities for assistance on disposal.
----------------------------	--

**Section VII. Handling and Storage**

Handling and Storage Information	FLAMMABLE. CORROSIVE. HARMFUL. ENVIRONMENTAL HAZARD. RESPIRATORY SENSITIZER. CARCINOGEN. MUTAGEN. REPRODUCTIVE TOXICITY. REFRIGERATE. Keep container dry. Keep away from heat. Mechanical exhaust required. Avoid excessive heat and light. Do not breathe gas/fumes/ vapor/spray. Never add water to this product. Wear suitable protective clothing. If you feel unwell, seek medical attention and show the label when possible. Treat symptomatically and supportively. Always store away from incompatible compounds such as oxidizing agents, acids.
----------------------------------	---

**Section VIII. Exposure Controls/Personal Protection**

Engineering Controls	Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value. Ensure that eyewash station and safety shower is proximal to the work-station location.
Personal Protection	Face shield. Lab coat. Vapor respirator. Boots. Gloves. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product. Be sure to use a MSHA/NIOSH approved respirator or equivalent.
Exposure Limits	 This chemical is classified as a carcinogen. There is no acceptable exposure limit for a carcinogen. This compound is classified as a mutagen. There is no acceptable exposure limit for a mutage.

**Section IX. Physical and Chemical Properties**

Physical state @ 20°C	Liquid. (Clear, colorless.)	Solubility	Not available.
Specific Gravity	0.59 0.79 (Ethanol)		
Molecular Weight	H <sub>3</sub> N: 17.03 C <sub>2</sub> H <sub>6</sub> O: 46.07 (Ethanol)	Partition Coefficient	Log P <sub>ow</sub> : -0.32 (Ethanol)
Boiling Point	-33 °C (-27.4 °F) 78 to 80 °C (172.4 to 176 °F) (Ethanol)	Vapor Pressure	4802 mmHg (@ 15.5 °C) 5.8 kPa (@ 20 °C) (Ethanol)
Melting Point	-78 °C (-108.4 °F)	Vapor Density	0.59 (Air = 1) 1.6 (Air = 1) (Ethanol)
Refractive Index	Not available.	Volatility	Not available.

Continued on Next Page

Emergency phone number (800) 424-9300

(ca. 4% in Ethanol, ca. 2.0mol/L)

Critical Temperature	Not available.	Odor	Not available.
Viscosity	Not available.	Taste	Not available.

### Section X. Stability and Reactivity Data

Stability	This material is stable if stored under proper conditions. (See Section VII for instructions)
Conditions of Instability	Avoid excessive heat and light.
Incompatibilities	Reactive with oxidizing agents, acids, alkali metals, zinc, iron, ammonia, aldehydes, peroxides, copper, halogens, cadmium/cadmium oxides, silver/silver oxides.

### Section XI. Toxicological Information

RTECS Number	BO0875000 KQ630000 (Ethanol)
Routes of Exposure	Eye Contact. Ingestion. Inhalation. Skin contact.
Toxicity Data	Rat LC <sub>50</sub> (inhalation) 2000 ppm/4H (Ethanol) Rat LD <sub>50</sub> (oral) 7060 mg/kg Mouse LD <sub>50</sub> (oral) 3450 mg/kg Rat LC <sub>50</sub> (inhalation) 20000 ppm/10H
Chronic Toxic Effects	<b>CARCINOGENIC EFFECTS</b> : Carcinogenic by RTECS criteria. <b>MUTAGENIC EFFECTS</b> : Not available. <b>TERATOGENIC EFFECTS</b> : Tumorigenic effects. Rat TDLo Oral 1680 mg/kg/24 weeks continuous TOXIC Effects: Tumorigenic - Carcinogenic by RTECS criteria Gastrointestinal - Tumors <b>TERATOGENIC EFFECTS</b> : Tumorigenic effects. (Ethanol) Mouse TDLo Oral 320 mg/kg/50 weeks intermittent TOXIC Effects: Tumorigenic - Equivocal tumorigenic agent by RTECS criteria Liver - Tumors Blood - Lymphomas including Hodgkin's disease Mouse TDLo Rectal 120 gm/kg/18 weeks intermittent TOXIC Effects: Tumorigenic Equivocal tumorigenic agent by RTECS criteria Gastrointestinal - Tumors Livers - Tumors <b>DEVELOPMENTAL TOXICITY</b> : Reproductive Effects. (Ethanol) Rat TDLo Intraperitoneal 600 mg/kg, female 6-15 days of pregnancy TOXIC Effects: Effects on Fertility - Post-implantation mortality Effects on Embryo or Fetus - Extra embryonic structures Effects on Embryo or Fetus - Fetotoxicity Rat TDLo Oral 135 gm/kg, female 1 day of pregnancy - 7 days after birth TOXIC Effects: Effects on Newborn - Behavioral Effects on Newborn - Physical Rat TDLo Oral 147 mg/kg, female 1-21 days of pregnancy TOXIC Effects: Specific Developmental Abnormalities - Endocrine system Effects on Newborn - Delayed effects Repeated or prolonged contact with spray mist may produce chronic eye irritation and severe skin irritation. Repeated or prolonged exposure to spray mist may produce respiratory tract irritation leading to frequent attacks of bronchial infection.
Acute Toxic Effects	Corrosive to skin, eyes, and respiratory system. Liquid or spray mist may produce tissue damage, particularly in mucous membranes of the eyes, mouth and respiratory tract. Skin contact may produce burns. Eye contact can result in corneal damage or blindness. Inhalation of the spray mist may produce severe irritation of respiratory tract, characterized by coughing, choking, or shortness of breath. Corrosive materials may cause serious injury if ingested. Harmful if ingested or inhaled. Minimize exposure to this material. Severe overexposure can result in injury or death. Sensitizer; may cause allergy or asthma symptoms or breathing difficulties if inhaled. Follow safe industrial hygiene practices and always wear proper protective equipment when handling this compound.

### Section XII. Ecological Information

Ecotoxicity	Not available.
Environmental Fate	Ethanol's production and use in alcoholic beverages, as a solvent, fuel additive, in the manufacture of denatured alcohol, pharmaceuticals (rubbing compounds, tonics, lotions, colognes), in perfumery, and organic synthesis may result in its release to the environment through various waste streams; its use as a fungicide and plant regulator will result in its direct release to the environment. Ethanol has been identified as a natural emission product from various plants, fermentation product and as a biological decomposition product of wastes and sewage. If released to the atmosphere, an extrapolated vapor pressure of 59.3 mm Hg at 25 deg C indicates that ethanol will exist solely in the vapor phase. Vapor phase ethanol is degraded in the atmosphere by reaction with photochemically-produced hydroxyl radicals; the half-life for this reaction in air is estimated to be 5 days. If released to soil, ethanol is expected to have very high mobility based upon an estimated Koc of 1. Volatilization from moist soil surfaces is expected to be an important fate process based upon a Henry's Law constant of 5X10 <sup>-6</sup> atm-cu m/mole. Ethanol may also volatilize from dry soils based upon its vapor pressure. Biodegradation is expected to occur rapidly in the environment based on numerous screening tests using different types of inocula and incubation periods. Ethanol was degraded with half-lives on the order of a few days using microcosms constructed with a low organic sandy soil and groundwater, indicating it is unlikely to be persistent in the environment. If released into water, ethanol is not expected to adsorb to suspended solids and sediment based upon the estimated Koc. Volatilization from water surfaces is expected to be an important fate process based upon this compound's Henry's Law constant. Estimated volatilization half-lives for a model

Continued on Next Page

Emergency phone number (800) 424-9300

(ca. 4% in Ethanol, ca. 2.0mol/L)

river and model lake are 3 and 39 days, respectively. An estimated BCF of 3 suggests the potential for bioconcentration in aquatic organisms is low. Hydrolysis of ethanol and photolysis in sunlit surface waters are not expected since ethanol lacks functional groups that are susceptible to hydrolysis or photolysis under environmental conditions. Occupational exposure to ethanol may occur through inhalation and dermal contact with this compound at workplaces where ethanol is produced or used. The general population is directly exposed to ethanol through the consumption of alcoholic beverages and other products that contain ethanol. Monitoring data also indicate that the general population may be exposed to ethanol via inhalation of ambient air.

### Section XIII. Disposal Considerations

**Waste Disposal** Recycle to process, if possible. Consult your local regional authorities. You may be able to dissolve or mix material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber system. Observe all federal, state and local regulations when disposing of the substance.

### Section XIV. Transport Information

DOT Classification DOT Class 3: Flammable material

PIN Number UN1170

Proper Shipping Name Ethanol solution

Packing Group (PG) II

DOT Pictograms



### Section XV. Other Regulatory Information and Pictograms

TSCA Chemical Inventory (EPA) This compound is **ON** the EPA Toxic Substances Control Act (TSCA) inventory list.

WHMIS Classification (Canada) CLASS B-2: Flammable liquid with a flash point lower than 37.8°C (100°F).  
CLASS D-2B: Material causing other toxic effects (TOXIC).  
CLASS E: Corrosive liquid.  
On DSL

EINECS Number (EEC) 231-635-3  
200-578-6 (Ethanol)

EEC Risk Statements R10- Flammable.  
R18- In use, may form flammable/explosive vapor-air mixture.  
R20/21/22- Harmful by inhalation, in contact with skin and if swallowed.  
R34- Causes burns.  
R45- May cause cancer.  
R46- May cause heritable genetic damage.  
R47- May cause birth defects.  
R42- May cause sensitization by inhalation.  
R50- Very toxic to aquatic organisms.  
R53- May cause long-term adverse effects in the aquatic environment.

Japanese Regulatory Data ENCS No. 1-314; 1-391  
ENCS No. 2-202 (Ethanol)

### Section XVI. Other Information

**Version 1.0**  
**Validated on 11/12/2010.**  
**Printed 11/12/2010.**

#### Notice to Reader

TCI laboratory chemicals are for research purposes only and are NOT intended for use as drugs, food additives, households, or pesticides. The information herein is believed to be correct, but does not claim to be all inclusive and should be used only as a guide. Neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All chemical reagents must be handled with the recognition that their chemical, physiological, toxicological, and hazardous properties have not been fully investigated or determined. All chemical reagents should be handled only by individuals who are familiar with their potential hazards and who have been fully trained in proper safety, laboratory, and chemical handling procedures. Although certain hazards are described herein, we can not guarantee that these are the only hazards which exist. Our MSDS sheets are based only on data available at the time of shipping and are subject to change without notice as new information is obtained. Avoid long storage periods since the product is subject to degradation with age and may become more dangerous or hazardous. It is the responsibility of the user to request updated MSDS sheets for products that are stored for extended periods. Disposal of unused product must be undertaken by qualified personnel who are knowledgeable in all applicable regulations and follow all pertinent safety precautions including the use of appropriate protective equipment (e.g. protective goggles, protective clothing, breathing equipment, facial mask, fume hood). For proper handling and disposal, always comply with federal, state, and local regulations.