



## PVC & CPVC SCHEDULE 80 FITTINGS, UNIONS, TANK ADAPTERS, EXPANSION JOINTS & SADDLES

# PVC Performance Engineered & Tested



SPEARS® Schedule 80 PVC product designs combine years of proven experience with computer generated stress analysis to yield the optimum physical structure and performance for each fitting. Material reinforcement is uniformly placed in stress concentration areas for substantially improved pressure handling capability. Resulting products are subjected to numerous verification tests to assure obtaining the very best PVC fittings available.

### 1/4" Through 12" Availability

Spears® comprehensive line of PVC injection molded fittings and extruded pipe offers a variety of configurations in sizes 1/4" through 12". Schedule 80 fittings are manufactured to ASTM D 2467 and pipe is produced to ASTM D 1785. Spears® exclusive CL150 Flanges are produced in sizes 1/2" - 18" with ANSI B16.5 bolt patterns, plus numerous Unions, Saddles, Transition and Specialty fittings in a variety of sizes.

### Exceptional Chemical & Corrosion Resistance

Unlike metal, PVC fittings and pipe never rust, scale, or pit, and will provide many years of maintenance-free service and extended system life.

### High Temperature Ratings

PVC thermoplastic can handle fluids at service temperatures up to 140°F (60°C), allowing a wide range of process applications, including corrosive fluids.

### Lower Installation Costs

Substantially lower material costs than steel alloys or lined steel, combined with lighter weight and ease of installation, can reduce installation costs by as much as 60% over conventional metal systems.

### Higher Flow Capacity

Smooth interior walls result in lower pressure loss and higher volume than conventional metal fittings.

### Additional Fabricated Configurations through 36"

Extra large, hard-to-find, and custom configurations are fabricated from NSF® Certified pipe. Fittings are engineered and tested to provide full pressure handling capabilities according to Spears® specifications.

### Advanced Design Specialty Fittings

Spears® wide range of innovative, improved products include numerous metal-to-plastic transition fittings and unions with Spears® patented special reinforced (SR) plastic threads.

### PVC Valves

SPEARS® PVC Valve products are available for total system compatibility and uniformity.

### 1/8" Through 24" Industrial Pipe Availability

Spears® premium quality Industrial CPVC pipe is offered in Schedule 80 sizes 1/8" through 24". Schedule 40 CPVC pipe is also available.

### PVC Sample Engineering Specifications

All PVC Schedule 80 pipe and fittings shall be produced by Spears® Manufacturing Company from PVC Type I, cell classification 12454, conforming to ASTM Standard D 1784. All PVC injection molded Schedule 80 fittings and extruded pipe shall be Certified for potable water service by NSF International. All Schedule 80 fittings shall be manufactured in strict compliance to ASTM D 2467 and Schedule 80 pipe shall be manufactured in strict compliance to ASTM D 1785. All fabricated fittings shall be produced in accordance with Spears® General Specifications for Fabricated Fittings. All PVC flanges shall be designed and manufactured to meet CL150 bolt pattern per ANSI Standard B16.5 and rated for a maximum internal pressure of 150 psi, non-shock at 73°F.

## CPVC Performance Engineered and Tested



SPEARS® Schedule 80 CPVC pipe and fitting designs combine years of proven experience with computer generated stress analysis to yield the optimum physical structure and performance for each fitting. Material reinforcement is uniformly placed in stress concentration areas for substantially improved pressure handling capability. Resulting products are subjected to numerous verification tests to assure the very best CPVC piping products available.

### **1/4" Through 24" Availability**

Spears® comprehensive line of CPVC fittings offers a variety of configurations in Schedule 80 sizes 1/4" through 24".

### **Exceptional Chemical & Corrosion Resistance**

Unlike metal, CPVC fittings never rust, scale or pit, and will provide many years of maintenance-free service and extended system life.

### **Higher Temperature Ratings**

High Temperature CPVC Thermoplastics can handle fluids at service temperatures up to 200°F, allowing a wide range of process applications, including hot corrosive liquids.

### **Higher Flow Capacity**

Smooth interior walls result in lower pressure loss and higher volume than conventional metal fittings.

### **Lower Installation Costs**

Substantially lower material costs than steel alloys or lined steel, combined with lighter weight and ease of installation, can reduce installation costs by as much as 60% over conventional metal systems.

### **SPEARS® Schedule 80 14" Through 24" Fittings & Flanges**

Schedule 80 CPVC 14" through 24" fittings are a special engineered product by Spears® Manufacturing Company, where no applicable ASTM specifications exist. Available in a variety of injection molded and fabricated configurations including Flanges, Couplings, Elbows, Bushings and Tees, plus custom fabrication to virtually any configuration.

### **1/8" Through 24" Industrial Pipe Availability**

Spears® premium quality Industrial CPVC pipe is offered in Schedule 80 sizes 1/8" through 24". Schedule 40 CPVC pipe is also available.

### **American Bureau of Shipping (ABS) Type Approval**

Spears® Schedule 40 and Schedule 80 CPVC pipe and fittings are ABS Type Approved for marine and offshore applications in nominal pipe sizes through 12". Type Approval details and restrictions are specified in ABS Certificate # 10-HS539421-1-PDA available on the ABS website at [www.eagle.org](http://www.eagle.org).

### **CPVC Sample Engineering Specifications**

All CPVC Schedule 80 fittings shall be produced by Spears® Manufacturing Company from CPVC materials, cell classification 23447 conforming to ASTM Standard D 1784. All injection molded fittings through 12" shall be manufactured in compliance to ASTM F 439 and all pipe through 16" shall be manufactured in compliance to ASTM F 441. Pipe and fittings shall be Certified by NSF International for use with potable water service. All 14" through 24" and fabricated fittings shall be produced in accordance with Spears® Specifications. All CPVC flanges shall be designed and manufactured to meet CL150 bolt pattern per ANSI Standard B16.5.



## PVC & CPVC SCHEDULE 80 FITTINGS, UNIONS, TANK ADAPTERS, EXPANSION JOINTS & SADDLES

The information contained in this publication is based on current information and Product design at the time of publication and is subject to change without notification. Our ongoing commitment to product improvement may result in some variation. No representations, guarantees or warranties of any kind are made as to its accuracy, suitability for particular applications or results to be obtained therefrom. For verification of technical data or additional information not contained herein, please contact Spears® Technical Services Department [West Coast: (818) 364-1611 — East Coast: (678) 985-1263].

### General Information

#### Recommendations For Installers And Users

Plastic piping systems should be ENGINEERED, INSTALLED and OPERATED in accordance with ESTABLISHED DESIGN AND ENGINEERING STANDARDS AND PROCEDURES for plastic piping systems. Suitability for the intended service application should be determined by the installer and/or user prior to installation of a plastic piping system. PRIOR TO ASSEMBLY, all piping system components should be inspected for damage or irregularities. Mating components should be checked to assure that tolerances and engagements are compatible. Do not use any components that appear irregular or do not fit properly. Contact the appropriate manufacturer of the component product in question to determine usability. Consult all applicable codes and regulations for compliance prior to installation.

**Solvent Weld Connections** — Use quality solvent cements and primers formulated for the intended service application, pipe size and type of joint. While the pipe and fitting materials may be compatible with the intended medium, the solvent cement may not be. Consult the manufacturers for suitability of use. Read and follow the cement and primer manufacturers' applications and cure time instructions thoroughly. Be sure to use the correct size applicator.

**Threaded Connections** — Use a quality grade thread sealant. **WARNING:** SOME PIPE JOINT COMPOUNDS OR PTFE PASTES MAY CONTAIN SUBSTANCES THAT COULD CAUSE STRESS CRACKING TO PLASTIC. Spears® Manufacturing company recommends the use of Spears® BLUE 75™ Thread Sealant which has been tested for compatibility with Spears® products. Please follow the sealant manufacturers' application/installation instructions. Choice of an appropriate thread sealant other than those listed above is at the discretion of the installer. 1 to 2 turns beyond FINGER TIGHT is generally all that is required to make a sound plastic threaded connection. Unnecessary OVERTIGHTENING will cause DAMAGE TO BOTH PIPE AND FITTING.

### Standards and Specifications


Molded Schedule 80 PVC products are manufactured to ASTM D 2467 for use with pipe manufactured to ASTM D 1785. Molded Schedule 80 CPVC products are manufactured to ASTM F 439 for use with pipe manufactured to ASTM F 441. Certain products carry reduced pressure handling capability and have maximum internal pressure ratings at 73°F noted.

Fabricated Schedule 80 PVC pressure fittings (part numbers ending with "F") are manufactured to Spears® specifications for use with pipe manufactured to ASTM D 1785. Schedule 80 CPVC fabricated fittings for use with pipe manufactured to ASTM F 441. See publication FAB-7, General Specifications for Standard Fabricated Fittings for additional information.


All specified Schedule 80 PVC and CPVC products are manufactured from materials certified by NSF® for use in potable water service.

"Lead Free" low lead certification – unless otherwise specified, all Spears® Schedule 80 fittings specified here-in are certified by NSF International to ANSI/NSF® Standard 61, Annex G and is in compliance with California's Health & Safety Code Section 116825 (commonly known as AB1953) and Vermont Act 193. Weighted average lead content  $\leq 0.25\%$ . Spears® PVC and CPVC Pipe, Fittings and Valves have always been lead-free and Certified by NSF International for use in potable water systems. Spears® offers a wide range of lead-free specialty fittings and transition adapters for plumbing applications. However, certain brass threaded adapter fittings for applications that are not intended to convey water for human consumption through drinking or cooking are still produced and available.


## ASTM STANDARD DIMENSIONS



| Nominal Pipe Size In. | Mean Outside Diameter In. | O. D. Tolerance In. | Minimum Wall Thickness In. |
|-----------------------|---------------------------|---------------------|----------------------------|
| 1/8                   | 0.405                     | ± 0.004             | 0.095                      |
| 1/4                   | 0.540                     | ± 0.004             | 0.119                      |
| 3/8                   | 0.675                     | ± 0.004             | 0.126                      |
| 1/2                   | 0.840                     | ± 0.004             | 0.147                      |
| 3/4                   | 1.050                     | ± 0.004             | 0.154                      |
| 1                     | 1.315                     | ± 0.005             | 0.179                      |
| 1-1/4                 | 1.660                     | ± 0.005             | 0.191                      |
| 1-1/2                 | 1.900                     | ± 0.006             | 0.200                      |
| 2                     | 2.375                     | ± 0.006             | 0.218                      |
| 2-1/2                 | 2.875                     | ± 0.007             | 0.276                      |
| 3                     | 3.500                     | ± 0.008             | 0.300                      |
| 4                     | 4.500                     | ± 0.009             | 0.337                      |
| 5                     | 5.563                     | ± 0.010             | 0.375                      |
| 6                     | 6.625                     | ± 0.011             | 0.432                      |
| 8                     | 8.625                     | ± 0.015             | 0.500                      |
| 10                    | 10.750                    | ± 0.015             | 0.593                      |
| 12                    | 12.750                    | ± 0.015             | 0.687                      |



| Nominal Size In. | Diameter   |          |             | Socket Length Minimum C |
|------------------|------------|----------|-------------|-------------------------|
|                  | Entrance A | Bottom B | Tolerance A |                         |
| 1/8              | 0.417      | 0.401    | ± 0.004     | 0.500                   |
| 1/4              | 0.552      | 0.536    | ± 0.004     | 0.625                   |
| 3/8              | 0.687      | 0.671    | ± 0.004     | 0.750                   |
| 1/2              | 0.848      | 0.836    | ± 0.004     | 0.875                   |
| 3/4              | 1.058      | 1.046    | ± 0.004     | 1.000                   |
| 1                | 1.325      | 1.310    | ± 0.005     | 1.125                   |
| 1-1/4            | 1.670      | 1.655    | ± 0.005     | 1.250                   |
| 1-1/2            | 1.912      | 1.894    | ± 0.006     | 1.375                   |
| 2                | 2.387      | 2.369    | ± 0.006     | 1.500                   |
| 2-1/2            | 2.889      | 2.868    | ± 0.007     | 1.750                   |
| 3                | 3.516      | 3.492    | ± 0.008     | 1.875                   |
| 4                | 4.518      | 4.491    | ± 0.009     | 2.250                   |
| 5                | 5.583      | 5.553    | ± 0.010     | 2.625                   |
| 6                | 6.647      | 6.614    | ± 0.011     | 3.000                   |
| 8                | 8.655      | 8.610    | ± 0.015     | 4.000                   |
| 10               | 10.780     | 10.735   | ± 0.015     | 5.000                   |
| 12               | 12.780     | 12.735   | ± 0.015     | 6.000                   |



| Nominal Size In. | Threads Per Inch | Effective Thread Length L | Pitch Of Thread P |
|------------------|------------------|---------------------------|-------------------|
| 1/8              | 27               | 0.2639                    | 0.03704           |
| 1/4              | 18               | 0.4018                    | 0.05556           |
| 3/8              | 18               | 0.4078                    | 0.05556           |
| 1/2              | 14               | 0.5337                    | 0.07143           |
| 3/4              | 14               | 0.5457                    | 0.07143           |
| 1                | 11-1/2           | 0.6828                    | 0.08696           |
| 1-1/4            | 11-1/2           | 0.7068                    | 0.08696           |
| 1-1/2            | 11-1/2           | 0.7235                    | 0.08696           |
| 2                | 11-1/2           | 0.7565                    | 0.08696           |
| 2-1/2            | 8                | 1.1375                    | 0.12500           |
| 3                | 8                | 1.2000                    | 0.12500           |
| 4                | 8                | 1.3000                    | 0.12500           |
| 5                | 8                | 1.4063                    | 0.12500           |
| 6                | 8                | 1.5125                    | 0.12500           |
| 8                | 8                | 1.7125                    | 0.12500           |

## STANDARD COMPARISONS

SPEARS® IPS-to-Metric transition unions are listed by nominal size. The chart below compares nominal and actual\* pipe O.D. for each size according to the designated standard.

| JIS K6741 (mm) |         | DIN 8062 (mm) |         | ASTM D1785 (in.) |         | NPT—ANSI B1.20.1** Tapered Thread |             | BSP—BS21, DIN 2999, ISO 7/1 Thread |                |
|----------------|---------|---------------|---------|------------------|---------|-----------------------------------|-------------|------------------------------------|----------------|
| Nominal        | Actual* | O.D.          | Actual* | Nominal          | Actual* | Designation                       | Threads/in. | Designation                        | Threads/25.4mm |
| 16             | 22      | 15            | 20      | 1/2              | .840    | 1/2                               | 14          | 1/2                                | 14             |
| 20             | 26      | 20            | 25      | 3/4              | 1.050   | 3/4                               | 14          | 3/4                                | 14             |
| 25             | 32      | 25            | 32      | 1                | 1.315   | 1                                 | 11.5        | 1                                  | 11             |
| 30             | 38      | 38            | 40      | 1-1/4            | 1.660   | 1-1/4                             | 11.5        | 1-1/4                              | 11             |
| 40             | 48      | 40            | 50      | 1-1/2            | 1.900   | 1-1/2                             | 11.5        | 1-1/2                              | 11             |
| 50             | 60      | 50            | 63      | 2                | 2.375   | 2                                 | 11.5        | 2                                  | 11             |
| 75             | 89      | 80            | 90      | 3                | 3.500   | 3                                 | 8           | 3                                  | 11             |
| 100            | 114     | 100           | 110     | 4                | 4.500   | 4                                 | 8           | 4                                  | 11             |

\*Specified dimension, certain tolerances apply

\*\*NPT and BSP have different thread angles and not compatible.



## PVC & CPVC SCHEDULE 80 FITTINGS, UNIONS, TANK ADAPTERS, EXPANSION JOINTS & SADDLES

### Injection Molded Dimensions References:

**G** = (LAYING LENGTH) intersection of center lines to bottom of socket/thread; 90° elbows, tees, crosses;  $\pm 1/32$  inch.  
**H** = Intersection of center lines to face of fitting; 90° elbow tees, crosses;  $\pm 1/32$  inch.  
**J** = Intersection of center lines to bottom of socket/thread; 45° elbows;  $\pm 1/32$  inch


**L** = Overall length of fittings;  $\pm 1/16$  inch.  
**H** = Outside diameter of socket/thread hub;  $\pm 1/16$  inch.  
**N** = Socket bottom to socket bottom; couplings;  $\pm 1/16$  inch  
**W** = Height of cap;  $\pm 1/16$  inch.

### Fabricated Dimension References:

**G** = (LAYING LENGTH) intersection of center lines to bottom of socket/thread; 90° elbows, tees, crosses  $\pm 1/4$  inch; 14" & larger  $\pm 1/2$  inch.  
**H** = Intersection of center lines to face of fitting; 90° elbows  $\pm 1/4$  inch, 14" & larger  $\pm 3/4$  inch; wyes  $\pm 1/2$  inch; tees, crosses  $\pm 1/4$  inch; 14" & larger  $\pm 1/2$  inch.  
**J** = Intersection of center lines to bottom of socket/thread; 45° elbows;  $\pm 1/4$  inch; 14" & larger  $\pm 1/2$  inch.


**L** = Overall length of fittings;  $\pm 1/2$  inch; 14" & larger  $\pm 1$  inch; wyes  $\pm 1$  inch.  
**M** = Outside diameter of socket/thread hub;  $\pm 1/4$  inch.  
**N** = Socket bottom to socket bottom; couplings;  $\pm 1/2$   
**W** = Height of cap;  $\pm 1/4$  inch.

### Typical Fabricated Dimension References



### TEE

Socket x Socket x Socket



| Part Number |          | Size  | G       | G1      | H       | H1      | L       | M       | Approx. Wt. (Lbs.) |      |
|-------------|----------|-------|---------|---------|---------|---------|---------|---------|--------------------|------|
| PVC         | CPVC     |       |         |         |         |         |         |         | PVC                | CPVC |
| 801-002     | 801-002C | 1/4   | 5/16    | 5/16    | 31/32   | 31/32   | 1-15/16 | 27/32   | .04                | .04  |
| 801-003     | 801-003C | 3/8   | 15/32   | 15/32   | 1-1/4   | 1-1/4   | 2-1/2   | 31/32   | .06                | .06  |
| 801-005     | 801-005C | 1/2   | 17/32   | 17/32   | 1-15/32 | 1-15/32 | 2-15/16 | 1-3/16  | .11                | .11  |
| 801-007     | 801-007C | 3/4   | 21/32   | 21/32   | 1-11/16 | 1-11/16 | 3-13/32 | 1-13/32 | .16                | .18  |
| 801-010     | ---      | 1     | 7/8     | 7/8     | 2       | 2       | 4       | 1-3/4   | .27                | ---  |
| ---         | 801-010C | 1     | 27/32   | 27/32   | 2       | 2       | 3-31/32 | 1-23/32 | ---                | .29  |
| 801-012     | 801-012C | 1-1/4 | 1-1/32  | 1-1/32  | 2-9/32  | 2-9/32  | 4-19/32 | 2-3/32  | .39                | .40  |
| 801-015     | 801-015C | 1-1/2 | 1-3/16  | 1-3/16  | 2-9/32  | 2-9/32  | 5-1/8   | 2-3/8   | .52                | .57  |
| 801-020     | 801-020C | 2     | 1-11/32 | 1-11/32 | 2-15/16 | 2-15/16 | 5-27/32 | 2-7/8   | .80                | .85  |
| 801-025     | ---      | 2-1/2 | 1-3/4   | 1-3/4   | 3-1/2   | 3-1/2   | 7-1/32  | 3-15/32 | 1.46               | ---  |
| ---         | 801-025C | 2-1/2 | 1-23/32 | 1-23/32 | 3-1/2   | 3-1/2   | 7       | 3-15/32 | ---                | 1.62 |
| 801-030     | 801-030C | 3     | 2-3/32  | 2-3/32  | 3-31/32 | 3-31/32 | 7-15/16 | 4-3/16  | 2.16               | 2.43 |
| 801-040     | 801-040C | 4     | 2-1/2   | 2-1/2   | 4-3/4   | 4-3/4   | 9-1/2   | 5-1/4   | 3.52               | 3.72 |


# PVC & CPVC SCHEDULE 80 FITTINGS, UNIONS, TANK ADAPTERS, EXPANSION JOINTS & SADDLES



## TEE

(continued)


Socket x Socket x Socket



| Part Number |           | Size | G       | G1      | H        | H1       | L       | M        | Approx. Wt. (Lbs.) |        |
|-------------|-----------|------|---------|---------|----------|----------|---------|----------|--------------------|--------|
| PVC         | CPVC      |      |         |         |          |          |         |          | PVC                | CPVC   |
| 801-050     | 801-050C  | 5    | 3-1/8   | 3-1/8   | 5-25/32  | 5-25/32  | 11-5/8  | 6-13/32  | 6.03               | 6.47   |
| 801-050F    | 801-050CF | 5    | 5-1/2   | 5-1/2   | 8-1/2    | 8-1/2    | 17      | 6-5/16   | 13.26              | 18.38  |
| 801-060     | ---       | 6    | 3-25/32 | 3-25/32 | 6-13/16  | 6-13/16  | 13-5/8  | 7-5/8    | 10.78              | ---    |
| ---         | 801-060C  | 6    | 4-1/32  | 4-1/32  | 7-3/32   | 7-3/32   | 14-5/32 | 7-19/32  | ---                | 12.19  |
| 801-080     | 801-080C  | 8    | 4-13/16 | 4-13/16 | 8-7/8    | 8-7/8    | 17-3/4  | 9-23/32  | 21.21              | 21.53  |
| 801-080F    | 801-080CF | 8    | 7-5/8   | 7-5/8   | 11-7/8   | 11-7/8   | 23-3/4  | 9-5/8    | 22.84              | 30.91  |
| 801-100     | 801-100C  | 10   | 5-3/4   | 5-3/4   | 10-13/16 | 10-13/16 | 21-5/8  | 11-19/32 | 37.89              | 40.50  |
| 801-100F    | 801-100CF | 10   | 9       | 9       | 14-1/4   | 14-1/4   | 28-1/2  | 11-15/16 | 39.82              | 51.41  |
| 801-120     | 801-120C  | 12   | 6-15/16 | 6-15/16 | 12-15/16 | 12-15/16 | 25-7/8  | 14-1/4   | 54.45              | 62.00  |
| 801-120F    | 801-120CF | 12   | 11-1/4  | 11-1/4  | 17-1/2   | 17-1/2   | 35      | 14-1/8   | 67.13              | 83.37  |
| 801-140F    | 801-140CF | 14   | 12-1/4  | 12-1/4  | 19-1/4   | 19-1/4   | 38-1/2  | 15-1/2   | 103.37             | 108.34 |
| 801-160F    | 801-160CF | 16   | 13      | 13      | 21       | 21       | 42      | 17-11/16 | 144.87             | 144.86 |
| 801-180F    | 801-180CF | 18   | 13-3/4  | 13-3/4  | 22-3/4   | 22-3/4   | 45-1/2  | 19-7/8   | 182.75             | 198.00 |
| 801-200F    | 801-200CF | 20   | 16-3/8  | 16-3/8  | 26-3/8   | 26-3/8   | 52-3/4  | 22-1/16  | 284.24             | 249.75 |
| 801-240F    | 801-240CF | 24   | 20-1/4  | 20-1/4  | 32-1/4   | 32-1/4   | 64-1/2  | 26-7/16  | 335.00             | 460.00 |

## REDUCING TEE

Socket x Socket x Socket



| Part Number          |                       | Size            | G     | G1      | G2    | H       | H1      | H2      | L       | M       | M1      | Approx. Wt. (Lbs.) |      |
|----------------------|-----------------------|-----------------|-------|---------|-------|---------|---------|---------|---------|---------|---------|--------------------|------|
| PVC                  | CPVC                  |                 |       |         |       |         |         |         |         |         |         | PVC                | CPVC |
| 801-101              | 801-101C              | 3/4x3/4x1/2     | 19/32 | 23/32   | 19/32 | 1-19/32 | 1-19/32 | 1-19/32 | 3-3/16  | 1-13/32 | 1-3/16  | .14                | .15  |
| 801-130              | 801-130C              | 1x1x1/2         | 19/32 | 7/8     | 19/32 | 1-23/32 | 1-3/4   | 1-23/32 | 3-7/16  | 1-3/4   | 1-3/16  | .20                | .21  |
| 801-131              | 801-131C              | 1x1x3/4         | 11/16 | 27/32   | 11/16 | 1-27/32 | 1-27/32 | 1-27/32 | 3-21/32 | 1-3/4   | 1-13/32 | .23                | .24  |
| 801-157              | ---                   | 1-1/4x1x3/4     | 11/16 | 1-1/16  | 5/8   | 1-15/16 | 2-1/16  | 1-7/8   | 3-13/16 | 2-1/8   | 1-7/16  | .30                | ---  |
| 801-158              | 801-158C              | 1-1/4x1x1       | 13/32 | 15/16   | 13/32 | 2-1/8   | 1-31/32 | 1-15/16 | 4       | 2-1/16  | 1-11/16 | .33                | .34  |
| 801-159              | 801-159C              | 1-1/4x1x1-1/4   | 15/16 | 1-1/32  | 7/8   | 2-3/16  | 2-5/32  | 2-1/8   | 4-5/16  | 2-1/16  | 2-1/16  | .39                | .41  |
| 801-166 <sup>1</sup> | 801-166C <sup>1</sup> | 1-1/4x1-1/4x1/2 | 7/8   | 1-13/32 | 7/8   | 2-3/32  | 2-3/8   | 2-3/32  | 4-7/32  | 2-1/8   | 1-3/4   | .42                | .43  |
| 801-167              | 801-167C              | 1-1/4x1-1/4x3/4 | 5/8   | 31/32   | 5/8   | 1-15/16 | 1-31/32 | 1-15/16 | 3-7/8   | 2-1/8   | 1-13/32 | .28                | .30  |
| 801-168              | 801-168C              | 1-1/4x1-1/4x1   | 27/32 | 1-1/32  | 27/32 | 2-3/32  | 2-5/32  | 2-3/32  | 4-7/32  | 2-3/32  | 1-3/4   | .34                | .36  |

<sup>1</sup> Outlet sized with bushing