

A light, sporty, comfortable low-cut occupational shoe featuring convenient side-mounted BOA® Fit System.

jalas® SPOC 5362

ASTM F2892-18 SD 35 ASTM F3445-21 SR EN ISO 20347:2012 01, A, E, FO, SRC

Learn more

A light, sporty, comfortable low-cut safety shoe featuring side-mounted BOA® Fit System for convenience. A ventilated textile upper gives strong yet flexible support for feet and keeps them cool when the heat is on. An oil-resistant nitrile outer sole provides excellent grip in slippery conditions, and JALAS® double impact protection zones in PORON® XRD® keeps feet safe all day long.

CHARACTERISTICS

- Excellent grip
- Perfect fit
- Extra comfortable
- Breathable
- Excellent shock absorption
- Light

FUNCTIONS

- Breathable mesh
- Low weight
- Oil-resistant outsole
- Anti-static properties
- BOA® Fit System
- Double shock absorption zones
- Conforms with IEC 61340-5-1 (ESD)

BOA DIALED IN. PRECISION FIT.

xrd PROTECTION

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

PREVENTS RISK OF

Prevents risk of: , Sprain injuries, Antistatic, Slipping, Strain injuries

PRIMARY ENVIRONMENTS OF USE

Outdoors, Indoors, Office environments, Slippery environments

PRIMARY AREAS OF USE

Cleaning, Hotel- and restaurant work, Healthcare, Care work, Service work, Office work, Shop work

PRIMARY INDUSTRIES OF USE

Accommodation and food service (HoReCa), Facility management services, Public safety, security and defence, Retail and wholesale

SPECIFICATION

TYPE Occupational footwear, Low shoes
CATEGORY Cat. II
FITTING Regular
COLLECTION SpOc
UPPER MATERIAL Textile
LINING MATERIAL Polyester
INSOLE JALAS FX2 Pro SpOc
INNERSOLE MATERIAL Textile, Soft EVA, Polyester-based conductive thread, Double shock absorption zones in PORON® XRD®
MIDSOLE MATERIAL EVA
OUTSOLE MATERIAL Nitrile rubber outsole
FASTENING BOA® Fit System
COLOUR Black
NET WEIGHT, (SIZE 42) 0.73 kg

COMPLIANCE

CE Cat. II

EAC TP TC 017:2011

ASTM F2892-18
SD 35

ASTM F3445-21
SR

EN ISO 20347:2012
01, A, E, FO, SRC

FEATURES

Anti-static properties

Ergothan Shock Absorption System

ESD

Oil-resistant outsole

SIZE				ARTICLE NUMBER	EAN
EU	UK	US M	US W		
35	2	3.5	4	5362-35	6408487510465
36	3	4	5	5362-36	6408487510472
37	4	5	6	5362-37	6408487510489
38	5	5.5	6.5	5362-38	6408487510496
39	6	6.5	7.5	5362-39	6408487510502
40	6.5	7.5	8.5	5362-40	6408487510519
41	7	8	9	5362-41	6408487510526
42	8	9	10	5362-42	6408487510533
43	9	9.5	11	5362-43	6408487510540
44	10	10.5	11.5	5362-44	6408487510557
45	10.5	11	12.5	5362-45	6408487510564
46	11	12	13	5362-46	6408487510571
47	12	13	14	5362-47	6408487510588
48	13	13.5	14.5	5362-48	6408487510595

ejendals
Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.