



# Tork Industrial Cleaning Cloth

520374

Think ahead.



## Description

- Its strong texture and high absorbency makes it ideal for removing oil, grease, lubricants and dirt
- Meets your cleaning needs due to suitability with most solvents, disinfectants, and detergents

## Product Certifications



Health  
Canada

## Product Details

Print	No
Folded length	4.3 in
Unfolded Width	14 in
Folded width	14 in
Unfolded length	16.3 in
Ply	1
Embossing	No
System	W7
Color	Grey

## Shipping Data

	Consumer Units (CON)	Transport unit (TRP)	Pallet (PAL)
EAN	73286662316	73286662316	7322541414805
Packaging Material	Box	Carton	-
Pieces	210	210 (1 CON)	27300 (130 TRP)
Height	8.27 in	8.27 in	82.68 in
Length	9.37 in	14.72 in	46.85 in
Width	14.72 in	9.37 in	38.82 in
Gross Weight	5 lb	5 lb	650.01 lb
Net Weight	4.43 lb	4.43 lb	576.35 lb
Volume	0.66 ft	0.66 ft	87.02 ft
Layers Per Pallet	-	-	10
TRP Per Layer	-	-	13



Think ahead.

# Tork Industrial Cleaning Cloth

520374

## Environmental Information

<b>Raw materials</b>	Cellulose pulp Polyester Polypropylene Functional agents or additives
<b>Cellulose Pulp</b>	Cellulose pulp is produced either from softwood or hardwood coming from responsibly managed forests. The wood chips are boiled together with chemicals to remove the lignin between the fibers. The pulp is TCF (Totally Chlorine Free) or ECF (Elementary Chlorine Free) bleached in order to achieve a clean, bright and strong product, but also to increase the hygienic and absorbent qualities.
<b>Polyester</b>	Polyester fiber is produced from terephthalic acid and ethylene glycol, which react through condensation to polyester resin. The molten resin is spun to fibers through spinnerets and cooled with air. The fibers are then cut to intended fiber length.
<b>Polypropylene</b>	Polypropylene or polypropene is a thermoplastic polymer made from oil. The moten resin is spun to endless fibers through spinnerets and cooled by air. The fibers form a web.
<b>Functional agents and additives</b>	Functional additives could be wet strength agent, antistatic agent and wetting additives /tensides.
<b>Environmental certification</b>	This product is certified for FSC®.
<b>Packaging</b>	Fulfilment of Packaging and Packaging Waste Directive (94/62/EC): Yes
<b>Article creation date and latest article revision</b>	Date of issue: 20-07-2021 Revision date: 03-07-2025
<b>Production</b>	This product is produced at Suameer - NL mill.
<b>Disposal/destruction of used product</b>	This product is mainly used for industrial processes. When used in industrial processes the product might through use be contaminated with different substances. This will determine how the used product will be handled/disposed of/destroyed. The product itself is suitable for incineration. If used in industrial processes contact local authorities before destruction.

**Essity North America Inc., Cira Centre, Suite 2600 2929 Arch Street, Philadelphia, PA 19104, USA**