



22260, 22261, 22262, 22268, 22269 Special Tec B FE 0W-30

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)
Issue date: 11/16/2022 Revision date: 5/4/2026 Version: 2.0

SECTION 1 Identification

1.1. Product identifier

Product form : Mixture
Trade name : 22260, 22261, 22262, 22268, 22269 Special Tec B FE 0W-30

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Intended for general public
Recommended use : Engine oil
Restrictions on use : None known

1.4. Supplier's details

Supplier

Liqui Moly GmbH
Jerg-Wieland-Strasse 4 Ulm D-89081 Germany
T +49 731 1420 0
info@liqui-moly.de - www.liqui-moly.us

Distributor

LIQUI MOLY USA Inc.
62-64 Enter Lane
Islandia, New York 11749
USA
T (888)665-9645

1.5. Emergency phone number

Emergency number : INFOTRAC
+1800 535 5053 (USA, Canada); +1352 323 3500 (International)

SECTION 2 Hazard Identification

2.1. Classification of the substance or mixture

GHS US classification

Reproductive toxicity, Category 2	H361	Suspected of damaging fertility.
Specific target organ toxicity — Repeated exposure, Category 2	H373	May cause damage to organs (liver) through prolonged or repeated exposure.

Full text of H statements : see section 16

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US)



Signal word (GHS US) : Warning
Hazard statements (GHS US) : H361 - Suspected of damaging fertility.
H373 - May cause damage to organs (liver) through prolonged or repeated exposure
Precautionary statements (GHS US) : P101 - If medical advice is needed, have product container or label at hand.
P102 - Keep out of reach of children.
P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.

22260, 22261, 22262, 22268, 22269 Special Tec B FE 0W-30

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

P260 - Do not breathe mist.
P280 - Wear protective gloves.
P308+P313 - If exposed or concerned: Get medical advice/attention.
P314 - Get medical advice or attention if you feel unwell.
P405 - Store locked up.
P501 - Dispose of contents and/or container to an approved waste disposal plant.

2.3. Hazards associated with known or reasonably anticipated uses

None known

2.4. Hazards not otherwise classified

Other hazards which do not result in classification : None known.

2.5. Unknown acute toxicity

No additional information available

SECTION 3 Composition/information on ingredients

Mixtures

Name	Product identifier	Conc. (% w/w)
Distillates (petroleum), hydrotreated heavy paraffinic	CAS-No.: 64742-54-7	30 – 60
Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated	CAS-No.: 68037-01-4	15-40
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	CAS-No.: 72623-86-0	5 – 10
Lubricating Oils (petroleum), C20-50, hydrotreated neutral oil-based	CAS-No.: 72623-87-1	5 – 10
Phenol, 2 or 4-C14-18 (even numbered) sec-alkyl derivs.	CAS-No.: 701-556-3**	1 – 5
Distillates (petroleum), hydrotreated light paraffinic	CAS-No.: 64742-55-8	1 – 5
Distillates (petroleum), solvent-dewaxed light paraffinic	CAS-No.: 64742-56-9	1 – 5
Distillates (petroleum), solvent - dewaxed heavy paraffinic	CAS-No.: 64742-65-0	1 – 5
Reaction products of diphenylamine with nonene, branched	CAS-No.: 701-385-4**	0.5-1.5
Zinc bis(OO-diisooctyl) bis(dithiophosphate)	CAS-No.: 28629-66-5	1 – 5

Comments : ** Unique identifier is an EC List Number

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

SECTION 4 First aid measures

4.1. Description of necessary first-aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Wash skin with mild soap and water.
First-aid measures after eye contact : Rinse eyes with water as a precaution. Get medical attention if irritation develops and persists.
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms/effects, acute and delayed

Inhalation : Inhalation of mists or vapors at elevated temperatures may cause respiratory irritation.
Skin : Repeated or prolonged skin contact may cause dermatitis and defatting.

22260, 22261, 22262, 22268, 22269 Special Tec B FE 0W-30

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

Eyes	: May cause minor eye irritation.
Ingestion	: Abdominal pain. Diarrhoea.
Chronic symptoms	: Suspected of damaging fertility. May cause damage to organs (liver) through prolonged or repeated exposure.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Use of heavy stream of water may spread fire.

5.2. Specific hazards arising from the chemical

Fire hazard	: This product is not classified as flammable or combustible.
Hazardous decomposition products in case of fire	: Toxic fumes may be released. Carbon oxides (CO, CO ₂). Fire will produce dense black smoke.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Cool down the containers exposed to heat with a water spray.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Emergency procedures	: Ventilate spillage area.
----------------------	----------------------------

For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

Environmental precautions	: Avoid release to the environment.
---------------------------	-------------------------------------

6.2. Methods and materials for containment and cleaning up

For containment	: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
Methods for cleaning up	: Absorb and/or contain spill with inert material, then place in suitable container.
Other information	: Dispose of materials or solid residues at an authorized site.

For further information refer to section 13.

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Ensure good ventilation of the work station. Wear personal protective equipment. Avoid contact with eyes. Avoid repeated or prolonged skin contact.
Hygiene measures	: Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

22260, 22261, 22262, 22268, 22269 Special Tec B FE 0W-30

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

7.2. Conditions for safe storage, including incompatibilities

Storage conditions	: Store in a well-ventilated place. Keep cool.
Incompatible materials	: Strong oxidizers.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
USA - ACGIH® - Threshold Limit Values	
Local name	Mineral oil, excluding metal working fluids Pure, highly and severely refined
ACGIH® TLV® TWA	5 mg/m³ (I - Inhalable particulate matter)
Remark (ACGIH®)	TLV® Basis: URT irr. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2024
USA - OSHA - Occupational Exposure Limits	
Local name	Oil mist, mineral
OSHA PEL (TWA)	5 mg/m³
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)	
USA - ACGIH® - Threshold Limit Values	
ACGIH® TLV® TWA	5 mg/m³ inhalable
USA - OSHA - Occupational Exposure Limits	
OSHA PEL (TWA)	5 mg/m³
Lubricating Oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)	
USA - ACGIH® - Threshold Limit Values	
ACGIH® TLV® TWA	5 mg/m³ inhalable
USA - OSHA - Occupational Exposure Limits	
OSHA PEL (TWA)	5 mg/m³
Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)	
USA - ACGIH® - Threshold Limit Values	
ACGIH® TLV® TWA	5 mg/m³ inhalable
USA - OSHA - Occupational Exposure Limits	
OSHA PEL (TWA)	5 mg/m³
Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)	
USA - ACGIH® - Threshold Limit Values	
ACGIH® TLV® TWA	5 mg/m³ inhalable
USA - OSHA - Occupational Exposure Limits	
OSHA PEL (TWA)	5 mg/m³

22260, 22261, 22262, 22268, 22269 Special Tec B FE 0W-30

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

Distillates (petroleum), solvent - dewaxed heavy paraffinic (64742-65-0)

USA - ACGIH® - Threshold Limit Values

Local name	Mineral oil, excluding metal working fluids Pure, highly and severely refined
ACGIH® TLV® TWA	5 mg/m³ (I - Inhalable particulate matter)
Remark (ACGIH®)	TLV® Basis: URT irr. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2024

USA - OSHA - Occupational Exposure Limits

Local name	Oil mist, mineral
OSHA PEL (TWA)	5 mg/m³
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Environmental exposure controls	: Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment

Hand protection:

In case of repeated or prolonged contact wear gloves. Consult supplier for specific recommendations.

Eye protection:

Not required for normal conditions of use

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In operations where exposure limits are exceeded or exposure levels are excessive, an approved respirator should be used. Respirator selection and use should be based on contaminant type, form and concentration. Follow applicable regulations and good Industrial Hygiene practice.

SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Color	: Brown
Odor	: Characteristic
Odor threshold	: No data available
pH	: No data available
Melting point	: -45 °C
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 220 °C (428F)
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: 0.845
Solubility	: Insoluble in water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available

22260, 22261, 22262, 22268, 22269 Special Tec B FE 0W-30

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

Decomposition temperature	: No data available
Viscosity, kinematic	: 51 mm ² /s @40C
Explosion limits	: No data available
Explosive properties	: None.
Oxidizing properties	: None.
Particle characteristics	: Particle characteristics : Not applicable

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10 Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

Strong oxidizers. Strong acids. Strong bases.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11 Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	> 2000 mg/kg body weight
LD50 dermal rabbit	> 5000 mg/kg Source: IUCLID
LC50 Inhalation - Rat	> 5000 mg/m ³
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)	
LD50 oral rat	> 5000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method)
Lubricating Oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)	
LD50 oral rat	5000 mg/kg body weight
LD50 dermal rat	> 2000 mg/kg body weight

22260, 22261, 22262, 22268, 22269 Special Tec B FE 0W-30

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

Lubricating Oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)	
LC50 Inhalation - Rat	> 5 mg/l/4h
Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated (68037-01-4)	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rat	> 2000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)	
LD50 oral rat	> 5000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method)
LD50 dermal rabbit	> 2000 mg/kg Source: IUCLID
Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)	
LD50 oral rat	> 5000 mg/kg body weight OECD 401
LD50 dermal rabbit	> 2000 mg/kg Source: EHCA
LC50 Inhalation - Rat (Dust/Mist)	> 2.18 mg/l Source: ECHA
Distillates (petroleum), solvent - dewaxed heavy paraffinic (64742-65-0)	
LD50 oral rat	> 5000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method)
Zinc bis(OO-diisooctyl) bis(dithiophosphate) (28629-66-5)	
LD50 oral rat	≈ 3200 mg/kg body weight Animal: rat, Animal sex: male, Guideline: other., 95% CL: 2000 - 5300
LD50 dermal rabbit	> 5000 mg/kg body weight Animal: rabbit, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
Phenol, 2 or 4-C14-18 (even numbered) sec-alkyl derivs. (701-556-3**)	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rat	> 2000 mg/kg
Reaction products of diphenylamine with nonene, branched (701-385-4**)	
LD50 oral rat	> 5000 mg/kg
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified.
Respiratory or skin sensitization	: Skin sensitization: Not classified.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Suspected of damaging fertility.
STOT-single exposure	: Not classified
STOT-repeated exposure	: May cause damage to organs (liver) through prolonged or repeated exposure.
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LOAEL (oral,rat,90 days)	125 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)	
LOAEL (oral,rat,90 days)	125 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

22260, 22261, 22262, 22268, 22269 Special Tec B FE 0W-30

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

Lubricating Oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)	
LOAEL (oral,rat,90 days)	125 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)	
LOAEL (oral,rat,90 days)	125 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
NOAEC (inhalation,rat,dust/mist/fume,90 days)	> 0.98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)
Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)	
LOAEL (oral,rat,90 days)	125 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Distillates (petroleum), solvent - dewaxed heavy paraffinic (64742-65-0)	
LOAEL (oral,rat,90 days)	125 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
NOAEL (dermal,rat/rabbit,90 days)	≈ 1000 mg/kg body weight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
Phenol, 2 or 4-C14-18 (even numbered) sec-alkyl derivs. (701-556-3**)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified

22260, 22261, 22262, 22268, 22269 Special Tec B FE 0W-30	
Viscosity, kinematic	51 mm²/s @40C
Inhalation	: Inhalation of mists or vapors at elevated temperatures may cause respiratory irritation.
Skin	: Repeated or prolonged skin contact may cause dermatitis and defatting.
Eyes	: May cause minor eye irritation.
Ingestion	: Abdominal pain. Diarrhoea.
Chronic symptoms	: Suspected of damaging fertility. May cause damage to organs (liver) through prolonged or repeated exposure.

SECTION 12 Ecological information

12.1. Ecotoxicity

Ecology - general	: The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment. An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LC50 - Fish [1]	≥ 100 mg/l
EC50 - Crustacea [1]	> 10 g/l
EC50 96h - Algae [1]	> 1000 mg/l Source: IUCLID
Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated (68037-01-4)	
LC50 - Fish [1]	> 1000 mg/l

22260, 22261, 22262, 22268, 22269 Special Tec B FE 0W-30

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated (68037-01-4)	
EC50 - Crustacea [1]	> 1000 mg/l
EC50 72h - Algae [1]	> 1000 mg/l
Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)	
LC50 - Fish [1]	> 5000 mg/l Source: IUCLID
EC50 - Crustacea [1]	> 1000 mg/l Source: IUCLID
Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)	
LC50 - Fish [1]	> 100 mg/l
EC50 - Crustacea [1]	> 10000
ErC50 algae	> 100 mg/l
NOEC chronic crustacea	10 mg/l
Zinc bis(OO-diisooctyl) bis(dithiophosphate) (28629-66-5)	
LC50 - Fish [1]	46 mg/l Test organisms (species): Cyprinodon variegatus
LC50 - Fish [2]	3.6 mg/kg Oncorhynchus mykiss (Rainbow trout)
Phenol, 2 or 4-C14-18 (even numbered) sec-alkyl derivs. (701-556-3**)	
LC50 - Fish [1]	> 100 mg/l
EC50 - Crustacea [1]	> 100 mg/l
ErC50 algae	> 100 mg/l
12.2. Persistence and degradability	
22260, 22261, 22262, 22268, 22269 Special Tec B FE 0W-30	
Persistence and degradability	No additional information available.
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Persistence and degradability	Inherently biodegradable.
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)	
Persistence and degradability	Rapidly degradable
Lubricating Oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)	
Persistence and degradability	Rapidly degradable
Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated (68037-01-4)	
Persistence and degradability	Not rapidly degradable
Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)	
Persistence and degradability	Not rapidly degradable
Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)	
Persistence and degradability	Not rapidly degradable
Distillates (petroleum), solvent - dewaxed heavy paraffinic (64742-65-0)	
Persistence and degradability	Inherently biodegradable.

22260, 22261, 22262, 22268, 22269 Special Tec B FE 0W-30

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

Zinc bis(OO-diisooctyl) bis(dithiophosphate) (28629-66-5)	
Persistence and degradability	Not readily biodegradable.
Phenol, 2 or 4-C14-18 (even numbered) sec-alkyl derivs. (701-556-3**)	
Persistence and degradability	Not readily biodegradable.
Reaction products of diphenylamine with nonene, branched (701-385-4**)	
Persistence and degradability	No additional information available.

12.3. Bioaccumulative potential

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Partition coefficient n-octanol/water (Log Pow)	3.9 – 6 Source: IUCLID
Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated (68037-01-4)	
Partition coefficient n-octanol/water (Log Pow)	> 6.5
Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)	
Partition coefficient n-octanol/water (Log Pow)	3.9 – 6 Source: IUCLID
Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)	
Partition coefficient n-octanol/water (Log Pow)	3.9 – 6 Source: IUCLID

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Ozone	: Not classified
Fluorinated greenhouse gases	: No

SECTION 13 Disposal considerations

Waste treatment methods : Dispose in a safe manner in accordance with local/national regulations.

SECTION 14 Transport information

In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG	IATA
14.1. UN number			
Not regulated for transport			
14.2. Proper Shipping Name			
Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)			
Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group			
Not regulated	Not regulated	Not regulated	Not regulated

22260, 22261, 22262, 22268, 22269 Special Tec B FE 0W-30

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

DOT	TDG	IMDG	IATA
14.5. Environmental hazards			
Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available			

14.6. Transport in bulk

Not applicable

14.7. Special precautions for user

DOT
Not regulated

TDG
Not regulated

IMDG
Not regulated

IATA
Not regulated

SECTION 15 Regulatory information

15.1. Federal regulations

22260, 22261, 22262, 22268, 22269 Special Tec B FE 0W-30	
SARA Section 311/312 Hazard Classes	Refer to Section 2 for OSHA Hazard Classification.

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.		
Zinc Compounds	CAS-No.	1 – 2%

15.2. International regulations

CANADA

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)
Listed on the Canadian DSL (Domestic Substances List)

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)
Listed on the Canadian DSL (Domestic Substances List)

Lubricating Oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)
Listed on the Canadian DSL (Domestic Substances List)

22260, 22261, 22262, 22268, 22269 Special Tec B FE 0W-30

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated (68037-01-4)

Listed on the Canadian DSL (Domestic Substances List)

Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)

Listed on the Canadian DSL (Domestic Substances List)

Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)

Listed on the Canadian DSL (Domestic Substances List)

Distillates (petroleum), solvent - dewaxed heavy paraffinic (64742-65-0)

Listed on the Canadian DSL (Domestic Substances List)

Zinc bis(OO-diisooctyl) bis(dithiophosphate) (28629-66-5)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

22260, 22261, 22262, 22268, 22269 Special Tec B FE 0W-30

Listed on the Canadian DSL (Domestic Substances List)

Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated (68037-01-4)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16 Other information

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

Revision date : 5/4/2026

Issue date : 11/16/2022

Data sources : This safety data sheet was compiled with data and information from the following sources :
ECHA, ECOSAR, HSDB, SIDS SIAP, CESAR, Chemical DB.


Full text of hazard classes and H-statements

H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure

NFPA health hazard : 0 - Materials that, under emergency conditions, would offer no hazard beyond that of ordinary combustible materials.

NFPA fire hazard : 1 - Materials that must be preheated before ignition can occur.

NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



22260, 22261, 22262, 22268, 22269 Special Tec B FE 0W-30

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.