•TRUSTED QUALITY SINCE
RUST-OLEUM®

CLEANER & DEGREASER
FOR CONCRETE



WARNING! EYE AND SKIN IRRITANT
See other cautions on back panel

1 Gallon (128 Fl. Oz./3.78L)

•TRUSTED QUALITY SINCE 1921•
RUST-OLEUM®

CLEANER & DEGREASER
FOR CONCRETE



WARNING! EYE AND SKIN IRRITANT
See other cautions on back panel

1 Gallon (128 Fl. Oz./3.78L)

•TRUSTED QUALITY SINCE 1921•
RUST-OLEUM®

RUST-OLEUM® CLEANER & DEGREASER is formulated to break down oil, grease stains, tire marks, dirt, harmful silicates and more to properly clean and prepare surface for coatings, epoxies, paints, stains and sealants. **Thoroughly cleaning the entire surface, spot treating heavy stains and removing contaminants is an essential step to ensuring adhesion.** Diluted Cleaner & Degreaser can be used to clean the coated surface and is suitable for interior and exterior use.

READ ALL INSTRUCTIONS CAREFULLY BEFORE STARTING PROJECT

WHERE TO USE: Ideal for use on bare or coated concrete: garage floors, basements, driveways, carports, patios, walkways, and pool decks.

SURFACE PREPARATION: Wear protective clothing and eyewear when applying product. Wipe up excess oil and grease spills. Scrape and sweep away dirt and loose contaminants on the surface. Newly poured concrete must cure for a minimum of 30 days prior to cleaning or coating.

COVERAGE: Up to 150 - 200 Sq. Ft.

MIXING INSTRUCTIONS: Dilute **RUST-OLEUM® CLEANER & DEGREASER** according to application listed in table below.

DILUTION TABLE	
Tough Stains (bare concrete)	Full strength
Coating Prep/General Purpose	1:1 [1 gal. (128 oz.) degreaser in 1 gal. (128 oz.) of water]
Painted/Sealed Surfaces	1:10 [1 cup (8 oz.) degreaser and 10 cups (80 oz.) water]

APPLICATION: Use only when air (ambient) temperature is 50-90°F (10-32°C) and relative humidity is below 85%.

1. Dilute according to the dilution table above. Pour mixture onto the entire floor. Allow to soak into the surface for 20 minutes (longer soak times may be necessary for removal of curing compounds). Mist the surface as needed to keep it damp.
2. Work into the surface with a stiff bristle broom.
3. After scrubbing the floor, rinse thoroughly with water or power wash to remove all cleaner residue. NOTE: If cleaner dries before rinsing, apply more cleaner, scrub and rinse.
4. Squeegee or broom excess moisture from the surface.
5. Re-application may be necessary for extremely dirty, stained floors, or hard to remove stains. Always test in an inconspicuous area prior to using on entire floor.

DRY TIME: Allow to dry for at least 24 hours before staining, sealing or coating.

CLEAN UP: Wash tools and equipment with soap and warm water. Properly dispose of all soiled rags and protect unused product from freezing.

SAFETY INFORMATION: Before opening the package, read all warning labels and data sheets. Follow all precautions.

WARNING! CONTAINS GLYCOL ETHERS. Do not take internally. Harmful if inhaled or ingested. Causes eye, skin, nose and throat irritation. May cause respiratory irritation, asthma or breathing difficulties if inhaled. **Use only with adequate ventilation.** Do not breathe dust, vapors or spray mist. Ensure fresh air entry during application and drying. Avoid contact with skin and eyes. Wear safety glasses and protective gloves. Close container after each use. Wash thoroughly after handling.

KEEP OUT OF REACH OF CHILDREN AND ANIMALS

FIRST AID:

EYE CONTACT: In case of eye contact, flush immediately with plenty of water for at least 20 minutes and get medical attention.

SKIN CONTACT: In case of skin contact, wash thoroughly with soap and water. Consult a physician if rash or persistent irritation occurs. Clean any contaminated clothing before re-use.

INHALATION: If affected by inhalation of vapor or spray, move to fresh air. If breathing difficulty persists or occurs later, consult a physician and have label information available.

INGESTIONS: If swallowed, rinse out mouth and drink water. Get medical attention immediately. Do not induce vomiting.

EMERGENCY TELEPHONE: 1-800-424-9300

SATISFACTION GUARANTEED: If you are dissatisfied with this product, contact Rust-Oleum Product Support at 888-683-5667 for a product replacement or full refund of the purchase price. Refer to product number and UPC code on the label.

RUST-OLEUM CORPORATION
11 Hawthorn Pkwy., Vernon Hills, IL 60061
888-683-5667 rustoleum.com/garage
Made in USA
©2022 Rust-Oleum Corporation 372450 0322

301243
CLEANER & DEGREASER
0 20066 32252 6