



Scratch Fix®

Safety Data Sheet

according to US OSHA HazCom 2024

Issue date: 18 February 2025 Revision date: 18 February 2025 Version: 1.0

SECTION 1 Identification

1.1. Product identifier

Product form : Article
Trade name : Scratch Fix®
Product code : 10611U Light Brown SF1201, 10612U Dark Brown SF1202, 10613U Black Brown SF1203, 10614U Red Brown SF1204, 10615U Medium Brown SF1205

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Wood Stain Pen

1.4. Supplier's details

Supplier
U-Mark Inc.
102 Iowa Ave.
Belleville, IL
62220, USA
T: 618-235-7500; 866-383-6275
compliance@umarkers.com

1.5. Emergency phone number

Emergency number : 24-hour Emergency Phone: Infotrac 1-800-535-5053 (USA & Canada), 1-352-323-3500 (International)

SECTION 2 Hazard Identification

This SDS has been prepared detailing the hazards of the ink. This product is considered in an article per OSHA Haz Com 29 CFR 1910.1200 and the ink is hermetically sealed within the pen. Therefore, exposure to the ink is not anticipated under normal and typical conditions of use. **The classification identified and labelling elements identified are for the ink itself not the final hermetically sealed pen.**

2.1. Classification of the substance or mixture

GHS US classification according to US OSHA HazCom 2024

Flammable liquid, Category 2
Serious eye damage/eye irritation, Category 2A
Skin sensitization, Category 1
Specific target organ toxicity – Single exposure, Category 3, Narcosis

Highly flammable liquid and vapor.
Causes serious eye irritation.
May cause an allergic skin reaction.
May cause drowsiness or dizziness.

2.2. Label elements

This SDS has been prepared detailing the hazards of the ink. This product is considered in an article per OSHA Haz Com 29 CFR 1910.1200 and the ink is hermetically sealed within the pen. **Therefore, these label elements are not relevant for the final hermetically sealed pen; consumer product labeling would be applicable.**

GHS US labeling according to US OSHA HazCom 2024 (for bulk liquid only, the marking pen is an article and does not require GHS labeling.)

Hazard pictograms (GHS US) :



Scratch Fix®

Safety Data Sheet

according to US OSHA HazCom 2024

Signal word (GHS US)	: Danger
Hazard statements (GHS US)	: Highly flammable liquid and vapor May cause an allergic skin reaction Causes serious eye irritation May cause drowsiness or dizziness
Precautionary statements (GHS US)	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Avoid breathing vapors. Wash hands thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Call a doctor if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. In case of fire: Use media other than water to extinguish. Store in a well-ventilated place. Keep cool. Dispose of contents/container to comply with applicable regulations.

2.3. Hazards associated with known or reasonably anticipated uses

This SDS has been prepared detailing the hazards of the ink. This product is considered in an article per OSHA Haz Com 29 CFR 1910.1200 and the ink is hermetically sealed within the pen. Therefore, exposure to the ink is not anticipated under normal and typical conditions of use.

2.4. Hazards not otherwise classified

Other hazards which do not result in classification : Toxic to aquatic life with long lasting effects.

2.5. Unknown acute toxicity

No additional information available

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Ethyl alcohol	CAS-No.: 64-17-5	55 – 100	Flam. Liq. 2, H225 Eye Irrit. 2A, H319
Propanol, 1(or 2)-ethoxy-	CAS-No.: 52125-53-8	0 – 10	Flam. Liq. 3, H226 STOT SE 3, H335
1-Ethoxy-2-propanol	CAS-No.: 1569-02-4	0 – 10	Flam. Liq. 3, H226 STOT SE 3, H336
1-methoxy-2-propanol, monopropylene glycol methyl ether	CAS-No.: 107-98-2	0.1 – 10	Flam. Liq. 3, H226 STOT SE 3, H336
Cobaltate(4-), bis[2-[[[3-[[[1-[(2-chlorophenyl)amino]carbonyl]-2-oxopropyl]azo]-4-hydroxyphenyl]sulfonyl]amino]benzoato(3-)]-], tetrasodium	CAS-No.: 70851-34-2	0 – 10	Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Scratch Fix®

Safety Data Sheet

according to US OSHA HazCom 2024

Name	Product identifier	%	GHS US classification
propan-2-ol, isopropyl alcohol, isopropanol	CAS-No.: 67-63-0	2.5 – 10	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

SECTION 4 First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general	: This SDS has been prepared detailing the hazards of the ink. This product is considered in an article and the ink is hermetically sealed within the pen. Therefore, exposure to the ink is not anticipated under normal and typical conditions of use. Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep at rest in a position comfortable for breathing. Obtain medical attention if breathing difficulty persists.
First-aid measures after skin contact	: Remove immediately contaminated clothing. Wash off immediately and plentifully with water for at least 20 minutes. Seek medical advice (show the label where possible).
First-aid measures after eye contact	: In case of contact, immediately rinse eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Do NOT induce vomiting. Rinse mouth. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Eye irritation.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Note to physician :	: Treat symptomatically.
---------------------	--------------------------

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Carbon dioxide. Alcohol resistant foam. dry extinguishing powder.
Unsuitable extinguishing media	: None known. Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	: Highly flammable liquid and vapor. On combustion, forms: carbon oxides (CO and CO ₂).
Explosion hazard	: May form flammable/explosive vapor-air mixture.
Hazardous decomposition products in case of fire	: Toxic fumes may be released. Thermal decomposition can lead to the release of irritating gases and vapors.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

Scratch Fix®

Safety Data Sheet

according to US OSHA HazCom 2024

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : No open flames, no sparks, and no smoking. Avoid contact with skin and eyes.

For non-emergency personnel

Protective equipment : Large amounts: Wear personal protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

For emergency responders

Protective equipment : Large amounts: Wear personal protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. No open flames, no sparks, and no smoking. Stop leak if safe to do so.

Environmental precautions : Avoid release to the environment.

6.2. Methods and materials for containment and cleaning up

For containment : Collect spillage. Soak up with inert absorbent material (for example sand, sawdust, a universal binder, silica gel).

Methods for cleaning up : Stop leak if safe to do so. Collect spillage. Wipe up with absorbent material (for example cloth). Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Other information : Dispose of materials or solid residues at an authorized site.

For further information refer to section 8: "Exposure controls/personal protection", For disposal of residues refer to section 13 : "Disposal considerations"

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure adequate ventilation. Wear personal protective equipment. Avoid breathing vapors, mist. Avoid contact with skin and eyes. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Flammable vapors may accumulate in the container.

Hygiene measures : Use good personal hygiene practices. Always wash hands after handling the product. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Separate working clothes from town clothes. Launder separately.

7.2. Conditions for safe storage, including incompatibilities

Technical measures : Avoid ignition sources.

Storage conditions : Follow label instructions. Store in a dry, cool and well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Incompatible materials : Strong oxidizing agents.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

Scratch Fix®

Safety Data Sheet

according to US OSHA HazCom 2024

Ethyl alcohol (64-17-5)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH® TLV® STEL	1880 mg/m³
ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans
USA - IDLH - Occupational Exposure Limits	
IDLH	3300 ppm (10% LEL)
USA - NIOSH - Occupational Exposure Limits	
Local name	Ethyl alcohol (Ethanol)
NIOSH REL TWA	1900 mg/m³
	1000 ppm
NIOSH REL 10h TWA	1000 ppm
Regulatory reference (US-NIOSH)	OSHA Annotated Table Z-1 (NIOSH Pocket Guide to Chemical Hazards (NPG))
Propanol, 1(or 2)-(2-methoxymethylethoxy)- (34590-94-8)	
USA - OSHA - Occupational Exposure Limits	
Local name	Dipropylene glycol methyl ether
OSHA PEL TWA	600 mg/m³
	100 ppm
Limit value category (OSHA)	prevent or reduce skin absorption
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - IDLH - Occupational Exposure Limits	
IDLH	600 ppm
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL TWA	600 mg/m³
	100 ppm
NIOSH REL STEL	900 mg/m³
	150 ppm
US-NIOSH chemical category	Potential for dermal absorption
1-Ethoxy-2-propanol (1569-02-4)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH® TLV® TWA	50 ppm
ACGIH® TLV® STEL	200 ppm
ACGIH chemical category	Skin - potential significant contribution to overall exposure by the cutaneous route
1-methoxy-2-propanol, monopropylene glycol methyl ether (107-98-2)	
USA - ACGIH - Occupational Exposure Limits	
Local name	1-Methoxy-2-propanol
ACGIH® TLV® TWA	184 mg/m³
	50 ppm
ACGIH® TLV® STEL	369 mg/m³

Scratch Fix®

Safety Data Sheet

according to US OSHA HazCom 2024

1-methoxy-2-propanol, monopropylene glycol methyl ether (107-98-2)	
	100 ppm
Remark (ACGIH)	TLV® Basis: Eye & URT irr. Notations: A4 (Not classifiable as a Human Carcinogen)
ACGIH chemical category	Not Classifiable as a Human Carcinogen
Regulatory reference	ACGIH 2025
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL TWA	360 mg/m³
	100 ppm
NIOSH REL STEL	540 mg/m³
	150 ppm
propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)	
USA - ACGIH - Occupational Exposure Limits	
Local name	2-Propanol
ACGIH® TLV® TWA	491 mg/m³
	200 ppm
ACGIH® TLV® STEL	984 mg/m³
	400 ppm
Remark (ACGIH)	TLV® Basis: Eye & URT irr; CNS repair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2025
USA - ACGIH - Biological Exposure Indices	
Local name	2-Propanol
BEI	40 mg/l Parameter: Acetone - Medium: urine - Sampling time: End of shift at end of workweek - Notations: B, Ns
Regulatory reference	ACGIH 2025
USA - OSHA - Occupational Exposure Limits	
Local name	Isopropyl alcohol
OSHA PEL TWA	980 mg/m³
	400 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

8.2. Appropriate engineering controls

- Appropriate engineering controls : Ensure good ventilation of the work station. Emergency eye wash fountains should be available in the immediate vicinity of any potential exposure.
- Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment

Hand protection:
Wear suitable gloves resistant to chemical penetration. ISO 374-1

Scratch Fix®

Safety Data Sheet

according to US OSHA HazCom 2024

Eye protection:
Chemical goggles or safety glasses. ISO 16321-1
Skin and body protection:
Long sleeved protective clothing
Respiratory protection:
In case of insufficient ventilation, wear suitable respiratory equipment. respirator with combination filter for vapor/particles. Approved organic vapor respirator

Other information:

Do not eat, drink or smoke during use.

SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
Color	: brown
Odor	: Alcohol-like
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Explosion limits	: No data available
Particle characteristics	: No data available

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10 Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapor.

10.2. Chemical stability

The product is stable at normal handling and storage conditions.

10.3. Possibility of hazardous reactions

None under normal conditions.

Scratch Fix®

Safety Data Sheet

according to US OSHA HazCom 2024

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Strong oxidizers.

10.6. Hazardous decomposition products

Toxic fumes may be released. Thermal decomposition can lead to the release of irritating gases and vapors.

SECTION 11 Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : No data available (Based on available data, the classification criteria are not met)
Acute toxicity (dermal) : No data available (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation) : No data available (Based on available data, the classification criteria are not met)

Ethyl alcohol (64-17-5)

LD50 oral rat	7060 mg/kg (Source: NLM_CIP)
LD50 oral	10470 mg/kg body weight
LD50 dermal	15800 mg/kg body weight
LC50 Inhalation - Rat	133.8 mg/l/4h
LC50 Inhalation - Rat (Dust/Mist)	> 99999 mg/l
LC50 Inhalation - Rat (Vapors)	116.9 mg/l Source: ECHA

1-Ethoxy-2-propanol (1569-02-4)

LD50 oral rat	4400 mg/kg (Source: NLM_CIP)
LD50 dermal rabbit	8100 mg/kg (Source: NLM_CIP)
LC50 Inhalation - Rat	> 9.59 mg/l/4h

1-methoxy-2-propanol, monopropylene glycol methyl ether (107-98-2)

LD50 oral rat	5000 mg/kg (Source: JAPAN_GHS)
LD50 dermal rabbit	13 g/kg (Source: NLM_CIP)
LC50 Inhalation - Rat	> 6 mg/l/4h
LC50 Inhalation - Rat [ppm]	> 7559 ppm (Exposure time: 6 h Source: OECD_SIDS)
ATE US (oral)	5000 mg/kg body weight
ATE US (dermal)	13000 mg/kg body weight

propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)

LD50 oral rat	> 4396 mg/kg body weight
LD50 dermal rabbit	> 12800 mg/kg body weight
LC50 Inhalation - Rat	> 20 mg/l/4h
ATE US (oral)	20000 mg/kg body weight
ATE US (dermal)	20800 mg/kg body weight

Skin corrosion/irritation : No data available (Based on available data, the classification criteria are not met)

Scratch Fix®

Safety Data Sheet

according to US OSHA HazCom 2024

Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: No data available (Based on available data, the classification criteria are not met)
Carcinogenicity	: No data available (Based on available data, the classification criteria are not met)

propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)

IARC group	3 - Not classifiable
Reproductive toxicity	: No data available (Based on available data, the classification criteria are not met)
STOT-single exposure	: May cause drowsiness or dizziness.

Propanol, 1(or 2)-ethoxy- (52125-53-8)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

1-Ethoxy-2-propanol (1569-02-4)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

1-methoxy-2-propanol, monopropylene glycol methyl ether (107-98-2)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

STOT-repeated exposure : No data available (Based on available data, the classification criteria are not met)

Ethyl alcohol (64-17-5)

NOAEL (subchronic,oral,animal/male,90 days)	< 9700 mg/kg body weight Animal: mouse, Animal sex: male, Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)
NOAEL (subchronic,oral,animal/female,90 days)	> 9400 mg/kg body weight Animal: mouse, Animal sex: female, Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)

Aspiration hazard : No data available (Based on available data, the classification criteria are not met)

Ethyl alcohol (64-17-5)

Viscosity, kinematic	1.369 mm ² /s
----------------------	--------------------------

Symptoms/effects after inhalation	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Eye irritation.
Other information	: This SDS has been prepared detailing the hazards of the ink. This product is considered in an article and the ink is hermetically sealed within the pen. Therefore, exposure to the ink is not anticipated under normal and typical conditions of use.

SECTION 12 Ecological information

12.1. Ecotoxicity

Hazardous to the aquatic environment, short-term (acute)	: Not a OSHA HazCom 2024 hazard endpoint
Hazardous to the aquatic environment, long-term (chronic)	: Not a OSHA HazCom 2024 hazard endpoint

12.2. Persistence and degradability

Scratch Fix®

Persistence and degradability	Not established.
-------------------------------	------------------

Scratch Fix®

Safety Data Sheet

according to US OSHA HazCom 2024

Ethyl alcohol (64-17-5)	
Persistence and degradability	Rapidly degradable
Propanol, 1(or 2)-ethoxy- (52125-53-8)	
Persistence and degradability	Rapidly degradable
1-Ethoxy-2-propanol (1569-02-4)	
Persistence and degradability	Rapidly degradable
1-methoxy-2-propanol, monopropylene glycol methyl ether (107-98-2)	
Persistence and degradability	Rapidly degradable
Cobaltate(4-), bis[2-[[[3-[[1-[[[2-chlorophenyl]amino]carbonyl]-2-oxopropyl]azo]-4-hydroxyphenyl]sulfonyl]amino]benzoato(3-)]-, tetrasodium (70851-34-2)	
Persistence and degradability	Rapidly degradable
propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)	
Persistence and degradability	Rapidly degradable

12.3. Bioaccumulative potential

Ethyl alcohol (64-17-5)	
Partition coefficient n-octanol/water (Log Pow)	-0.35 (at 24 °C (at pH 7.4)
1-Ethoxy-2-propanol (1569-02-4)	
BCF - Fish [1]	(1 dimensionless)
1-methoxy-2-propanol, monopropylene glycol methyl ether (107-98-2)	
BCF - Fish [1]	(2 dimensionless)
Partition coefficient n-octanol/water (Log Pow)	< 1 (at 20 °C (at pH 6.8)
propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)	
Partition coefficient n-octanol/water (Log Pow)	0.05
Partition coefficient n-octanol/water (Log Kow)	< 1
Bioaccumulative potential	No bioaccumulation.

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Ozone	: Not a OSHA HazCom 2024 hazard endpoint
Fluorinated greenhouse gases	: No
Other information	: Avoid release to the environment.

SECTION 13 Disposal considerations

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
Additional information	: Flammable vapors may accumulate in the container.
Ecological waste information	: Avoid release to the environment.

Scratch Fix®

Safety Data Sheet

according to US OSHA HazCom 2024

SECTION 14 Transport information

In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG	IATA
14.1. UN number			
Not regulated for transport			
14.2. Proper Shipping Name			
Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)			
Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group			
Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards			
Not regulated	Not regulated	Not regulated	Not regulated
This product is classified as an article, with the ink hermetically sealed within the pen. As a result, exposure to the ink is not anticipated under normal conditions of use. Therefore, the pens containing the ink are not classified as hazardous for transport.			

SECTION 15 Regulatory information

15.1. Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, except for:

1-Ethoxy-2-propanol	CAS-No. 1569-02-4	0 – 10%
---------------------	-------------------	---------

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

propan-2-ol, isopropyl alcohol, isopropanol	CAS-No. 67-63-0	2.5 – 10%
---	-----------------	-----------

15.2. International regulations

No additional information available

15.3. State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

Component	State or local regulations
Ethyl alcohol(64-17-5)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Minnesota - Hazardous Substance List; U.S. - Massachusetts - Right To Know List; U.S. - Maine - Chemicals of Concern
Propanol, 1(or 2)-(2-methoxymethylethoxy)-(34590-94-8)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Minnesota - Hazardous Substance List; U.S. - Massachusetts - Right To Know List

Scratch Fix®

Safety Data Sheet

according to US OSHA HazCom 2024

Component	State or local regulations
1-methoxy-2-propanol, monopropylene glycol methyl ether(107-98-2)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Minnesota - Hazardous Substance List; U.S. - Massachusetts - Right To Know List
Sodium sulfate(7757-82-6)	U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List; U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
propan-2-ol, isopropyl alcohol, isopropanol(67-63-0)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York City - Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16 Other information

according to US OSHA HazCom 2024.

Revision date

: 18 February 2025

Issue date

: 18 February 2025

Other information

: None.

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.