

8740 B VDE HF Zyklop Hex bit socket, insulated, with holding function, 3/8" drive, 8 x 59 mm



EAN:	4013288210166	Size:	160x120x23 mm
Part number:	05004903001	Weight:	65 g
Article number:	8740 B VDE HF	Country of origin:	CZ
		Customs tariff number:	82079030

- Individually tested tools as per IEC 60900 at 10,000 V for safe working up to 1,000 volt
- Extremely short and compact insulated 3/8" bit socket for easy working even in very confined spaces
- Increased safety thanks to 2-component insulation with a yellow insulation core under an outer red insulation layer
- The holding function holds screws securely on the tool
- Plastic sleeve protects surfaces from damage

VDE 3/8" bit socket with holding function for particularly comfortable screwdriving with reduced risk of screw loss when feeding to the component. With increased safety due to yellow insulation core, which becomes visible in case of damage to the outer red VDE insulation layer. Individually tested tool as per IEC 60900 at 10,000 V for safe working at the approved voltage of 1,000 V.

Web link
<https://www.wera.de/en/05004903001>

Wera - 8740 B VDE HF
05004903001 - 4013288210166

Wera Werkzeuge GmbH
Korzter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

Increased safety



The Zyklop sockets and extensions for electricians offer increased safety thanks to their 2-component insulation with a yellow insulation core under an outer red insulation layer.

Bit sockets with retaining function for hexagon socket screws







The clamping of the screw is achieved by a flexible locking ball. The holding function is especially helpful in confined, hard-to-reach spaces, where there is no room for a second hand to secure the screw.

Hex-Plus



Hexagon socket screws are a problem, because the contact surfaces that transfer the force of the tool to the screw are very narrow. The consequence: the head of the screw can be damaged, usually rounding out the recess. Hex-Plus tools have larger contact surfaces to prevent this, driving from the flats of the recess, rather than the corners. Good to know: Hex-Plus tools fit into every standard hexagon socket screw!

Further versions in this product family:

	 mm	 mm	 mm	 mm
05004900001	4.0	55.0	23.0	9.0
05004901001	5.0	55.0	23.0	9.0
05004902001	6.0	55.0	23.0	9.0
05004903001	8.0	59.0	23.0	13.0

Web link

<https://www.wera.de/en/05004903001>

Wera - 8740 B VDE HF
05004903001 - 4013288210166

Wera Werkzeuge GmbH
Korzter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de